

**WEST 1/16TH CORNER SOUTHWEST QUARTER OF SECTION 10, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 29, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 29 DATED APRIL 25, 1870 TO ESTABLISH THE CORNERS OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 9-19-11, SAID THAT **HE SET A STONE** FOR THE PERMANENT 1/2/4 CORNER ON THE EAST SIDE OF THE SOUTHEAST 1/4 OF SECTION 9 ON LINE AND HALFWAY BETWEEN THE STONES HE FOUND AT THE EAST 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 9 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:

- 1) 1,323' NORTH TO THE STONE FOUND AT THE EAST 1/4 CORNER OF SECTION 9
 - 2) 1,323' SOUTH TO THE STONE FOUND AT THE SOUTHEAST CORNER OF SEC. 9
- 2) LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A LEGAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 37 DATED JUNE 15, 1960 TO LOCATE THE BOUNDARIES OF LOT 165 ON WALNUT STREET IN WHITCOMB'S ADDITION, SHOWS A **SPIKE & WASHER IN PAVEMENT** AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 9 AT THE INTERSECTION OF 9TH AVENUE AND WEST STREET ON THIS **PERMANENT SURVEY**.
HIS DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 1,323.7' NORTH TO A SPIKE & WASHER IN PAVEMENT AT THE NORTHEAST CORNER OF THE NE1/4 SE1/4 OF SECTION 9
 - 2) 1,329.8' WEST TO AN IRON PIN IN PAVEMENT AT THE SOUTHWEST CORNER OF THE NE1/4 SE1/4 OF SECTION 9

WEST SIXTEENTH CORNER SOUTHWEST QUARTER SECTION 10-19-11