

**NORTH 1/16<sup>TH</sup> CORNER NORTHWEST QUARTER OF SECTION 11, TOWNSHIP 19 SOUTH,  
RANGE 11 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 93 RECORDED IN SURVEY BOOK "A" ON PAGES 186, 187 & 188 DATED FEBRUARY 21, 1869 TO SURVEY THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 11-19-11 INTO 5 ARE LOTS, MORE OR LESS, LEAVING 40 FEET ON THE EAST AND 40 ON THE SOUTHERN BOUNDARY, AND A STREET 80 FEET IN THE CENTER OF LOT RUNNING NORTH AND SOUTH, AND ALSO A STREET 60 FEET IN WIDTH IN THE MIDDLE ON THE NORTH SIDE OF THE NORTH EAST LOT AS PER THE APPLICATION OF C. C. KNOTT, SAID THAT **HE SET A STONE** FOR THE 1/2/4 CORNER ON THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 11 EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER AND THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNERS OF SECTION 11-19-11 ON THIS SURVEY.
  
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED AUGUST 31, 2004, FOR PROJECT NUMBER 04233-02, SAID THAT **HE FOUND A 1/2" REBAR** AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 11-19-11.
  - 1) 46.0' SW TO THE NEAR FACE OF A PIPE GATE POST
  - 2) 38.1' SSW TO THE NEAR FACE OF A PIPE GATE POST
  - 3) 14.7' SSE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 4) 4.5' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL ROAD 180 EAST-WEST
  - 5) 3.0' EAST TO A FENCE LINE TO THE SOUTH

NORTH SIXTEENTH CORNER NORTHWEST QUARTER SECTION 11-19-11