

WEST 1/4 CORNER SECTION 12, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 356 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 16" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 11 & 12-19-11 ON MARCH 18, 1857.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 30" X 20" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-19-11
 - 2) 40.00 CHAINS SOUTH TO THE 24" X 20" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14-19-11

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 20 RECORDED IN SURVEY BOOK "A" ON PAGE 116 DATED FEBRUARY 26 & 27, 1868 FOR A SURVEY OF ELWOOD CHAPMAN'S AND HENRY HENSHAW'S LAND, BEING THE SOUTHEAST 1/4 OF SECTION 12-19-11, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 12-19-11 ON THIS SURVEY.
HIS SURVEY SHOWS THE FOLLOWING INFORMATION:
 - 1) 322 RODS, 10-3/4 LINKS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 12-19-11 ON THE RANGE LINE

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 30 RECORDED IN SURVEY BOOK "A" ON PAGE 125 DATED MARCH 31, 1868 FOR S SURVEY OF FRAKER'S AND TNASK'S LAND CONTAINED IN THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 11-19-11, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 11-19-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 157 RODS, 11 LINKS WEST TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 11-19-11
 - 2) 317 RODS, 11 LINKS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 11-19-11

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 61 DATED JUNE 13, 1883 FOR A ROAD IN TOWNSHIP 19, RANGE 11 FOR WALTER M. WRIGHT, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 11-19-11 ON THIS ROAD SURVEY. THERE WAS NO WIDTH RECORDED ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 34.8 RODS TO THE CENTER OF THE TRACK OF THE A. T. & S. F. RAILROAD ON A FILL OF ABOUT 8', AND CONTINUES NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 11-91-11 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 160 RODS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 11-19-11 TO COMMENCE THIS ROAD SURVEY

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 233 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 518 TO 520 PETITIONED BY WALTER M. WRIGHT AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-11 [PACKET 456 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 13 1883, AND WAS ESTABLISHED AT 40 FEET WIDE ON JULY 6, 1883 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS AND ATTESTED TO BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 11-19-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 34.8 RODS TO THE CENTER OF THE TRACK OF THE A. T. & S. F. RAILROAD ON A FILL OF ABOUT 8', AND CONTINUES NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 11-91-11 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 160 RODS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 11-19-11 TO COMMENCE THIS ROAD SURVEY
- 6) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 445 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 45 THROUGH 48 PETITIONED BY WALTER M. WRIGHT AND OTHERS FOR A ROAD IN TOWNSHIP 19-11 [PACKET 683 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 13, 1898, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 7, 1898 AS NOTED BY JACOB JACOB, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED TO BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON JANUARY 4, 1900 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 12-19-11 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE EAST AND WEST CENTER LINE OF SECTION 12-19-11 SHALL BE THE NORTH LINE OF SAID ROAD FROM THE WEST 1/4 CORNER OF SECTION 12-19-11 TO A POINT 50 FEET WEST OF THE CENTER CORNER OF SAID SECTION 12-19-11, THENCE NORTHEASTERLY TO THE CENTER CORNER OF SAID SECTION 12, AND FROM THE CENTER CORNER OF SAID SECTION 12 IT SHALL BE 20 FEET ON EACH SIDE OF SAID EAST AND WEST CENTER LINE OF SAID SECTION 12-19-11 TO THE EAST SIDE OF SAID SECTION 12-19-11 AT THE TERMINUS OF SAID ROAD
- 7) J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A PERMANENT SURVEY RECORDED IN SURVEY BOOK 1 ON PAGE 81 AND DATED APRIL 1911, FOR A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "E" ON PAGE 20, SAID THAT **HE FOUND A 4" X 14" X 18" SANDSTONE AT 12" DEEP** AT THE WEST 1/4 CORNER OF SECTION 12-19-11 ON THIS **PERMANENT SURVEY**. HE SAID THAT AT THE EAST SIDE OF THE SANDSTONE AT 24" DEEP IS A **3-1/2" X 12" X 8" LIMESTONE** WHICH HE DETERMINED WAS THE **UPPER PORTION OF THE GLO STONE**.

- 8) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 128 DATED JUNE 12, 1911 TO ASCERTAIN THE CENTERLINE OF THE ROAD ON THE WEST SIDE OF THE NORTHWEST 1/4 OF SECTION 12, SAID THAT **HE SET A 12" X 6" X 4" STONE** ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 12-19-11 AND THE STAKE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 12-19-11 ON THIS ROAD SURVEY. HE DOES **NOT** CALL THIS STONE THE WEST 1/4 CORNER OF SECTION 12-19-11.

HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323' NORTH TO THE 12" X 8" X 6" STONE HE SET FOR THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 12-19-11
- 2) 2,170.5' NORTH TO THE STONE HE FOUND IN PLACE
- 3) 2,646' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 12-19-11
- 4) 2,646' SOUTH TO THE SOUTHWEST CORNER OF SECTION 12-19-11, WHERE LINE COINCIDES WITH THE STAKE HE SET FOR SAID CORNER

CONTINUED ON PAGE 3

- 9) LARGE SURVEY SR #11026 IN THE SURVEY DRAWER FOR SECTIONS 11-16 IN TOWNSHIP 19-11 WITH THE LEGEND "PLAT PREPARED BY THE OFFICE OF THE COUNTY ENGINEER" AND DATED OCTOBER 29, 1946, SHOWS A "MONUMENT" AT THE EAST CORNER OF SECTION 11-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
THE SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,640' SOUTH TO THE IRON PIN IN PAVEMENT AT THE SOUTHEAST CORNER OF SECTION 11-19-11
- 10) SURVEY F12006 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR 4 TRACTS IN THE SOUTHWEST 1/4 OF SECTION 12-19-11 WITH NO NAME OR DATE BUT APPARENTLY BY LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, SHOWS A "MONUMENT" AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 12-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
- 11) IN A BROWN FIELD BOOK LABELED "MISC. 1957-1958" IN THE VAULT IN THE COUNTY ENGINEERS OFFICE FOR A SURVEY TO LOCATE THE EAST 1/4 CORNER OF SECTION 11-19-11 ON PAGES 37-38, IT SHOWS THAT **THEY SET A 1/2" SQUARE REBAR** AT THE EAST 1/4 CORNER OF SECTION 11-19-11 ON LINE AND AT 2,647.0 FEET BETWEEN THE NORTHEAST CORNER OF SECTION 11-19-11 AND THE SOUTHEAST CORNER OF SECTION 11-19-11.
- 1) 14.15' EAST TO A SPIKE IN A TELEPHONE POLE
 - 2) 47.5' SE TO A SPIKE IN A POWER POLE
 - 3) 48.5' SW TO A SPIKE IN A POWER POLE
 - 4) 2,647.0' NORTH TO THE NORTHEAST CORNER OF SECTION 11-19-11
 - 5) 2,647.0' SOUTH TO THE SOUTHEAST CORNER OF SECTION 11-19-11
- 12) KDOT PLANS FOR THE 1-35 BY PASS, PROJECT 35-56-I35-2(1)(127)/50-56-F050-5(5) DATED 1963 ON PAGE 26 SHOWS A **1" REBAR BELOW A 4" X 10" LIMESTONE** AT THE WEST 1/4 CORNER OF SECTION 12-19-11.
- 1) 43.57' NORTH OF EAST BOUND CENTERLINE STATION 598+06.37
 - 2) 47.78' SSW TO A SPIKE & WASHER IN A GUY POLE
 - 3) 47.05' SSE TO A SPIKE & WASHER IN A POWER POLE
 - 4) 15.00 EAST TO A SPIKE & WASHER IN A GUY POLE
- 13) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F12014 IN THE SURVEY FILE FOR SECTIONS 1-8, TOWNSHIP 19-11 FOR A PLAT OF SURVEY TO SET THE CORNERS TO A TRACT OF LAND LOCATED IN THE SOUTHWEST 1/4 OF SECTION 12-19-11 FOR BLEVINS DATED SEPTEMBER 14, 1973, SHOWS AN "**IRON PIN**" AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 12-19-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 990' SOUTH TO THE NORTHWEST TRACT CORNER [IRON PIN AT 20' EAST]
 - 2) 1,320' SOUTH TO THE SOUTHWEST TRACT CORNER [IRON PIN AT 20' EAST]

WEST QUARTER CORNER SECTION 12-19-11