

NORTH 1/4 CORNER SECTION 13, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 356 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 13" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 12 & 13-19-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.24 CHAINS WEST TO THE 24" X 20" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14-19-11
 - 2) 40.24 CHAINS EAST TO THE 17" X 13" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 12 & 13-19-11 ON THE EAST TOWNSHIP LINE

 - 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 20 RECORDED IN SURVEY BOOK "A" ON PAGE 116 DATED FEBRUARY 26 & 27, 1868 FOR A SURVEY OF ELWOOD CHAPMAN'S AND HENRY HENSHAW'S LAND, BEING THE SOUTHEAST 1/4 OF SECTION 12-19-11, SAID THAT HE FOUND THE STONE **MISSING** AT THE SOUTH 1/4 CORNER OF SECTION 12-19-11 ON THIS SURVEY. **HE SET A STONE** FOR THE SOUTH 1/4 CORNER OF SECTION 12-19-11 ON TRUE LINE AND EQUIDISTANT BETWEEN THE SOUTHWEST CORNER AND THE SOUTHEAST CORNER OF SECTION 12-19-11 ON THE RANGE LINE.

 - 3) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** FOR ROAD 662 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 81 FOR H. M. SLATER, PRINCIPAL PETITIONER, FOR THE SURVEY OF A ROAD TO BE WIDENED ON THE 1/2 SECTION LINE RUNNING EAST AND WEST THROUGH SECTION 13-19-11, SAID THAT **HE FOUND THE GOVERNMENT STONE SHOWING AT THE SURFACE** AT THE 1/4 CORNER ON THE NORTH SIDE OF SECTION 13-19-11 ON THIS **PERMANENT SURVEY**. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 14-19-11 TO SET A STAKE FOR THE TRUE NORTHWEST CORNER OF SECTION 13-19-11. THE SURVEY WAS MADE MARCH 15, 22, 23, & 24, 1911 AND ENTERED ON MAY 5, 1911. HE NOTED IN THE UPPER RIGHT CORNER THAT THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "E" ON PAGE 19.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,627-6/12' WEST TO THE STAKE HE SET FOR THE TRUE NORTHWEST CORNER OF SECTION 13-9-11
 - 2) 5,285' WEST TO THE ORIGINAL GOVERNMENT STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 14-19-11

 - 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY HOWARD C. BROWN, DEPUTY COUNTY SURVEYOR, ON A SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 4 DATED JUNE 6, 1914, ON ORDERS OF THE BOARD OF COUNTY COMMISSIONERS TO LOWER THE STONE AT THE 1/4 CORNER BETWEEN SECTIONS 12 & 13-19-11, TOOK W. S. RUGGLES, COUNTY ENGINEER AS A WITNESS. THEY LIFTED THE LARGE STONE WHICH WAS SUPPOSED TO BE THE 1/4 CORNER, AND FOUND A LIMESTONE DIRECTLY UNDER SAID LARGE STONE, WHICH THEY TOOK TO BE **THE ORIGINAL GOVERNMENT STONE** SET IN THE GROUND IN THE PROPER CONDITION. THEY TOOK THE LARGE STONE THAT HAD BEEN OVER THE GOVERNMENT STONE AND THEY SET IT ON A LINE BETWEEN THE 1/4 CORNER AND A HEDGE FENCE RUNNING NORTH AND SOUTH ON THE SOUTH SIDE OF THE ROAD, AND 22 FEET 7 INCHES SOUTH OF THE 1/4 CORNER AS A **WITNESS STONE**.

 - 5) IN A FIELD BOOK LABELED "CHAINING SECTION "C" SURVEY NOTES 102-A" IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE DATED 1919, ON PAGE 22 IT SHOWS A **STONE** AT THE SOUTH 1/4 CORNER OF SECTION 12-19-11.
- TIES ARE ON PAGE 2

- 1) 3.4' RIGHT OF SURVEY LINE
 - 2) REFERENCE STAKES SET 39.0' NW AND 46.0' SW
 - 3) IN LINE WITH A HEDGE TO THE RIGHT
 - 4) 4.5' SOUTH OF A LINE OF HEDGE TO THE LEFT
- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS A **STONE** AT THE "S1/4 CORNER SECTION 12-19-11".
- 1) 3.4' SOUTH TO THE CENTERLINE OF THE ROAD FROM THE ALIGNMENT NOTES OF 1919
- 7) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #12001 IN THE SURVEY DRAWER FOR SECTIONS 11-14 IN TOWNSHIP 19-11 DATED MARCH 1965, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN IN PAVEMENT** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 12-19-11. THERE ARE NO TIES ON THE SURVEY.
- 8) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F12009 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR A SURVEY SHOWING THE LOCATION OF A BUILDING IN THE SOUTHWEST 1/4 OF SECTION 12-19-11 DATED NOVEMBER 24, 1967, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 12-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 33' NORTH TO THE "MONUMENT" HE SET ON THE RIGHT-OF-WAY LINE – NOT DESCRIBED
 - 2) 155.85' WEST TO THE "MONUMENT" HE SET FOR THE SOUTHEAST TRACT CORNER AT THE INTERSECTION OF A "PUBLIC STREET" – NOT DESCRIBED
 - 3) 300.85' WEST TO THE "MONUMENT" HE SET FOR THE SOUTHWEST TRACT CORNER AS WITNESSED BY THE "MONUMENT" HE SET AT 33' NORTH – NOT DESCRIBED
- 9) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F12011 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR A SURVEY SHOWING THE BOUNDARIES OF FOUR TRACTS IN THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 12-19-11 INCLUDING THE CHURCH PROPERTY DATED JANUARY 15, 1970, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 12-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 33' NORTH TO THE "MONUMENT" HE SET ON THE RIGHT-OF-WAY LINE – NOT DESCRIBED
- 10) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F12012 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR A PLAT OF SURVEY TO LOCATE THE CORNERS OF A TRACT OF GROUND LOCATED IN THE SOUTHWEST 1/4 OF SECTION 12-19-11 WITH NO DATE, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 12. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 814' NORTH TO THE "MONUMENT" HE SET FOR A TRACT CORNER – NOT DESCRIBED

HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) 300.85' WEST TO THE SOUTHEAST TRACT CORNER AS WITNESSED BY THE "MONUMENT" HE SET AT 33' NORTH – NOT DESCRIBED
 - 3) 400.85' WEST TO THE SOUTHWEST TRACT CORNER AS WITNESSED BY THE "MONUMENT" HE SET AT 33' NORTH – NOT DESCRIBED
- 11) C. MICHAEL BUTLER, P.E. 6562 OF SCHWAB-EATON, P.A. IN THE *FINAL PLAT OF KENSINGTON ADDITION* DATED NOVEMBER 1977, SHOWS ON HIS PLAT A "**MONUMENT FOUND**" AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 13-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,654.86' WEST TO THE "MONUMENT" HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 13-19-11 – NOT IDENTIFIED
- 12) GREGORY ALAN MILES, L.S. 667, IN SURVEY F12004 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11, FOR A SURVEY OF A 2.79 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 12-19-11 FOR PROJECT NUMBER 82-199 DATED JANUARY 1983 AND RECORDED IN VOLUME 395 ON PAGE 858 IN THE REGISTER OF DEEDS OFFICE ON FEBRUARY 3, 1983, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 12-19-11. HE DOES NOT DESCRIBE THE MONUMENT IN HIS LEGEND AND THERE ARE ON TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 32.84' NORTH TO THE PIN HE FOUND AT THE SOUTHEAST CORNER OF THE 2.79 ACRE TRACT
 - 2) 813.78' NORTH TO THE PIN HE FOUND AT THE NORTHEAST CORNER OF THE 2.79 ACRE TRACT
- 13) JOHN R. YOUNG, L.S. 112, OF SCHWAB-EATON, P.A., IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 13, 1997, FOR THE FINAL PLAT OF SKYVIEW SUBDIVISION UNIT ONE, SAID THAT **HE FOUND A 2" DISC IN THE CONCRETE PAVEMENT AT 2" BELOW THE PAVEMENT SURFACE** AT THE NORTH 1/4 CORNER OF SECTION 13-19-11.
- 1) 30.6' SOUTH TO A SPIKE & WASHER IN THE TOP OF A FENCE POST
 - 2) 36.3' NW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 3) 78.4' NE TO THE TOP EAST END OF A 12" CORRUGATED METAL PIPE CULVERT
 - 4) 3.0' NORTH TO THE CENTERLINE TRAVELED WAY OF ROAD 170 [OLD-OLD HIGHWAY 50] OR EAST 6TH STREET
 - 5) STATE PLANE COORDINATES IN U.S. FEET – GROUND LEVEL
NORTH = 1953810.951 EAST = 1987604.879
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,660.41' EAST TO THE "SECTION CORNER" HE FOUND AT THE NORTHEAST CORNER OF SECTION 13-19-11 – NOT IDENTIFIED
 - 2) 2,682.60' SOUTH TO THE "SECTION CORNER" HE FOUND AT THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 13-19-11 – NOT IDENTIFIED
- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 15, 2000, FOR JOB NUMBER 00089-02, SURVEY F12016 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR THREE TRACTS IN THE SOUTHWEST QUARTER OF SECTION 12-19-11, SAID THAT **HE FOUND THE 1-1/2" IRON PIN** AT THE SOUTH 1/4 CORNER OF SECTION 12-19-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE. SEE ALSO THE *FINAL PLAT OF R. L. JOHNSON SUBDIVISION* IN THE SURVEY DRAWER FOR SECTIONS 11-16 IN TOWNSHIP 19-11 FOR THIS PROJECT NUMBER.

HIS TIES ARE ON PAGE 4

- 1) 40.5' SW TO A NAIL & WASHER IN A POWER POLE
- 2) 33.9' NW TO A NAIL & WASHER IN A POWER POLE
- 3) 3.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 170; OLD-OLD HIGHWAY 50; OR EAST 6TH STREET

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,651.59' NORTH TO THE SQUARE #4 REBAR HE FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 12-19-11
- 2) 670.85' WEST TO THE NAIL IN THE ROAD HE SET FOR A TRACT CORNER
- 3) 720.85' WEST TO THE SOUTHEAST CORNER OF TRACT TWO
- 4) 860.85' WEST TO THE SOUTHWEST CORNER OF TRACT TWO
- 5) 990.00' WEST TO THE NAIL IN THE ROAD HE SET FOR THE SOUTHWEST CORNER OF TRACT ONE
- 6) 2,654.23' WEST TO THE 5/8" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 12-19-11

- 15) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 14, 2003, FOR PROJECT NUMBER 03072-02, SAID THAT **HE FOUND THE 1-1/2" IRON PIN** AT THE SOUTH 1/4 CORNER OF SECTION 12-19-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED MAY 2000. SEE ALSO THE *FINAL PLAT OF DEFOOR SUBDIVISION* IN THE SURVEY DRAWER FOR SECTIONS 11-16 IN TOWNSHIP 19-11 FOR THIS PROJECT NUMBER.

- 1) 40.5' SW TO A 40 D NAIL & WASHER IN A POWER POLE
- 2) 33.9' NW TO A 40 D NAIL & WASHER IN A POWER POLE
- 3) 28.4' NORTH TO THE NEAR FACE OF A SIGN POST "KEEP OUT NO TRESPASSING"
- 4) 3.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
- 5) 1.0' WEST TO A LINE OF RAILROAD TIES TO THE NORTH-EXTENDED

HIS PLAT DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,654.23' WEST TO THE 5/8" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 12-19-11

NORTH QUARTER CORNER SECTION 13-19-11