

NORTH 1/16TH CORNER SOUTHWEST QUARTER OF SECTION 13, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED APRIL 15, 1998, FOR PROJECT NUMBER 98132-02, SAID THAT **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE NORTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 13.
 - 1) 20.80' NE TO A 40 D SPIKE & WASHER IN A FENCE POST
 - 2) 66.00' ENE TO A 40D SPIKE & WASHER IN A POWER POLE
 - 3) 45.3' SSE TO A 40 D SPIKE & WASHER IN A 2' TREE
 - 4) 20' DUE SOUTH TO A WITNESS CORNER IN THE DITCH
 - 4) 4.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST

- 2) TIM SLOAN, L.S. 783, IN A *NOTICE OF COMPLETION OF ENDANGERMENT ACTIVITY AND REPORT OF RESTORATION* SECTION CORNER REPORT DATED JANUARY 17, 2003, STATED THAT **THE ORIGINAL MONUMENT IS STILL IN PLACE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 13. HE SAID THAT IT WAS CHECKED AFTER THE CONSTRUCTION PROJECT WAS COMPLETED. **METRIC TIES:**
 - 1) 12.11 METERS NE TO A PK NAIL IN A TIMBER POLE [SOUTH FACE]
 - 2) 8.91 METERS SSE TO A PK NAIL IN A 750 MM ELM TREE
 - 3) 22.37 METERS SE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) 6.60 METERS NW TO A "+" CUT IN THE CENTER OF A CURB INLET
 - 5) 0.3 METERS SOUTH TO THE CENTERLINE OF SOUTH AVENUE BEARING EAST-WEST

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED FEBRUARY 26, 2003, FOR PROJECT NUMBER 02492-02, SURVEY F13012 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR A SURVEY OF THE NORTHEAST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 13-19-11, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE NORTH 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 13 FROM EXISTING REFERENCE TIES.
 - 1) 20.0' SOUTH TO 1/2" REBAR WITH AN HIS CAP FOUND
 - 2) 29.45' SSE TO A MAG NAIL IN A 24" TREE
 - 3) 73.40' SE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) 50.7' NW TO THE TOP BOLT ON A FIRE HYDRANT
 - 5) 27.0' NNE TO A CONCRETE NAIL IN A POLE
 - 6) 21.65' NW TO A PLUS "+" CUT IN THE TOP OF AN INLET IN THE CENTER OF THE SOUTH SIDE
 - 7) 24.6' SE TO THE SOUTHEAST CORNER OF AN INLET
 - 8) 4.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE EAST-WEST ROAD**HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:**
 - 1) 1,320.26' SOUTH TO A 5/8" REBAR WITH "BOOKER RATCLIFF" CAP FOUND A THE SOUTHWEST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 13
 - 2) 1,329.09' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 13

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED FEBRUARY 05, 2008, FOR PROJECT NUMBER 07442-02, THE FINAL PLAT OF EAST PARK III SUBDIVISION, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE NORTH 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 13 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.

HIS TIES ARE ON PAGE 2

- 1) 20.0' SOUTH TO 1/2" REBAR WITH AN HIS "LS 752" CAP FOUND
 - 2) 29.45' SSE TO A MAG NAIL IN A 24" TREE
 - 3) 73.40' SE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) 50.7' NW TO THE TOP BOLT ON A FIRE HYDRANT
 - 5) 27.10' NNE TO A CONCRETE NAIL IN A POLE
 - 6) 21.65' NW TO A PLUS "+" CUT IN THE TOP OF AN INLET IN THE CENTER OF THE SOUTH SIDE
 - 7) 24.6' SE TO THE SOUTHEAST CORNER OF AN INLET
 - 8) 4.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE EAST-WEST ROAD
- HIS PLAT DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,329.20' WEST TO A 1/2" REBAR IN A MONUMENT WELL FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 13
- 2) 1,329.09' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 13

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER SECTION 13-19-11