

**NORTH 1/16TH CORNER NORTHWEST QUARTER OF SECTION 14, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 133, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 214 ORDERED BY W. H. JOHNSON DATED OCTOBER 6 & 7, 1905 FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF A TRACT OF LAND DESCRIBED AS FOLLOWS: BEGINNING 49 RODS AND 8-1/2 LINKS EAST AND 40 RODS NORTH OF THE SOUTHWEST CORNER OF SECTION 11-19-11, THENCE WEST 134 FEET, THENCE NORTH 100 FEET, THENCE EAST 134 FEET, THENCE NORTH 100 FEET, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF THE SOUTHWEST 1/4 OF SECTION 11-19-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 495.1' WEST TO THE GAS PIPE HE DROVE ON THIS PERMANENT SURVEY
 - 2) 629.1' WEST TO THE IRON PIN HE DROVE ON THIS PERMANENT SURVEY
 - 3) 1,315.5' WEST TO THE STONE HE FOUND AT 6TH AVENUE AND EAST STREET [SOUTHWEST CORNER OF SECTION 11-19-11]
 - 4) 1,313.5' EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 11-19-11
- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY HOWARD E. BROWN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 90 DATED MARCH 27, 1914, AT THE REQUEST OF MRS. ELIZA ANN BRADLEY TO MARK THE CORNERS AND BOUNDARIES OF HER TRACT IN THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-9-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 132.55' EAST TO THE 15" X 3" X 3" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE BRADLEY LAND
 - 2) 319.75' EAST TO THE 13" X 5" X 2-1/2" LIMESTONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE BRADLEY LAND
- 3) AI CHAMNESS, DEPUTY COUNTY SURVEYOR FROM 1906 TO 1946, IN A BOOK LABELED "CHAMNESS BOOK Y" IN THE KRETSINGER COLLECTION, ON PAGES 36 TO 39 FOR A SURVEY FOR RAYMOND DATED OCTOBER 28, 1941, SAID THAT **HE FOUND** THIS NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 ON THIS SURVEY. HE DOES NOT IDENTIFY THE MONUMENT THAT HE FOUND AT THIS CORNER.
- 1) 3' NORTH TO THE CENTER JOINT OF THE CONCRETE SLAB
 - 2) 27.33' SW TO A TELEPHONE POLE WHICH IS 1.87' WEST OF THE CONCRETE HEADWALL OF THE WEST END OF A CULVERT
 - 3) 27.92' SE TO THE SOUTHEAST CORNER OF SAME CULVERT
 - 4) 31.87' SE TO THE NEXT TELEPHONE POLE EAST
 - 5) 1,315' EAST OF THE NORTHWEST CORNER OF SECTION 14
 - 6) 1.315' EAST TO THE N1/4 CORNER OF SECTION 14 UNDER THE OVERPASS
- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS A **STONE** AT THE "NE CORNER NW1/4 NW1/4 SECTION 14-19-11".
- 1) 23' SOUTH BY EAST TO A TELEPHONE POLE
 - 2) 40.5' NORTH TO THE SOUTH SIDE OF A MAPLE TREE
 - 3) 44.9' SW TO A CORNER POST SET IN CONCRETE

CONTINUED ON PAGE 2

- 5) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 10 DATED MAY 10, 1955, AT THE REQUEST OF HARRY WATERMAN TO LOCATE AND PERMANENTLY ESTABLISH THE CORNERS OF HIS TRACT OF LAND LOCATED IN THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 14-19-11, SAID THAT HE SET A **TEMPORARY POINT** FOR THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 ON LINE AND HALFWAY BETWEEN THE NORTHWEST CORNER AND THE NORTH 1/4 CORNER OF SECTION 14-19-11 IN THE INTERSECTION OF **SIXTH AVENUE AND PEYTON STREET** TO THE SOUTH ON THIS **PERMANENT SURVEY**. **HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,314.66' WEST TO THE NORTHWEST CORNER OF SECTION 14-19-11 – NOT DESCRIBED
 - 2) 1,314.66' EAST TO THE NORTH 1/4 CORNER OF SECTION 14-19-11 - NOT DESCRIBED
- 6) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #14001 IN THE SURVEY DRAWER FOR SECTIONS 11-14 IN TOWNSHIP 19-11 THAT IS SIGNED BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING A “**MONUMENT**” AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 14-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT AT THIS CORNER.
- 7) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F14032 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR A PLAT OF A SURVEY OF A TRACT IN THE NORTHWEST 1/4 OF SECTION 14-19-11 DATED SEPTEMBER 4, 1970, SHOWS ON HIS SURVEY DRAWING A “**MONUMENT**” AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 IN THE CENTERLINE OF 6TH AVENUE. THERE IS NO DESCRIPTION OF THE MONUMENT AT THIS CORNER.
- 8) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F14031 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR A PLAT OF SURVEY OF A TRACT OF GROUND IN THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 DATED APRIL 4, 1972, SHOWS ON HIS SURVEY DRAWING A “**MONUMENT**” AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION -19-11 AT THE INTERSECTION OF 6TH AVENUE AND PEYTON STREET. THERE IS NO DESCRIPTION OF THE MONUMENT AT THIS CORNER.
- 9) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F14030 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR A PLAT OF SURVEY TO DETERMINE THE CORNERS TO A TRACK OF LAND LOCATED IN THE NORTHWEST 1/4 OF SECTION 14-19-11 DATED FEBRUARY 25, 1974, SHOWS ON HIS SURVEY DRAWING A “**MONUMENT**” AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 IN THE CENTERLINE OF EAST 6TH AVENUE AND PEYTON STREET. THERE IS NO DESCRIPTION OF THE MONUMENT AT THIS CORNER.
- 10) GREGORY ALAN MILES, L.S. 667, IN LARGE SURVEY SR #14030 IN THE SURVEY DRAWER FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR PROJECT NUMBER 81-92 DATED DECEMBER 1981, FOR A BOUNDARY SURVEY FOR THE BUNGE CORPORATION, SHOWS A “**MONUMENT**” AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 14-19-11. HE DOES NOT DESCRIBE THE MONUMENT AT THIS CORNER.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 3

- 1) 1,315.59' WEST TO THE "MONUMENT" AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 14-19-11 – NOT DESCRIBED
 - 2) 1,312.52' SOUTH TO THE "MONUMENT" AT THE SOUTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 14-19-11 – NOT DESCRIBED
- 11) GREGORY ALAN MILES, L.S. 667, IN SURVEY F14045 IN THE SURVEY FILES FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR THE SURVEY OF A 1.15 ACRE TRACT IN THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 14-19-11 FOR MARK II LUMBER FOR PROJECT NUMBER 82-152 DATED OCTOBER 14, 1982 AND RECORDED IN VOLUME 395 ON PAGE 119 IN THE REGISTER OF DEEDS OFFICE ON NOVEMBER 12, 1982, SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 IN THE INTERSECTION OF 6TH AVENUE AND PEYTON STREET. HE DOES NOT DESCRIBE THE MONUMENT IN HIS LEGEND.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 175.00' WEST TO A PIN HE SET FOR THE NORTHEAST TRACT CORNER
 - 2) 324.75' WEST TO A PIN HE PREVIOUSLY SET AND HE FOUND AT THE NORTHWEST TRACT CORNER
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F14051 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR A 1.74 ACRE TRACT IN THE WEST HALF OF THE NORTHWEST 1/4 OF SECTION 14-19-11 DATED JULY 18, 1984 AND RECORDED IN VOLUME 409 ON PAGE 726 IN THE REGISTER OF DEEDS OFFICE ON JULY 30, 1984, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A SPIKE & WASHER IN THE ASPHALT SURFACE TO REPLACE A CONCRETE NAIL THAT HE FOUND** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 AT THE INTERSECTION OF 6TH AVENUE AND PEYTON STREET.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 329.62' SOUTH TO THE P.O.B. OF THE 1.74 ACRE TRACT, AS WITNESSED BY THE #4 REBAR HE FOUND STANDING 19.5' WEST, ASSUMED TO BE ATTRIBUTABLE TO A PERMANENT SURVEY BY GOULD RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 10
 - 2) 539.98' SOUTH TO THE SOUTHEAST CORNER OF THE 1.74 ACRE TRACT, AS WITNESSED BY THE #4 REBAR HE FOUND STANDING 19.5' WEST, ASSUMED TO BE ATTRIBUTABLE TO A PERMANENT SURVEY BY GOULD RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 10
- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F14053 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR A 0.58 ACRE TRACT IN THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 DATED JULY 13, 1984 AND RECORDED IN VOLUME 409 ON PAGE 726 IN THE REGISTER OF DEEDS OFFICE ON JULY 30, 1984, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A SPIKE & WASHER THAT REPLACED A CONCRETE NAIL HE FOUND** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 IN THE CENTERLINE OF PEYTON STREET.
- 14) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN SURVEY F14057 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR THE SURVEY OF A TRACT IN THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 14-19-11 FOR MARK II CORPORATION DATED DECEMBER 22, 1994, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A PK NAIL** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 AT THE INTERSECTION OF 6TH AVENUE AND PEYTON STREET.

CONTINUED ON PAGE 4

- 15) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN SURVEY F14058 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR THE SURVEY OF A TRACT IN THE EAST HALF OF THE NORTHWEST QUARTER OF SECTION 14-19-11 FOR HOPKINS MANUFACTURING CORPORATION, INC. DATED JULY 7, 1995, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A CONCRETE NAIL** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 AT THE INTERSECTION OF *6TH AVENUE AND PEYTON STREET*.
- 16) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F14062 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR THE SURVEY OF A TRACT IN THE NORTHWEST QUARTER OF SECTION 14-19-11 FOR PROJECT NUMBER 95132-02 DATED AUGUST 17, 1995, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A PK NAIL** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-19-11.
- 17) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN SURVEY F14059 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11 FOR THE SURVEY OF A 4.92 ACRE TRACT IN THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 14-19-11 FOR MARK II CORPORATION DATED SEPTEMBER 1, 1995, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A CONCRETE NAIL** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-19-11 AT THE INTERSECTION OF *6TH AVENUE AND PEYTON STREET*.
- 18) JOHN H. LILAK, L.S. 1287, OF TRANSYSTEMS CORP, FOR JOB NUMBER 50-56-K-6829-01 FOR KDOT DATED DECEMBER 9, 1999, IN A LAND SURVEY REFERENCE REPORT SAID THAT **HE FOUND A 1/2" CAPPED BAR [BROSEMER LS 752] FLUSH WITH THE PAVEMENT** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 14 FROM LAND SURVEY REFERENCE REPORT TIES OF RECORD AND SURVEYS OF RECORD AT *EAST 6TH AVENUE AND PEYTON STREET*. KDOT CORNER NUMBER 14351
- 1) NAD 1983 MODIFIED GROUND COORDINATE: CAF = 0.09992180
NORTH = 595528.390 METERS EAST = 603859.275 METERS
 - 5) 40.34' SE TO A NAIL & WASHER IN THE NORTH SIDE OF A POWER POLE
 - 3) 28.86' SOUTH TO THE NORTH RIM [NEAR EDGE] OF A SANITARY SEWER MANHOLE
 - 4) 42.68' SW TO A MAG NAIL & SURVEY MARKER DISC IN THE WEST FACE OF A POWER POLE
 - 5) 42.23' NE TO A 16DD NAIL & SHINER IN THE SOUTHWEST FACE OF A POWER POLE
- THE DRAWING SIGNED BY KIM L. HUXMAN, L.S. 975 IN THE BROWN FOLDER FOR THIS PROJECT IN THE SURVEY DRAWER FOR SECTIONS 11-16 IN TOWNSHIP 19-11 DATED FEBRUARY 28, 2000 SHOWS THE FOLLOWING INFORMATION:
- 1) 400.624 METERS WEST TO THE 5/8" IRON BAR WITH A PLASTIC CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 14-19-11
 - 2) 400.767 METERS EAST TO THE IRON BAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 14-19-11
 - 3) 801.779 METERS EAST TO THE 1/4" HEAD COTTON GIN SPINDLE HE FOUND AT THE 1/16TH CORNER ON THE NORTH SIDE OF THE NE1/4 OF SECTION 14-19-11
 - 4) 1,202.751 METERS EAST TO THE 3/4" IRON BAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 14-19-11
- 19) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN AN ALTA/ACSM LAND TITLE SURVEY FOR HOPKINS MANUFACTURING CORPORATION DATED OCTOBER 31, 2000 FOR PROJECT NUMBER 00035-20 IN THE SURVEYING DRAWER FOR SECTIONS 11-14 IN TOWNSHIP 19-11, SHOWS ON HIS SURVEY DRAWING THAT

HE FOUND A DRILL HOLE AND HIS “LS 752” CAP AT THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 14-19-11.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,314.79’ EAST TO THE DRILL HOLE IN THE CONCRETE PAVEMENT WITH A LYON COUNTY CAP UNDER THE OVERPASS AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 14-19-11
 - 2) 2,654.08’ SOUTH TO THE COTTON GIN SPINDLE HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 14-19-11
- 20) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 14, 2002, FOR PROJECT NUMBER 02120-02, SAID THAT **HE FOUND THE 1/2” REBAR WITH HIS “LS 752” CAP AT THE SOUTH 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 11-19-11 FROM A PREVIOUS PROJECT.**
- 1) 29.4’ NNE TO THE CENTER OF A WATER VALVE LID
 - 2) 42.05’ NE TO A 40 D SPIKE & SHINER IN A POWER POLE
 - 3) 40.35’ SE TO A SPIKE & WASHER IN A POWER POLE
 - 4) 42.70’ SW TO A NAIL & PLASTIC SURVEY DISC IN A POWER POLE
- 21) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 12, 2006, FOR PROJECT 05010-04, KDOT PROJECT 50-56 K-6829-01 [2006], SAID THAT **HE SET A 1/2” X 24” REBAR WITH A 2” ALUMINUM CAP IN A MONUMENT WELL FOR THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 14-19-11 AFTER THE CONSTRUCTION PROJECT FROM THE PROJECT CONTROL AND EXISTING REFERENCE TIES.**
- 1) 42.05’ NE TO A NAIL & SHINER IN A POWER POLE
 - 2) 43.90’ SE TO A 1/2” REBAR WITH A 2” ALUMINUM CAP [KDOT RIGHT-OF-WAY MONUMENT]
 - 3) 42.80’ SW TO A MAG NAIL & PLASTIC DISC IN A POWER POLE
 - 4) IN THE CENTERLINE TRAVELED-WAY FOR U. S. 50 HIGHWAY
 - 5) 45.00’ EAST TO THE EDGE OF THE CONCRETE PAVEMENT AT THE CENTERLINE OF U.S. 50 HIGHWAY
 - 6) 98.20’ NNW TO THE SOUTHEAST CORNER OF THE BUILDING FOR “MARY’S PLACE”
 - 7) 0.5’ EAST TO THE CENTER SEAM OF THE CONCRETE PAVEMENT EXTENDED FOR *PEYTON STREET*
- 22) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED FEBRUARY 19, 2013 FOR PROJECT NUMBER 13035-02, A SURVEY OF THE EAST LINE OF A TRACT IN THE WEST HALF OF THE NORTHWEST 1/4 OF SECTION 14-19-11 FOR GLORIA WIETRICK, SURVEY F14078 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11, SAID THAT **HE FOUND THE 1/2” IRON PIN IN A MONUMENT WELL AT THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 SECTION 14-19-11 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE BY DAVIS, L.S. 1368, DATED 2006.**
- 1) 42.05’ NE TO A NAIL & SHINER IN A LARGE POWER POLE [IN FRONT OF THE AMERICAN RED CROSS
 - 2) 43.9’ SE TO A 1/2” IRON PIN WITH AN ALUMINUM CAP [KDOT RIGHT-OF-WAY]
 - 3) 98.2’ NNW TO THE SOUTHEAST CORNER OF A BUILDING [“MARY’S PLACE”]
 - 4) 0.5’ EAST TO THE CENTER SEAM OF THE CONCRETE PAVEMENT EXTENDED FOR *PEYTON STREET* TO THE SOUTH
 - 5) IN THE CENTERLINE TRAVELED AY OF U.S. 50 HIGHWAY
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,322.27’ SOUTH TO THE CALCULATED POSITION FOR THE NORTHEAST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 14-19-11
 - 2) 2,645.08’ SOUTH TO THE COTTON GIN SPINDLE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 14-19-11

- 23) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED APRIL 15, 2015 FOR PROJECT NUMBER 15058, A SURVEY OF A TRACT IN THE WEST HALF OF THE NORTHWEST 1/4 OF SECTION 14-19-11 FOR CHRISTINE MATSON AT 810 EAST SOUTH AVENUE, SURVEY F14079 IN THE SURVEY FILE FOR SECTIONS 11-14 IN TOWNSHIP 19-11, SAID THAT **HE FOUND THE RECORD 1/2" IRON PIN IN A MONUMENT BOX** AT THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 14-19-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE IN 2013.
- 1) 42.05' NE TO A NAIL & SHINER IN A LARGE POLE IN FRONT OF THE RED CROSS BUILDING
 - 2) 43.9' SE TO A 1/2" IRON PIN WITH AN ALUMINUM KDOT CAP FOUND
 - 3) 98.2' NW TO THE SOUTHEAST CORNER OF "MARY'S PLACE" BUILDING
 - 4) 0.5' EAST TO THE CENTERLINE OF PEYTON STREET TO THE SOUTH
 - 5) IN THE CENTERLINE OF 6TH STREET
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,645.03' SOUTH TO THE COTTON GIN SPINDLE HE FOUND AT THE SOUTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 14-19-11 IN INTERSECTION OF PEYTON STREET AND SOUTH AVENUE

NORTH SIXTEENTH CORNER NORTHWEST QUARTER SECTION 14-19-11