

**WEST 1/16<sup>TH</sup> CORNER SOUTHWEST QUARTER OF SECTION 15, TOWNSHIP 19 SOUTH,  
RANGE 11 EAST**

1) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED FEBRUARY 26, 2002, FOR PROJECT NUMBER 01004-02, SURVEY F16068 IN THE SURVEY FILE FOR SECTIONS 15-16 IN TOWNSHIP 19-11 FOR A SURVEY OF THREE TRACTS IN THE SOUTHEAST QUARTER OF SECTION 16-19-11, SAID THAT **SHE SET A 1/2" REBAR WITH HER "LS 1130" CAP** FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 16 AT HALF THE TOTAL DISTANCE AND ON LINE BETWEEN THE SOUTHEAST AND NORTHEAST CORNERS OF THE SOUTHEAST 1/4 OF SECTION 16, BEING THE NORTHEAST CORNER OF TRACT II.

- 1) 2.2' WEST TO THE EDGE OF THE ASPHALT MAT FOR A DRIVE ON THE WEST SIDE OF THE PARK
- 2) 43.65' WEST TO THE TOP CENTER OF THE NORTH END OF A CMP FOR AN ENTRANCE TO THE PARK
- 3) 67.95' SW TO A SQUARE CUT IN THE TOP OF AN INLET PIPE HUBGUARD
- 4) 79.75' NW TO THE SOUTHEAST CORNER OF THE FIELD HOUSE BUILDING AT GROUND LEVEL
- 5) 42.20' NE TO A CONCRETE NAIL & BOTTLECAP IN THE SOUTH GATE POST TO THE PARK
- 6) 43.15' TO A CONCRETE NAIL & BOTTLECAP IN A GUARD POST FOR A CABLE FENCE ALONG THE WEST SIDE OF THE PARK

**HER SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:**

- 1) 659.72' NORTH TO A 1/2" REBAR WITH HER "LS 1130" CAP SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF THE SE1/4 OF SECTION 16 AND THE NORTHEAST CORNER OF TRACT I
- 2) 1,319.43' NORTH TO A 5/8" LYON COUNTY CAP FOUND IN A DRILL HOLE AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16
- 3) 330.24' SOUTH TO A 2" PIPE FOUND WITH A 1/2" REBAR IN THE CENTER AT THE SOUTHEAST CORNER OF THE NORTH 20 RODS OF THE SE1/4 OF THE SE1/4 OF SECTION 16 AND THE SOUTHEAST CORNER OF TRACT II
- 4) 1,319.41' SOUTH TO THE STONE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 16
- 5) 458.50' WEST TO A 1/2" REBAR WITH HER "LS 1130" CAP SET FOR THE NORTHWEST CORNER OF TRACT II
- 6) 1,325.40' WEST TO A 1/2" REBAR WITH HER "LS 1130" CAP SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 16 AND THE NORTHWEST CORNER OF TRACT III
- 7) 2,650.00' WEST TO THE STONE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 16

2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 28, 2011, FOR PROJECT NUMBER 13152-02, SURVEY F16076 IN THE SURVEY FILE FOR SECTIONS 15-16 IN TOWNSHIP 19-11 FOR THREE TRACTS IN THE NORTHWEST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 16-19-11 FOR SMITH/ALDRETE, SAID THAT **HE FOUND THE 1/2" IRON PIN WITH THE REMAINS OF A CAP** AT THE EAST 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 16-19-11 FROM EXISTING REFERENCE TIES ON FILE IN THE COUNTY SURVEYORS OFFICE BY P. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN 2002.

- 1) IN THE CENTERLINE TO THE NORTH EXTENDED
- 2) 31.95' NE TO A CONCRETE NAIL & BOTTLECAP IN THE TOP OF A GUARD POST
- 3) 30.8' EAST TO A FENCE NORTH-SOUTH
- 4) 74.1' WEST TO THE SOUTH GATE POST AT THE GROUND
- 5) 91.7' SW TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 330.24' SOUTH TO THE 2" PIPE WITH A 1/2" IRON PIN IN THE CENTER HE FOUND AT THE SOUTHEAST CORNER OF THE NORTH 20 RODS OF THE SE1/4 OF THE SE1/4 OF SECTION 16
- 2) 1,319.36' NORTH TO A 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16 FROM A PREVIOUS SURVEY
- 3) 1,325.27' WEST TO A 1/2" IRON PIN WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 16
- 4) 1,659.89' WEST TO A 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF SKINNER ADDITION

WEST SIXTEENTH CORNER SOUTHWEST QUARTER SECTION 15-19-11