

CENTER 1/4 CORNER SECTION 17, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 14 RECORDED IN SURVEY BOOK "A" ON PAGE 10 DATED JUNE 23, 1858, A **PERMANENT SURVEY** TO ESTABLISH THE CENTER POST OF SECTION 17-19-11 SAID THAT **HE SET THE CENTER POST STONE** OF SECTION 17 ON LINE BETWEEN THE 1/4 POST STONES HE FOUND ON THE NORTH AND SOUTH LINES OF SECTION 17 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING DISTANCES
 - 1) 39.90 CHAINS NORTH TO THE FOUND NORTH 1/4 POST STONE OF SECTION 17
 - 2) 39.96 CHAINS SOUTH TO THE FOUND SOUTH 1/4 POST STONE OF SECTION 17

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 32, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 32 DATED APRIL 27, 1870 TO ESTABLISH THE CENTER OF SECTION 17-19-11, THE 1/2/4 CORNERS ON THE NORTH AND EAST SIDES OF THE NORTHEAST 1/4, TO DIVIDE THE SOUTHWEST 1/4 BY A LINE RUNNING NORTH & SOUTH, TO DIVIDE THE SOUTHEAST 1/4 INTO 4 EQUAL PARTS, AND THE DIVIDE THE NORTHEAST 1/4 INTO 4 EQUAL PARTS, SAID THAT **HE SET A STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 17 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING DISTANCES:
 - 1) 1,320' NORTH TO THE STONE HE SET FOR THE PERMANENT 1/2/4 CORNER ON THE WEST SIDE OF THE NE1/4 OF SECTION 17
 - 2) 2,640' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17
 - 3) 1,320' SOUTH TO THE STONE HE SET FOR THE PERMANENT 1/2/4 CORNER ON THE WEST SIDE OF THE SE1/4 OF SECTION 17
 - 4) 2,640' SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 17
 - 5) 1,320' WEST TO A POST HE SET FOR THE TEMPORARY 1/2/4 CORNER ON THE SOUTH SIDE OF THE NW1/4 OF SECTION 17
 - 6) 2,640' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 17
 - 7) 1,321' EAST TO THE STONE SET FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH SIDE OF THE SE1/4 OF SECTION 17
 - 8) 2,642' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 17

- 3) A. J. BAKER, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 24, A SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 24 DATED MARCH 1884 TO ESTABLISH THE NORTH 1/4 CORNER AND THE CENTER CORNER OF SECTION 17-19-11, ALSO TO ESTABLISH THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHEAST 1/4, AND TO DIVIDE THE WEST 1/2 OF THE NORTHEAST 1/4 EQUALLY NORTH & SOUTH, AND TO SET A 20 ROD AND 40 ROD STONE ON SAID LINE NORTH & SOUTH THAT DIVIDES SAID WEST 1/2 OF THE NORTHEAST 1/4, SAID THAT **HE SET A 6" X 7" X 8" STONE** FOR THE CENTER CORNER OF SECTION 17 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS SURVEY.

- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS A "**MONUMENT**" AT THE "CENTER CORNER SECTION 17-19-11".
 - 1) 100.35' NW TO A SPIKE IN A POWER POLE
 - 2) 45.5' NE TO A SPIKE IN A POWER POLE

- 5) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #17002 IN THE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHWEST CORNER OF NORTHEAST 1/4 OF SECTION 17 ALSO CALLED THE

CENTER OF THE SECTION. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCE:

- 1) 2,640.55' EAST TO A "MONUMENT" AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 17 – NOT IDENTIFIED
- 6) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F17015 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR 2 TRACTS IN THE NORTHEAST 1/4 OF SECTION 17-19-11 FOR BLUE STEM FEED YARDS DATED JUNE 4, 1976 SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE SOUTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 17 ALSO CALLED HE CENTER CORNER OF THE SECTION. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
- 7) GREGORY ALAN MILES, L.S. 667, IN LARGE SURVEY SR #17010 IN THE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR PROJECT NUMBER 87-01 DATED JANUARY 8, 1987, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A 1/2" REBAR** AT THE CENTER CORNER OF SECTION 17. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCE:
- 1) 2,640.63' NORTH TO A PK NAIL HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17
- 8) FRED I. GIBBS, L.S. 387, IN A SECTION CORNER REPORT DATED DECEMBER 28, 1992, FOR THE SURVEY OF THE CITY OF EMPORIA/LYON COUNTY LANDFILL, SAID THAT **HE FOUND A 1/2" IRON BAR AT 1" BELOW THE ASPHALT ROAD SURFACE** AT THE CENTER CORNER OF SECTION 17.
- 1) 46.1' NORTH TO A WIRE & 2 WASHERS ON A STEEL FENCE POST
 - 2) 29.6' SOUTH TO THE NE OF A CORNER CONCRETE BASE FOR A POWER POLE
 - 3) 61.0' NW TO A WIRED WASHER ON A STEEL FENCE POST
 - 4) 4.5' NORTH TO THE CENTERLINE T-E OF SOUTH AVENUE EAST-WEST
- 9) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED DECEMBER 10, 1993, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE CENTER CORNER OF SECTION 17 FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.
- 1) 30.0' SSW TO THE NORTHWEST CORNER OF A CONCRETE PAD FOR A POWER POLE
 - 2) 29.6' SSE TO THE NORTHEAST CORNER A CONCRETE PAD FOR A POWER POLE
 - 3) 61.0' NW TO A STEEL FENCE POST
 - 4) 4' NORTH TO THE CENTERLINE T-W OF SOUTH AVENUE EAST-WEST
- 10) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MAY 9, 2001, FOR PROJECT NUMBER 01-59, **FOUND THE 1/2" REBAR** AT THE CENTER CORNER OF SECTION 17 FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY MARION WAYNE BLACKBOURN, L.S. 1127, DATED DECEMBER 10, 1993. **I REPLACED THIS 1/2" REBAR WITH A 5/8" X 24" REBAR WITH LYON COUNTY CAP AND I SET A COUNTY MONUMENT BOX FLUSH WITH THE ASPHALT SURFACE OF SOUTH AVENUE.**
- 1) 30.0' SSW TO THE NW CORNER OF A CONCRETE PAD FOR A POWER POLE
 - 2) 29.6' SSE TO THE NE CORNER OF A CONCRETE PAD FOR A POWER POLE
 - 3) 30.1' SOUTH TO A CHISELED "+" IN A CONCRETE PAD FOR A POWER POLE
- 11) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED APRIL 15, 2002, FOR PROJECT NUMBER 02-91, SURVEY F17017 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11, FOR A TRACT IN THE

NORTHWEST QUARTER OF SECTION 17-19-11 FOR THE NOXIOUS WEED DEPARTMENT ORDERED BY THE BOARD OF COUNTY COMMISSIONER OF LYON COUNTY RECORDED IN VOLUME 555 ON PAGE 461 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 18, 2002, FOUND **THE 5/8" REAR WITH LYON COUNTY CAP SET IN A COUNTY MONUMENT BOX FLUSH WITH THE SURFACE OF SOUTH AVENUE** AT THE CENTER CORNER OF SECTION 17 FROM MY TIES DATED MAY 9, 2001 IN THE COUNTY ENGINEER'S OFFICE.

- 1) 30.0' SSW TO THE NW CORNER OF A CONCRETE PAD FOR A POWER POLE
- 2) 29.6' SSE TO THE NE CORNER OF A CONCRETE PAD FOR A POWER POLE
- 3) 30.1' SOUTH TO A CHISELED "+" IN A CONCRETE PAD FOR A POWER POLE
- 4) 38.3' SE TO A CORNER FENCE POST FOR A CHAIN LINK FENCE TO THE EAST
- 5) 2' NORTH TO THE CENTERLINE TRAVELED WAY OF SOUTH AVENUE

MY SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 515.26' WEST TO A COTTON GIN SPINDLE I SET FOR THE SOUTHEAST CORNER OF THE NOXIOUS WEED DEPARTMENT TRACT AS WITNESSED BY A 1/2" REBAR WITH "BG" CAP I FOUND 30.00' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE
- 2) 939.04' WEST TO A COTTON GIN SPINDLE I SET FOR THE SOUTHWEST CORNER OF THE NOXIOUS WEED DEPARTMENT TRACT AS WITNESSED BY A CHISELED PLUS WITH MAG NAIL I SET 30.00' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE
- 3) 2,638.56' WEST TO A 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT BOX I FOUND AT THE WEST 1/4 CORNER OF SECTION 17

- 12) FRED I. GIBBS, L.S. 387, IN A SECTION CORNER REPORT DATED MAY 29, 2002, FOR JOB NUMBER 02-159E, SURVEY F17016 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A 1.423 ACRE TRACT IN THE NORTHWEST QUARTER OF SECTION 17-19-11 FOR THE CITY OF EMPORIA, SAID THAT **HE FOUND THE 5/8" REBAR IN A COUNTY MONUMENT BOX** AT THE CENTER CORNER OF SECTION 17 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE.

- 1) 30.0' SSW TO THE NW CORNER OF A CONCRETE PAD FOR A POWER POLE
- 2) 29.5' SSE TO THE NE CORNER OF A CONCRETE PAD FOR A POWER POLE
- 3) 30.1' SOUTH TO A CHISELED "+" IN A CONCRETE PAD FOR A POWER POLE
- 4) 38.3' SE TO A CORNER FENCE POST FOR A CHAIN LINK FENCE TO THE EAST
- 5) 2' NORTH TO TRAVELED WAY OF SOUTH AVENUE

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 315.26' WEST TO A COTTON GIN SPINDLE HE SET FOR THE SOUTHEAST CORNER OF THE 1.423 ACRE TRACT AS WITNESSED BY A 1/2" REBAR WITH "BG" CAP HE SET 30' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE
- 2) 515.26' WEST TO A COTTON GIN SPINDLE HE SET FOR THE SOUTHWEST CORNER OF THE 1.423 ACRE TRACT AS WITNESSED BY A 1/2" REBAR WITH "BG" CAP HE SET 30' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE
- 3) 2,638.57' WEST TO A 1/2" REBAR 5" BELOW THE ASPHALT INTERSECTION HE FOUND AT THE WEST 1/4 CORNER OF SECTION 17

- 13) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 04, 2002, FOR LYON COUNTY PROJECT NUMBER 02-AU, **FOUND THE 5/8" REBAR WITH LYON COUNTY CAP SET IN A COUNTY MONUMENT BOX FLUSH WITH SURFACE OF THE ASPHALT ROAD** AT THE CENTER CORNER OF SECTION 17 FROM EXISTING MY TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED APRIL 15, 2002 AND TIES OF FRED I. GIBBS, L.S. 387, DATED MAY 29, 2002.

- 1) 30.0' SSW TO THE NE CORNER OF A CONCRETE PAD FOR A POWER POLE
- 2) 29.5' SSE TO THE NE CORNER OF A CONCRETE PAD FOR A POWER POLE

MY TIES ARE CONTINUED ON PAGE 4

- 3) 30.1' SOUTH TO A CHISELED "+" IN A CONCRETE PAD FOR A POWER POLE
 - 4) 38.3' SE TO A CORNER FENCE POST FOR A CHAIN LINK FENCE TO THE EAST
 - 5) 2' NORTH TO TRAVELED WAY OF SOUTH AVENUE
- 14) FRED I. GIBBS, L.S. 387, IN A SECTION CORNER REPORT DATED MARCH 18, 2004, FOR PROJECT NUMBER 03-307E FOR LYON COUNTY PROJECT NUMBER 03-DB, SAID THAT **HE FOUND THE 5/8" LYON COUNTY CAPPED REBAR IN A MONUMENT BOX** AT THE CENTER CORNER OF SECTION 17 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.
- 1) 30.1' SSW TO THE NW CORNER OF A CONCRETE PAD FOR A POWER POLE
 - 2) 29.1' SE TO THE NORTHEAST CORNER OF A CONCRETE PAD FOR A POWER POLE
 - 3) 30.0' SOUTH TO A "+" CUT ON THE NORTH SIDE OF A CONCRETE PAD FOR A POWER POLE
 - 4) 38.3' SE TO A FENCE POST FOR A CHAIN LINK FENCE TO THE EAST
- 15) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MARCH 24, 2005, FOR PROJECT NUMBER 05064-02, SURVEY F17018 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11, A SURVEY FOR A 10.37 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 17-17-11 FOR F & F FEEDS, SAID THAT **HE FOUND THE 5/8" REBAR WITH LYON COUNTY CAP IN A MONUMENT WELL** AT THE CENTER CORNER OF SECTION 17 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.
- 1) 30.0' SSW TO THE NW CORNER OF A CONCRETE PAD FOR A POWER POLE
 - 2) 29.6' SE TO THE NORTHEAST CORNER OF A CONCRETE PAD FOR A POWER POLE
 - 3) 30.1' SOUTH TO A PLUS "+" CUT IN THE CONCRETE PAD FOR A POWER POLE
 - 4) 38.3' SE TO THE NEAR FACE OF A CORNER FENCE POST FOR A CHAIN LINK FENCE TO THE EAST
 - 5) 2.0' NORTH TO THE CENTERLINE OF THE TRAVELED WAY
- HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:
- 1) 574.84' EAST TO THE SOUTHWEST CORNER OF THE 10.37 ACRE TRACT AS WITNESSED BY A 1/2" REBAR WITH HIS "LS 752" CAP HE SET 30' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE
 - 2) 1,377.64' EAST TO A CONCRETE NAIL HE FOUND AND HE REPLACED WITH A COTTON GIN SPINDLE AT THE SOUTHEAST CORNER OF THE 10.37 ACRE TRACT AS WITNESSED BY A 1/2" REBAR WITH HIS "LS 752" CAP HE SET 30' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE
 - 3) 2,635.39' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 17
- 16) FRED I. GIBBS, L.S. 387, OF BG CONSULTANTS, INC. IN LARGE SURVEY SR #17001 IN THE SURVEY DRAWER FOR SECTIONS 17 TO 36 IN TOWNSHIP 19-11 FOR PROJECT NUMBER 05-094E DATED JUNE 5, 2005 FOR A CERTIFICATE OF SURVEY FOR TYSON FOODS, SHOWS A **5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL** AT THE CENTER CORNER OF SECTION 17. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCE:
- 1) 2,635.40' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE EAST 1/4 CORNER OF SECTION 17
- 17) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED DECEMBER 7, 2009, FOR PROJECT NUMBER 09152-02 FOR LYON COUNTY PROJECT 09-TN AND SURVEY F17020 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A SKETCH OF THE RIGHT-OF-WAY STAKED ALONG THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE IN THE NORTH HALF OF SECTION 17-19-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN THE**

MONUMENT WELL AT THE CENTER CORNER OF SECTION 17 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE

- 1) 30.00' SSW TO THE NORTHWEST CORNER OF A CONCRETE PAD FOR A POWER POLE
- 2) 29.60' SE TO THE NORTHEAST CORNER OF A CONCRETE PAD FOR A POWER POLE
- 3) 30.10' SOUTH TO A PLUS (+) CUT IN A CONCRETE PAD FOR A POWER POLE
- 4) 38.30' SE TO THE NEAR FACE OF A CORNER FENCE POST FOR A CHAIN LINK FENCE TO THE EAST
- 5) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF SOUTH AVENUE TO THE EAST AND WEST
- 6) IN LINE WITH A FENCE TO THE SOUTH EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 2,638.45' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE WEST 1/4 CORNER OF SECTION 17
- 2) 1,377.49' EAST TO A COTTON GIN SPINDLE HE FOUND FROM A PRIOR SURVEY BY S. BROSEMER DATED 3/8/2005 AND RECORDED IN BOOK 611 ON PAGE 210

- 18) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED JULY 26, 2010 FOR PROJECT NUMBER 10178-02, SURVEYS F17021 AND F18011 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE CITY OF EMPORIA LANDFILL SITES IN SECTIONS 17 & 18-19-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL AT THE CENTER CORNER OF SECTION 17 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.**

- 1) 30.00' SW TO THE NW CORNER OF A CONCRETE PAD FOR A POWER POLE
- 2) 29.60' SE TO THE NE CORNER OF A CONCRETE PAD FOR A POWER POLE
- 3) 28.30' SE TO THE NEAR FACE OF A CORNER FENCE POST FOR A CHAIN-LINK FENCE TO THE EAST
- 4) 30.10' SOUTH TO A PLUS "+" CUT IN THE CONCRETE PAD FOR A POWER POLE
- 5) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF SOUTH AVENUE EAST-WEST
- 6) 34.20' NNW TO THE NEAR FACE OF THE EAST CHAIN-LINK FENCE GATE POST
- 7) 100.28' NORTH TO A 1/2" REBAR FOUND [**HORIZONTAL TIE**]

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 2,638.59' WEST TO A 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 18
- 2) 3,958.99' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE 1/16TH CORNER ON THE NORTH SIDE OF THE SE1/4 OF SECTION 18
- 3) 5,279.39' WEST TO A 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 18
- 4) 7,782.60' WEST TO A 5/8" REBAR HE FOUND IN A DRILL HOLE IN A DRAINAGE STRUCTURE AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 18
- 5) 2,640.78' NORTH TO A 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 17

CENTER QUARTER CORNER SECTION 17-19-11