

**NORTH 1/16<sup>TH</sup> CORNER SOUTHWEST QUARTER OF SECTION 17, TOWNSHIP 19 SOUTH,  
RANGE 11 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 32, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 32 DATED APRIL 27, 1870 TO ESTABLISH THE CENTER OF SECTION 17-19-11, THE 1/2/4 CORNERS ON THE NORTH AND EAST SIDES OF THE NORTHEAST 1/4, TO DIVIDE THE SOUTHWEST 1/4 BY A LINE RUNNING NORTH & SOUTH, TO DIVIDE THE SOUTHEAST 1/4 INTO 4 EQUAL PARTS, AND THE DIVIDE THE NORTHEAST 1/4 INTO 4 EQUAL PARTS, SAID THAT **HE SET A POST FOR THE TEMPORARY 1/2/4 CORNER** ON THE NORTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 17 ON LINE AND HALFWAY BETWEEN THE STONE HE FOUND AT THE WEST 1/4 CORNER AND THE STONE HE SET FOR THE CENTER OF SECTION 17 ON THIS **PERMANENT SURVEY**.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:**

- 1) 1,320' WEST TO THE STONE FOUND AT THE WEST 1/4 CORNER OF SECTION 17
- 2) 1,320' EAST TO THE STONE SET FOR THE PERMANENT CENTER OF SECTION 17
- 3) 2,641' EAST TO THE STONE SET FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH SIDE OF THE SE1/4 OF SECTION 17
- 4) 5,282' EAST TO THE STONE FOUND AT THE EAST 1/4 CORNER OF SECTION 17

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER 17-19-11