

**WEST 1/4 CORNER SECTION 17, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 382 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 2-1/2"** FOR THE WEST 1/4 CORNER OF SECTION 15-19-11.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 8 RECORDED IN SURVEY BOOK "A" ON PAGE 106 AND DATED JANUARY 1868, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 18-18-11 ON THIS SURVEY. THERE IS NO DRAWING AS HE NOTED THAT THE LAND OWNERS DID NOT WISH THEIR LANDS PLATTED.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 20.00 CHAINS WEST TO THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 18-19-11
  - 2) 40.00 CHAINS WEST TO THE PERMANENTLY ESTABLISHED CENTER CORNER OF SECTION 18-19-11
  - 3) 59.19 CHAINS WEST TO THE PROPERTY DIVISION CORNER HE SET ON THE NORTH SIDE OF THE SW1/4 OF SECTION 18-19-11
  - 4) 78.78 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 18-19-11
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 32, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 32 DATED APRIL 27, 1870 TO ESTABLISH THE CENTER OF SECTION 17-19-11, THE 1/2/4 CORNERS ON THE NORTH AND EAST SIDES OF THE NORTHEAST 1/4, TO DIVIDE THE SOUTHWEST 1/4 BY A LINE RUNNING NORTH & SOUTH, TO DIVIDE THE SOUTHEAST 1/4 INTO 4 EQUAL PARTS, AND THE DIVIDE THE NORTHEAST 1/4 INTO 4 EQUAL PARTS, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER BETWEEN SECTIONS 17 & 18-19-11 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,640' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 17-19-11
  - 2) 2,642' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 17-19-11
  - 3) 1,320' EAST TO A POST HE SET FOR THE TEMPORARY 1/2/4 CORNER ON THE NORTH SIDE OF THE SW1/4 OF SECTION 17-19-11
  - 4) 1,640' EAST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 17-19-11
  - 5) 3,961' EAST TO THE STONE HE SET FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH SIDE OF THE SE1/4 OF SECTION 17-19-11
  - 6) 5,282' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 17-19-11
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 63 OF THE 7<sup>TH</sup> TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 211 DATED JULY 17, 1872 FOR A ROAD IN TOWNSHIP 19, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER BETWEEN SECTION 17 & 18-19-11 TO END THIS ROAD SURVEY.
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 202 [PACKET 43 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY JOHN TRUITT AND OTHERS FOR A COUNTY ROADS IN TOWNSHIP 19-11 THAT HE SURVEYED ON JULY 17, 1872, AND WAS ORDERED ESTABLISHED AT A MEETING OF THE BOARD OF COUNTY COMMISSIONERS HELD JANUARY 6, 1873 AS A 60 FOOT WIDE ROAD AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE**

- FOUND THE STONE POST** AT THE WEST 1/4 CORNER OF SECTION 17-19-11 TO END THIS ROAD SURVEY.
- 1) THIS ROAD EXTENDS EAST ON THE CENTER SECTION LINES FOR 1 MILE AND 240-1/2 RODS TO THE SOUTHWEST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 16-19-11 TO COMMENCE THIS ROAD SURVEY
- 6) A. J. BAKER, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 24, A SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 24 DATED MARCH 1884 TO ESTABLISH THE NORTH 1/4 CORNER AND THE CENTER CORNER OF SECTION 17-19-11, ALSO TO ESTABLISH THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHEAST 1/4, AND TO DIVIDE THE WEST 1/2 OF THE NORTHEAST 1/4 EQUALLY NORTH & SOUTH, AND TO SET A 20 ROD AND 40 ROD STONE ON SAID LINE NORTH & SOUTH THAT DIVIDES SAID WEST 1/2 OF THE NORTHEAST 1/4, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 17-19-11 ON THIS SURVEY.
- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 167, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 167 DATED APRIL 25, 1887 ORDERED BY G. W. ANDERSON TO SURVEY AND LOCATE THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 18-19-11, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 18-19-11 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,322' WEST TO THE TEMPORARY STAKE HE SET FOR THE 1/8<sup>TH</sup> CORNER ON THE NORTH SIDE OF THE SE1/4 OF SECTION 18-19-11
  - 2) 2,644' WEST TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 18-19-11
  - 3) 1,324' SOUTH TO THE LIMESTONE 3" X 12" AT THE BASE, 15" LONG AND THE TOP SHARP HE SET FOR THE PERMANENT 1/8<sup>TH</sup> CORNER ON THE EAST SIDE OF THE SE1/4 OF SECTION 18-19-11
  - 4) 2,648' SOUTH TO THE 4" X 9" X 17" LIMESTONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 18-19-11
  - 5) 5,298' SOUTH TO THE LOCATION FOR THE STUMPS OF LINE TREES RECORDED IN THE GOVERNMENT SURVEY HE FOUND TO DETERMINE THE EAST 1/4 CORNER OF SECTION 19-19-11 – NO STONE FOUND
- 8) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 175, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 175 DATED MAY 16, 1887 FOR BY J. B. MOON FOR A COUNTY ROAD IN TOWNSHIPS 19-10 AND 19-11, **APPARENTLY FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 18-19-11 TO BEGIN THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE 1/4 SECTION LINES TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 13-19-10 TO END THIS ROAD SURVEY.
- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS AN **IRON PIN** AT THE "W1/4 CORNER SECTION 17-19-11".
- 1) 30' NORTH TO A SPIKE IN A SQUARE POST
  - 2) 25.6' SW TO THE NE CORNER OF A BARN
  - 3) 71' NE TO A SPIKE IN AN ELM TREE IN A YARD
- 10) NORMAN T. COOK, L.S. 169, OF COOK, FLATT & STROBEL, P.A., IN LARGE SURVEY SR #17003 IN THE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 DATED AUGUST 19, 1970, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN IN CONCRETE** AT THE WEST 1/4 CORNER OF SECTION 17-19-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,647.64' SOUTH TO THE IRON PIN IN CONCRETE AT THE SOUTHWEST CORNER OF SECTION 17-19-11

- 11) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #18001 IN THE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 DATED JULY 17, 1974, SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE EAST 1/4 CORNER OF SECTION 18-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320' WEST TO THE IRON PIN AT THE NORTHWEST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 18-19-11
  - 2) 2,639.8' NORTH TO THE IRON PIN IN PAVEMENT AT THE NORTHEAST CORNER OF SECTION 18-19-11
  - 3) 2,647.6' SOUTH TO THE IRON PIN IN PAVEMENT AT THE SOUTHEAST CORNER OF SECTION 18-19-11
- 12) GREGORY ALAN MILES, L.S. 667, IN LARGE SURVEY SR #17010 IN THE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR PROJECT NUMBER 87-01 DATED JANUARY 8, 1987, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A 1/2" REBAR** AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 17-19-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
  - 13) FRED I. GIBBS, L.S. 387, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 21, 1992, FOR THE CITY OF EMPORIA/LYON COUNTY LANDFILL SURVEY, SAID THAT **HE FOUND A 1/2" IRON BAR AT 5" BELOW THE SURFACE** AT THE EAST 1/4 CORNER OF SECTION 18-19-11.
    - 1) 36.5' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
    - 2) 74.1' SE TO A SPIKE & WASHER IN A POWER POLE
    - 3) 52.3' SW TO A RAILROAD SPIKE IN A POWER POLE
  - 14) WARREN CHIP WOODS, L.S.603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 23, 1996, FOR PROJECT NUMBER 96-10, **FOUND THE 1/2" REBAR AT 5" BELOW THE SURFACE OF THE ASPHALT ROAD** AT THE WEST 1/4 CORNER OF SECTION 17-19-11 FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY FRED I. GIBBS, L.S. 387, DATED DECEMBER 21, 1992.
    - 1) 36.5' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
    - 2) 74.1' SE TO A FOUND SPIKE & WASHER IN A POWER POLE
    - 3) 52.3' SW TO A FOUND RAILROAD SPIKE IN A POWER POLE
    - 4) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "H" TO THE SOUTH
    - 5) 2' NORTH TO THE CENTERLINE TRAVELED WAY OF ASPHALT SURFACED SOUTH AVENUE TO THE EAST
  - 15) WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 15, 2002, FOR PROJECT NUMBER 02-91, SURVEY F17017 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11, THE SURVEY FOR THE NOXIOUS WEED BUILDING ORDERED BY THE BOARD OF COUNTY COMMISSIONERS OF LYON COUNTY RECORDED IN VOLUME 555 ON PAGE 461 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 18, 2002, **FOUND THE 1/2" REBAR AT 5" BELOW THE ASPHALT ROAD SURFACE** AT THE WEST 1/4 CORNER OF SECTION 17-19-11 FROM MY TIES DATED APRIL 23, 1996 ON FILE IN THE COUNTY ENGINEER'S OFFICE. **I REPLACED THE FOUND 1/2" REBAR WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP AND I SET A LYON COUNTY MONUMENT BOX FLUSH WITH THE ASPHALT ROAD SURFACE OF SOUTH AVENUE.**

MY TIES ARE ON PAGE 4

- 1) 36.5' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 2) 74.1' SE TO A FOUND SPIKE & WASHER IN A POWER POLE
- 3) 52.3' SW TO A FOUND RAILROAD SPIKE IN A POWER POLE
- 4) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "H" TO THE SOUTH
- 5) 2' NORTH TO THE CENTERLINE TRAVELED WAY OF ASPHALT SURFACED SOUTH AVENUE TO THE EAST

MY SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,699.52' EAST TO THE COTTON GIN SPINDLE I SET FOR THE SOUTHWEST CORNER OF THE NOXIOUS WEED DEPARTMENT TRACT AS WITNESSED BY THE CHISELED PLUS WITH MAG NAIL I SET AT 30.00' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE
- 2) 2,123.30' EAST TO THE COTTON GIN SPINDLE I SET FOR THE SOUTHEAST CORNER OF THE NOXIOUS WEED DEPARTMENT TRACT AS WITNESSED BY THE 1/2" REBAR WITH "BG" CAP I FOUND AT 30.00' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE
- 3) 2,638.56' EAST TO THE 5/8" REBAR WITH A LYON CAP IN A MONUMENT BOX I FOUND AT THE CENTER CORNER OF SECTION 17-19-11

- 16) FRED I. GIBBS, L.S. 387, IN A LAND SURVEY REFERENCE REPORT DATED MAY 29, 2002, FOR JOB NUMBER 02-159E, SURVEY F17016 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A 1.423 ACRE TRACT IN THE NORTHWEST QUARTER OF SECTION 17-19-11 FOR THE CITY OF EMPORIA, SAID THAT **HE FOUND THE 1/2" REBAR AT 5" BELOW THE SURFACE OF THE ASPHALT INTERSECTION** AT THE WEST 1/4 CORNER OF SECTION 17-19-11 PRIOR TO THE LYON COUNTY SURVEYOR REPLACING IT AND INSTALLING THE MONUMENT BOX.

- 1) 37.1' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 2) 72.1' SE TO A PK NAIL & WASHER IN A POWER POLE
- 3) 52.3' SW TO A RAILROAD SPIKE IN A POWER POLE
- 4) 2.0' NORTH TO THE TRAVELED WAY OF SOUTH AVENUE TO THE EAST
- 5) IN THE TRAVELED WAY OF COUNTY ROAD "H" TO THE SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,123.31' EAST TO THE COTTON GIN SPINDLE HE SET FOR THE SOUTHWEST CORNER OF THE 1.423 ACRE TRACT AS WITNESSED BY THE 1/2" REBAR WITH "BG" CAP HE SET AT 30' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE
- 2) 2,323.31' EAST TO THE COTTON GIN SPINDLE HE SET FOR THE SOUTHEAST CORNER OF THE 1.423 ACRE TRACT AS WITNESSED BY THE 1/2" REBAR WITH "BG" CAP HE SET AT 30' NORTH ON THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE
- 3) 2,638.57' EAST TO THE 5/8" REBAR IN A COUNTY MONUMENT BOX HE FOUND AT THE CENTER CORNER OF SECTION 17-19-11

- 17) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 4, 2002, FOR PROJECT NUMBER 02-AU, THE BOUNDARY SURVEY OF THE NOXIOUS WEED BUILDING SITE, **FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN A COUNTY MONUMENT BOX FLUSH WITH THE SURFACE OF THE ASPHALT ROAD [SOUTH AVENUE]** AT THE WEST 1/4 CORNER OF SECTION 17-19-11 FROM MY TIES DATED APRIL 15, 2002 ON FILE IN THE COUNTY ENGINEER'S OFFICE.

- 1) 36.5' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 2) 74.1' SE TO A FOUND SPIKE & WASHER IN A POWER POLE
- 3) 52.3' SW TO A FOUND RAILROAD SPIKE IN A POWER POLE
- 4) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "H" TO THE SOUTH

MY TIES ARE CONTINUED ON PAGE 5

- 5) 2' NORTH TO THE CENTERLINE TRAVELED WAY OF ASPHALT SURFACED SOUTH AVENUE TO THE EAST
- 18) FRED I. GIBBS, L.S. 387, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 18, 2004, FOR PROJECT NUMBER 03-307E FOR LYON COUNTY PROJECT NUMBER 03-DB, SAID THAT **HE FOUND THE 5/8" LYON COUNTY CAPPED REBAR IN A MONUMENT BOX** AT THE WEST 1/4 CORNER OF SECTION 17-19-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.
- 1) 37.1' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 2) 72.1' SE TO A PK NAIL & WASHER IN A POWER POLE
  - 3) 52.3' SW TO A RAILROAD SPIKE IN A POWER POLE
  - 4) 2.0' NORTH TO THE TRAVELED WAY OF SOUTH AVENUE TO THE EAST
  - 5) IN THE TRAVELED WAY OF COUNTY ROAD "H" TO THE SOUTH
- 19) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 7, 2009, FOR PROJECT NUMBER 09152-02 FOR LYON COUNTY PROJECT 09-TN, AND SURVEY F17020 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A SKETCH OF THE RIGHT-OF-WAY STAKED ALONG THE NORTH RIGHT-OF-WAY LINE OF SOUTH AVENUE IN THE NORTH HALF OF SECTION 17-19-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT, SAID THAT **HE FOUND THE 5/8" CAPPED REBAR IN THE MONUMENT WELL** AT THE WEST 1/4 CORNER OF SECTION 17-19-11 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 34.45' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 2) 72.1' SE TO A PK NAIL & WASHER IN A POWER POLE
  - 3) 52.3' SW TO A RAILROAD SPIKE IN A POWER POLE
  - 4) 58.8' NW TO THE TOP CENTER OF A 5" PIPE POST AT THE NORTH GATE
  - 5) IN THE TRAVELED WAY OF COUNTY ROAD "H" TO THE SOUTH
  - 6) 2.0' NORTH TO THE TRAVELED WAY OF SOUTH AVENUE TO THE EAST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,638.45' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND IN A MONUMENT WELL AT THE CENTER CORNER OF SECTION 17-19-11
  - 2) 4,015.94' EAST TO THE COTTON GIN SPINDLE HE FOUND FROM A PRIOR SURVEY BY S. BROSEMER DATED 3/8/2005 AND RECORDED IN BOOK 611 ON PAGE 210 AT THE REGISTER OF DEEDS OFFICE
- 20) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 26, 2010 FOR PROJECT NUMBER 10178-02, SURVEYS F17021 AND F18011 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE CITY OF EMPORIA LANDFILL SITES IN SECTIONS 17 & 18-19-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL** AT THE EAST CORNER OF SECTION 18-19-11 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 34.45' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 2) 72.10' SE TO A PK NAIL & WASHER IN A POWER POLE
  - 3) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF SOUTH AVENUE TO THE EAST
  - 4) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H" TO THE SOUTH
  - 5) 58.7' NW TO THE TOP CENTER OF A 5" CORNER FENCE POST
  - 6) 30.00' NORTH TO A 1/2" REBAR WITH "LS 752" CAP SET [**HORIZONTAL TIE**]
  - 7) 20.00' WEST TO A 1/2" REBAR WITH "LS 752" CAP SET [**HORIZONTAL TIE**]
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,639.25' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 18-19-11
- HIS INFORMATION IS CONTINUED ON PAGE 6

- 2) 2,638.59' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 17-19-11
- 3) 2,658.45' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 18-19-11
- 4) 1,320.40' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 18-19-11
- 5) 2,640.80' WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 18-19-11
- 6) 5,144.01' WEST TO THE 5/8" REBAR IN A DRILL HOLE IN A DRAINAGE STRUCTURE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 18-18-11 ON THE TOWNSHIP LINE

WEST QUARTER CORNER SECTION 17-19-11