

CENTER CORNER SECTION 18, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 8 RECORDED IN SURVEY BOOK "A" ON PAGE 106 DATED JANUARY 1868, SAID THAT **HE PERMANENTLY ESTABLISHED** THE CENTER OF SECTION 18 AT THE POINT OF INTERSECTION OF THE TWO LINES FROM THE OPPOSITE 1/4 CORNERS OF SECTION 18 ON THIS SURVEY. THERE IS NO DRAWING AS HE NOTED THAT THE LAND OWNERS DID NOT WISH THEIR LANDS PLATTED.
HIS SURVEY NOTES SHOW THE FOLLOWING DISTANCES:
 - 1) 19.19 CHAINS WEST TO THE PROPERTY DIVISION CORNER SET ON THE NORTH SIDE OF THE SW1/4 OF SECTION 18
 - 2) 38.38 CHAINS WEST TO THE STONE FOUND AT THE WEST 1/4 CORNER OF SECTION 18
 - 3) 20.00 CHAINS EAST TO THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 18
 - 4) 40.00 CHAINS EAST TO THE STONE FOUND AT THE EAST 1/4 CORNER OF SEC. 18

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 167, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 167 DATED APRIL 25, 1887 ORDERED BY G. W. ANDERSON TO SURVEY AND LOCATE THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 18-19-11, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 18 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 1,322' EAST TO THE TEMPORARY STAKE HE SET FOR THE 1/8TH CORNER ON THE NORTH SIDE OF THE SE1/4 OF SECTION 18
 - 2) 2,644' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18

- 3) GREGORY ALAN MILES, L.S. 667, IN LARGE SURVEY SR #17010 IN THE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR PROJECT NUMBER 87-01 DATED JANUARY 8, 1987, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 1/2" REBAR** FOR THE CENTER CORNER OF SECTION 18 ON THIS SURVEY. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED JULY 26, 2010 FOR PROJECT NUMBER 10178-02, SURVEYS F17021 AND F18011 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE CITY OF EMPORIA LANDFILL SITES IN SECTIONS 17 & 18-19-11, SAID THAT **HE FOUND A 1/2" REBAR** AT THE CENTER CORNER OF SECTION 18 NEAR THE INTERSECTION OF OPPOSITE QUARTER CORNERS ATTRIBUTABLE TO GREGORY ALAN MILES, L.S. 667, FOR HIS 1987 SURVEY FOR THE CITY OF EMPORIA.
 - 1) 8.7' NORTH TO A LINE OF FENCE TO THE EAST AND WEST
 - 2) 11.65' NW TO A 16 D NAIL & BOTTLE CAP IN A FENCE POST
 - 3) 12.20' NE TO A 16 D NAIL & BOTTLE CAP IN FENCE POST
 - 4) 16.15' NW TO THE SOUTHEAST CORNER OF AN OLD METAL FENCE POST AT GROUND LEVEL
 - 5) 2,642.93' SOUTH TO A 5/8" REBAR WITH LYON COUNTY CAP IN A MONUMENT WELL AT THE SOUTH 1/4 CORNER OF SECTION 18-19S-11E
 - 6) 2,503.21' WEST TO A 5/8" REBAR IN A DRILL HOLE IN THE CONCRETE BRIDGE DECK AT THE WEST 1/4 CORNER OF SECTION 18-19S-11EHIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 2,638.14' NORTH TO A 2" ALUMINUM CAP ON A MONUMENT WELL HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 18
 - 2) 1,320.40' EAST TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/16TH CORNER OF THE SE1/4 OF SECTION 18

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,640.80' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 18
- 4) 5,279.39' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 18
- 5) 2,642.93' SOUTH TO A 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 18

CENTER QUARTER CORNER SECTION 18-19-11