

**NORTH 1/16TH CORNER NORTHWEST QUARTER OF SECTION 18, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 8 RECORDED IN SURVEY BOOK "A" ON PAGE 106 DATED JANUARY 1868, SAID THAT **HE SET A STONE FOR THE PROPERTY DIVISION CORNER** ON THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 18-19-11 LINE AND EQUIDISTANT FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER AND THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 18 ON THIS SURVEY. THERE IS NO DRAWING AS HE NOTED THAT THE LAND OWNERS DID NOT WISH THEIR LANDS PLATTED.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 19.37-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 18-19-11
- 2) 19.37-1/2 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/CORNER OF SECTION 18-19-11

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 9 RECORDED IN SURVEY BOOK "A" ON PAGE 107 AND DATED JANUARY 1868, SAID THAT **HE SET A STONE FOR THE PROPERTY DIVISION CORNER** ON THE SOUTH LINE OF THE SOUTHWEST 1/4 OF SECTION 7-19-11 ON LINE AND EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER AND THE STONE THAT HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 7-19-11 ON THIS SURVEY. THERE IS NO DRAWING AS HE NOTED THAT THE LAND OWNERS DID NOT WISH THEIR LANDS PLATTED.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 19.38 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-19-11
- 2) 19.38 CHAINS EAST TO THE STONE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 7-19-11
- 3) 78.76 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-19-11

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 26 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 81 DATED MAY 28, 1874 TO ESTABLISH THE CENTER CORNER AND SUBDIVIDE THE SOUTHWEST 1/4 OF SECTION 7-19-11 INTO EAST AND WEST HALVES, SAID THAT **HE FOUND THE STONE** AT THE 1/2/4 CORNER ON THE SOUTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 7-19-11 "ALREADY SET" ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING DISTANCES:

- 1) 1,237-1/2' WEST TO THE STONE HE FOUND AT THE CORNER TO SECTIONS 7 & 18-19-11 ON THE RANGE LINE
- 2) 3,876-1/2' EAST TO THE STONE HE FOUND AT THE CORNER TO SECTIONS 7, 8, 17 & 18-19-11

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A, SURVEY F07015 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 DATED JUNE 5, 2014 FOR PROJECT NUMBER 14108-02, FOR TWO TRACTS IN THE SOUTHWEST QUARTER OF SECTION 7-19-11 FOR EVERGREEN DESIGN, SHOWS ON HIS SURVEY DRAWING A **1/2" IRON PIN** AT THE SOUTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 7-19-11 AND THE SOUTHWEST CORNER OF TRACT 2.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,239.40' WEST TO THE 3/4" IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 18-19-11

- 2) 555.80' EAST TO THE SOUTHEAST CORNER OF TRACT 2 AND THE SOUTHWEST CORNER OF THE "GLACIER TRACT" RECORDED IN VOLUME 392 ON PAGE 58 IN THE REGISTER OF DEEDS OFFICE AS WITNESSED BY THE 1/2" X 24" IRON PIN WITH HIS "LS 752" CAP HE SET AT 33' NORTH ON THE NORTH RIGHT-OF-WAY LINE
- 3) 1,245.80' EAST TO THE KDOT CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 7-19-11

NORTH SIXTEENTH CORNER NORTHWEST QUARTER SECTION 18-19-11