

**NORTH 1/16<sup>TH</sup> CORNER SOUTHEAST QUARTER OF SECTION 18, TOWNSHIP 19 SOUTH,  
RANGE 11 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 8 RECORDED IN SURVEY BOOK "A" ON PAGE 106 DATED JANUARY 1868, SAID THAT **HE ESTABLISHED** THE NORTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 18 ON LINE AND EQUIDISTANT BETWEEN THE STONE HE FOUND AT THE EAST 1/4 CORNER AND HIS PERMANENTLY ESTABLISHED CENTER OF SECTION 18 ON THIS SURVEY. THERE IS NO DRAWING AS HE NOTED THAT THE LAND OWNERS DID NOT WISH THEIR LANDS PLATTED.  
HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:
  - 1) 20.00 CHAINS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18
  - 2) 20.00 CHAINS WEST TO THE PERMANENTLY ESTABLISHED CENTER CORNER OF SECTION 18
  - 3) 39.19 CHAINS WEST TO THE PROPERTY DIVISION CORNER HE SET ON THE NORTH SIDE OF THE SW1/4 OF SECTION 18
  - 4) 58.78 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 18
  
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 167, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 167 DATED APRIL 25, 1887 ORDERED BY G. W. ANDERSON TO SURVEY AND LOCATE THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 18-19-11, SAID THAT HE SET A **TEMPORARY STAKE** FOR THE 1/8<sup>TH</sup> CORNER ON THE NORTH SIDE OF THE SOUTHEAST 1/4 OF SECTION 18 ON LINE AND HALFWAY BETWEEN THE STONES THAT HE FOUND AT THE CENTER CORNER AND THE EAST 1/4 CORNER OF SECTION 18 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:
  - 1) 1,322' WEST TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 18
  - 2) 1,322' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18
  - 3) 1,320-1/2' SOUTH TO THE 4" X 7" X 14" LIMESTONE SET FOR THE PERMANENT CENTER OF THE SE1/4 OF SEC. 18
  - 4) 2,641' SOUTH TO THE 2-1/2" X 12" X 14" LIMESTONE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 18
  
- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #18001 IN THE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 DATED JULY 17, 1974, SHOWS ON HIS SURVEY DRAWING A **1/2" DIAMETER REBAR** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 18. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:
  - 1) 1,320' EAST TO THE EAST 1/4 CORNER OF SECTION 18 – NOT DESCRIBED
  - 2) 2,645.3' SOUTH TO THE SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 18 – NOT DESCRIBED
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED JULY 26, 2010 FOR PROJECT NUMBER 10178-02, SURVEYS F17021 AND F18011 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE CITY OF EMPORIA LANDFILL SITES IN SECTIONS 17 & 18-19-11, SAID THAT HE SEARCHED FOR THE McAULEY AND GOULD MONUMENT AT THIS 1/16<sup>TH</sup> CORNER, BUT HE DID NOT FIND ANY MONUMENT. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 18 ON TRUE LINE AND HALFWAY BETWEEN THE CENTER CORNER AND THE EAST 1/4 CORNER OF SECTION 18.

- 1) 30.17' NORTH TO A 1/2" REBAR FOUND
- 2) 40.33' WEST TO A 1/2" REBAR FOUND
- 3) 25.93' NW TO A 60 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 4) 23.65' WNW TO A 60 D NAIL & WASHER IN THE TOP OF THE SOUTH BRACE POST
- 5) 23.0' WEST TO A LINE OF FENCE TO THE SOUTH
- 6) 10.3' NORTH TO A LINE OF FENCE TO THE WEST EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,320.40' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 18
- 2) 3,958.99' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 17
- 3) 1,320.40' WEST TO A 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 18
- 4) 3,823.61' WEST TO A 5/8" REBAR IN A DRILL HOLE IN A DRAINAGE STRUCTURE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 18
- 5) 2,650.69' SOUTH TO A COTTON GIN SPINDLE HE SET FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 18

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER SECTION 18-19-11