

**CENTER CORNER SECTION 19, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY D. T. McAULEY, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 205 [PACKET 56 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY H. C. THOMPSON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-11 THAT HE SURVEYED OCTOBER 18, 1872, AND WAS ORDERED ESTABLISHED AS A 60 FOOT WIDE ROAD BY THE BOARD OF COUNTY COMMISSIONERS ON JANUARY 6, 1873 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 19-19-11 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE 1/4 CORNER BETWEEN SECTIONS 18 & 19-19-11
  - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO AN ANGLE TO THE SOUTHEASTERLY AT 191 RODS SOUTH OF THE NORTH 1/4 CORNER OF SECTION 19-19-11
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 45 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 102 DATED OCTOBER 9, 1874 TO FIND THE CENTER CORNER AND SUBDIVIDE A PART OF THE SOUTHWEST 1/4 OF SECTION 19-19-11, SAID THAT **HE SET A 16" X 12" X 3" STONE** FOR THE CENTER CORNER OF SECTION 19-19-11 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 2,647-1/2' SOUTH TO THE **WITNESS POST** TO THE 1/4 CORNER ON THE SOUTH BOUNDARY OF SECTION 19-19-11
  
- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #19001 IN THE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 19-19-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

CENTER QUARTER CORNER SECTION 19-19-11