

**WEST 1/16<sup>TH</sup> CORNER SOUTHEAST QUARTER OF SECTION 20, TOWNSHIP 19 SOUTH,  
RANGE 11 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 6 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 61 DATED FEBRUARY 26, 1874 TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 20-19-11 INTO NORTH AND SOUTH HALVES, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/2/4 CORNER ON THE WEST SIDE OF THE SOUTHEAST 1/4 OF SECTION 20-19-11 "ALREADY SET" ON THIS **PERMANENT SURVEY**.
  
- 2) RONALD J. SHANKS, P.S. 1255 OF BARTLETT & WEST IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 14, 2015 FOR PROJECT NUMBER 16521-2252, SAID THAT CONSIDERED THAT THIS CORNER WAS **LOST** AND HE RESET IT AT 1/2 DISTANCE AND ON LINE BETWEEN THE SOUTH 1/4 CORNER AND THE CENTER CORNER OF SECTION 20-19-11. **HE SET A 5/8" REBAR WITH "CLS 14" PLASTIC CAP** FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 20-19-11. HE SENT THE FOLLOWING **HORIZONTAL TIES**:
  - 1) NAD 83 COORDINATES: NORTH: 1944087.070000 EAST: 1966680.990000
  - 2) 1.5' BELOW THE GROUND SURFACE
  - 3) NO OTHER TIES AVAILABLE

WEST SIXTEENTH CORNER SOUTHEAST QUARTER SECTION 20-19-11