

WEST 1/16TH CORNER OF THE SOUTHWEST QUARTER OF SECTION 21, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 6 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 61 DATED FEBRUARY 26, 1874 TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 20-19-11 INTO NORTH AND SOUTH HALVES, SAID THAT **HE SET A 20" X 16" X 3" LIMESTONE** FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SOUTHEAST 1/4 OF SECTION 20-19-11 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 21-19-11 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21-19-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,322' NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 21-19-11
 - 2) 1,322' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21-19-11
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 41, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 222 DATED APRIL 25, 1902 AT THE ORDER OF J. M. STEEL TO SURVEY A 5 ACRE TRACT IN THE SOUTHWEST 1/4 OF SECTION 21-19-11, SAID THAT **HE FOUND THE STONE STANDING IN THE MIDDLE OF THE ROAD AND ON LINE WITH A HEDGE RUNNING WEST** AT THE WEST 1/8TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 21-19-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 52.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.10 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21-19-11
- 2) 20.08 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 21-19-11

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 60, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 140 DATED APRIL 25, 1902 FOR A ROAD IN TOWNSHIP 19, RANGE 11 FOR E. M. HEIDT THAT WAS ACQUIRED BY PURCHASE, SAID THAT **HE FOUND THE STONE AT THE 1/2/4 CORNER ON THE WEST SIDE OF THE SOUTHWEST 1/4 OF SECTION 21-19-11 IN THE MIDDLE OF THE ROAD AND IN LINE WITH A HEDGE TO THE WEST** ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 153 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.

HIS NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 11.65 CHAINS NORTH ON THE SECTION LINE TO A STAKE MARKED "A" HE SET AT AN ANGLE TO THE NORTHEASTERLY ON THIS ROAD SURVEY
 - 2) 20.08 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 21 AT 52 LINKS EAST AND 7 LINKS SOUTH OF AN 18" ELM TREE
 - 3) 20.10 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21 AT 20 FEET SOUTH AND 25 FEET WEST OF A HEDGE
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 576 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 169 THROUGH 172 PETITION BY E. M. HEIDT AND OTHERS FOR A ROAD IN TOWNSHIP 19-11 [PACKET 622 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 8, 1902, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE AT THE EAST 1/8TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 20-19-11 ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD, 25 FEET ON EACH SIDE OF THE LINE AS SURVEYED**. HE NOTED THAT THIS ROAD WAS

ACQUIRED BY PURCHASE BY THE DEEDS RECORDED IN BOOK 73 ON PAGE 578, BOOK 73 ON PAGE 442, AND BOOK 73 ON PGE 443 IN THE REGISTER OF DEEDS OFFICE. SEE THE SURVEY REPORT ON PAGE 172 FOR THE LOCATION OF THE CENTERLINE OF THIS ROAD SURVEY.

- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS A **STONE** AT THE "SE CORNER NE1/4 SE1/4 SECTION 20-19-11".
 - 1) 32.1' NW TO A POWER POLE
 - 2) 22.1' SE TO A NAIL IN A HEDGE TREE
 - 3) 793.0' NORTH TO AN IRON PIN

- 6) RONALD J. SHANKS, P.S. 1255 OF BARTLETT & WEST IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 14, 2015 FOR PROJECT NUMBER 16521-2252, SAID THAT **HE FOUND THE EXISTING 16" X 14" X 3" LIMESTONE** AT THE EAST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 20-19-11 FROM LYON COUNTY SECTION CORNER TIE RECORDS. HE SENT THE FOLLOWING **HORIZONTAL TIES:**
 - 1) NAD 83 COORDINATES: NORTH: 1944139.530000 EAST: 1969313.710000
 - 2) **0.25' WEST TO A 5/8" REBAR WITH "CLS 14" PLASTIC CAP**
 - 3) 45.01' WSW TO A MAG NAIL IN THE TOP EAST END OF A 24" CMP CULVERT
 - 4) 67.48' NW TO A MAG NAIL IN THE EAST FACE OF A POWER POLE
 - 5) 11' WEST TO THE TRAVELED WAY OF COUNTY ROAD J
 - 6) 1' BELOW THE ROAD SURFACE

WEST SIXTEENTH CORNER SOUTHWEST QUARTER SECTION 21-19-11