

CENTER CORNER SECTION 25, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 30, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 30 DATED APRIL 27, 1870 TO ESTABLISH THE CENTER CORNER [TEMPORARY] AND DIVIDE THE SOUTHWEST 1/4 OF SECTION 25-19-11 BY A LINE RUNNING NORTH & SOUTH, SAID THAT **HE SET A POST FOR THE TEMPORARY CENTER CORNER** OF SECTION 25-19-11 ON LINE WITH THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER AND THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 25-19-11 AT 2,640' NORTH OF THE SOUTH 1/4 CORNER OF SECTION 25-19-11 ON THIS **PERMANENT SURVEY**.
HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,320-3/4' WEST TO THE STAKE SET FOR THE TEMPORARY 1/2/4 CORNER ON THE NORTH SIDE OF THE SW1/4 OF SECTION 25-19-11
 - 2) 2,641-1/2' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 25-19-11

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 84 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 6 DATED FEBRUARY 5, 1873 TO ESTABLISH THE 1/4 CORNER ON THE TOWNSHIP LINE BETWEEN SECTION 25-19-11 AND 30-19-12, TO ESTABLISH THE CENTER CORNER OF SECTION 25-19-11, AND TO DIVIDE THE SOUTHEAST 1/4 OF SECTION 25-19-11 INTO HALVES BY A LINE RUNNING NORTH AND SOUTH, SAID THAT **HE SET A POST FOR THE PERMANENT CENTER CORNER** OF SECTION 25-19-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,316' EAST TO THE POST HE SET FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH SIDE OF THE SE1/4 OF SECTION 25-19-11
 - 2) 2,532' EAST TO THE POST HE SET FOR A WITNESS TO THE 1/4 CORNER BETWEEN SECTIONS 25 & 30 ON THE RANGE LINE
 - 3) 2,632' EAST TO THE LOCATION FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 30 ON THE RANGE LINE – FALLS IN THE RIVER

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 18, A ROAD SURVEY IN TOWNSHIP 19-11 RECORDED IN SURVEY BOOK "E" ON PAGE 198 DATED JANUARY 1, 1901 FOR H. E. WRIGHT, PRINCIPAL PETITIONER, SAID THAT HE BEGAN THIS ROAD SURVEY AT THE INTERSECTION OF TWO HEDGES AT THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 25-19-11, AND HE RAN WEST ON THE 1/4 SECTION LINE FOR 2,600 FEET TO THE END OF THIS ROAD SURVEY AT THE EAST SIDE OF THE PUBLIC ROAD ON THE WEST LINE OF SECTION 25, LAYING THE 16-1/2' WIDE ROAD ALL ON THE NORTH SIDE OF THE 1/4 SECTION LINE.

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 461 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 109 THROUGH 112 PETITIONED BY H. E. WRIGHT FOR AN OUTLET ROAD FOR LAND HE OWNED IN SECTION 25-19-11 [PACKET 704 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON JANUARY 9, 1901, WAS ESTABLISHED AND OPENED AS A 16-1/2 FOOT WIDE ROAD ON JANUARY 10, 1901 AS ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON JANUARY 29, 1901 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT HE BEGAN THIS ROAD SURVEY AT THE INTERSECTION OF TWO OSAGE HEDGES AT THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 25-19-11.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST, LAYING THE ROAD 16-1/2 FEET WIDE ALL ON THE NORTH SIDE OF THE 1/4 SECTION LINE, FOR 2,600 FEET TO THE EAST SIDE OF

THE PUBLIC ROAD ON THE WEST LINE OF SECTION 25-19-11 AT THE END OF THIS ROAD SURVEY

- 5) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F25003 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 SHOWING THE LINES OF A SURVEY OF A TRACT OF LAND CONSISTING OF A PART THE EAST 1/2 OF THE SOUTHWEST 1/4 AND ALL OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 25-19-11, BUT NOT DATED, IT SHOWS ON HIS SURVEY DRAWING THAT HE SET A "**TEMPORARY POINT**" AT 2,640' EAST OF THE WEST 1/4 CORNER OF SECTION 25-19-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320' WEST TO THE "MONUMENT" [NOT IDENTIFIED] HE SET FOR THE PLACE OF BEGINNING FOR THIS SURVEY AT THE "NORTHWEST CORNER OF THE EAST ONE-HALF OF THE SOUTHWEST QUARTER OF SECTION 25-19-11"
- 2) 2,640' WEST TO THE "MONUMENT" AT THE WEST 1/4 CORNER OF SECTION 25-19-11 – NOT IDENTIFIED
- 3) 1,320' EAST TO THE "MONUMENT" HE SET FOR THE NORTHEAST TRACT CORNER – NOT IDENTIFIED
- 4) 1,980' SOUTH TO THE "MONUMENT" HE SET FOR A TRACT CORNER – NOT IDENTIFIED
- 5) 2,647' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 25-19-11

CENTER QUARTER CORNER SECTION 25-19-11