

NORTH 1/4 CORNER SECTION 26, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 360 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 26-19-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.65 CHAINS WEST TO THE 22" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-19-11
 - 2) 39.85 CHAINS EAST TO THE 18" X 18" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-19-11

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 132 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 114 TO 116 PETITIONED BY W. B. WILLIS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-11 [PACKET 376 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 19, 1881, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 14, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 26-19-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 5,280 FEET TO THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 27-19-11 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 1,320 FEET TO THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 26-19-11; THEN EXTENDS EAST ON THE 1/4 SECTION LINE FOR 2,640 FEET TO THE SOUTHEAST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 26-19-11 TO COMMENCE THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 229 DATED SEPTEMBER 19, 1881, FOR A ROAD SURVEY IN TOWNSHIP 19-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 26-19-11 AT AN ANGLE POINT ON THIS ROAD SURVEY
HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCE:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 5,280 FEET TO THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 27-19-11 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 1,320 FEET TO THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 26-19-11; THEN EXTENDS EAST ON THE 1/4 SECTION LINE FOR 2,640 FEET TO THE SOUTHEAST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 26-19-11 TO COMMENCE THIS ROAD SURVEY

- 4) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 16, 1982, SAID THAT CONSIDERED THAT THE NORTH 1/4 CORNER OF SECTION 26-19-11 WAS **LOST**. **HE SET A 5/8" REBAR WITH A PLASTIC CAP** FOR THE NORTH 1/4 CORNER OF SECTION 26-19-11 ON TRUE LINE AND AT ONE-HALF THE DISTANCE BETWEEN THE NORTHEAST CORNER AND THE NORTHWEST CORNER OF SECTION 26-19-11. **HE SAID THAT THE CORNER POSITION FALLS IN A DITCH RUNNING NORTH-SOUTH, AND HE SET AN ORANGE CLAY PIGEON AROUND THE REBAR.**
 - 1) 50.0' WEST TO A 5/8" REBAR
 - 2) 14.0' WEST TO THE TRAVELED WAY OF THE ROAD TO THE SOUTH [EXTENDED]
 - 3) 3.5' SOUTH TO THE TRAVELED WAY OF THE ROAD TO THE WEST [EXTENDED]
 - 4) 34.0' SOUTH TO A LINE OF FENCE TO THE WEST [EXTENDED]
 - 5) 40.0' NNW TO A 1/2" REBAR IN A TRAIL

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:

- 1) 2,628.8' WEST TO THE NORTHWEST CORNER OF SECTION 26-19-11
- 2) 2,628.8' EAST TO THE NORTHEAST CORNER OF SECTION 26-19-11

5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 22, 2011 FOR PROJECT NUMBER 11177-02, A SURVEY FOR A TRACT IN THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 23-19-11 FOR EK REALTY, SURVEY F23008 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 23-19-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE DATED NOVEMBER 1982.

- 1) 50.00' WEST TO A 5/8" REBAR WITH A LYON COUNTY CAP ON THE SOUTH LINE OF SECTION 23
- 2) 14.00' WEST TO THE TRAVELED WAY OF THE ROAD TO THE SOUTH [EXTENDED]
- 3) 3.5' SOUTH TO THE TRAVELED WAY OF THE ROAD TO THE WEST [EXTENDED]
- 4) 17.35' NE TO A 40 D NAIL & 3 WASHERS IN A 16" HACKBERRY TREE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,628.65' WEST TO THE 5/8" REBAR HE FOUND WITH A LYON COUNTY CAP AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 23-19-11
- 2) 2,656.81' NORTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 23-19-11
- 3) 3,985.44' NORTH TO THE 1/2" REBAR HE FOUND WITH "BG CONSULTANTS" CAP AT THE WEST 1/16TH CORNER OF THE NE1/4 OF SECTION 23-19-11
- 4) 5,314.07' NORTH TO THE 5/8" REBAR HE FOUND WITH A 2" ALUMINUM CAP IN A MONUMENT WELL HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 23-19-11

NORTH QUARTER CORNER SECTION 26-19-11