

WEST 1/4 CORNER SECTION 26, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 360 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 8" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 27-19-11.

- 2) JAMES H. BROSEMER, L.S. 82, IN A LAND SURVEY REFERENCE REPORT DATED 1981 WHILE HE WAS KDOT CHIEF OF SURVEYS, FOR PROJECT 57-56-K0548-01 IN 1981, SAID THAT HE DETERMINED THAT THIS POINT FALLS IN A CULTIVATED FIELD WITH NO PHYSICAL EVIDENCE AND THAT THE CORNER WAS **NOT** SEARCHED FOR. HE SAID THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE EAST 1/4 CORNER OF SECTION 27-19-11 TO BE ON TRUE LINE AND 1/2 THE DISTANCE WITH THE SOUTHEAST & NORTHEAST CORNERS OF SECTION 27-19-11.
HE SAID THAT THE ROAD BETWEEN THE SOUTHWEST 1/4 OF SECTION 27-19-11 AND THE NORTHWEST 1/4 OF SECTION 34-19-11 HAS NO WIDTH RECORDED IN COMMISSIONERS JOURNAL 1 ON PAGE 269 OR IN ROAD RECORD BOOK "A" ON PAGE 127, OR IN ROAD RECORD BOOK "B" ON PAGE 135. WHEN NO WIDTH IS GIVEN THE ROAD IS 40' BY THE COUNTY ENGINEER.

WEST QUARTER CORNER SECTION 26-19-11