

**WEST 1/4 CORNER SECTION 27, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 366 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 7" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 28-19-11.
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 13, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 13 DATED FEBRUARY 24, 1870 TO ESTABLISH THE CENTER OF SECTION 28-19-11 AND TO SUBDIVIDE THE NORTHEAST 1/4 INTO 1/4/4 LOTS, SAID THAT THE EAST 1/4 CORNER OF SECTION 28-19-11 WAS **LOST. HE SET A STONE** FOR THE EAST 1/4 CORNER OF SECTION 28-19-11 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND DOWN AND HE RESET BY THE MUTUAL CONSENT OF ALL OF THE INTERESTED PARTIES AT THE SOUTHEAST CORNER OF SECTION 28-19-11, AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-19-11 ON THIS **PERMANENT SURVEY.**  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 1,315' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 28-19-11
  - 2) 2,630' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-19-11
  - 3) 2,630' SOUTH TO THE STONE HE FOUND DOWN AND **HE RESET** BY THE MUTUAL CONSENT AT THE SOUTHEAST CORNER OF SECTION 28-19-11
  - 4) 1,320-1/4' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 28-19-11
  - 5) 2,640-1/2' WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 28-19-11
  
- 3) JAMES H. BROSEMER, L.S. 82, IN A LAND SURVEY REFERENCE REPORT DATED 1981 WHILE HE WAS KDOT CHIEF OF SURVEYS, FOR PROJECT 57-56-K0548-01 IN 1981, SAID THAT **HE FOUND THE 4" X 7" X 20" GLO LIMESTONE AT 15" DEEP** AT THE WEST 1/4 CORNER OF SECTION 27-19-11. **HE PLACED A 1/2" REBAR OVER THE CENTER OF THE STONE AND SET AN ALUMINUM KDOT CAP STAMPED "W 1/4 27-19-11"** ON THE REBAR FOR THE WEST 1/4 CORNER OF SECTION 27-19-11.
  - 1) 29.6' NW TO A SPIKE & KDOT WASHER IN A POWER POLE
  - 2) 90.8' SSW TO A SPIKE & KDOT WASHER IN A POWER POLE
  - 3) 51.6' WEST TO THE CENTER AT THE TOP OF A 4" STEEL WATER LINE MARKER
  
- 4) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 6, 1996, **FOUND THE KDOT ALUMINUM CAPPED REBAR THAT IS OVER THE CENTER OF THE GLO LIMESTONE ACCORDING TO THE KDOT TIES AT 9" BELOW THE GRAVEL ROAD SURFACE** AT THE WEST 1/4 CORNER OF SECTION 27-19-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY JAMES H. BROSEMER, L.S. 82, IN 1981.
  - 1) 49.0' NE TO A PK NAIL & WASHER IN AN 18" CIRCUMFERENCE HEDGE TREE
  - 2) 37.4' SE TO A PK NAIL & WASHER IN A 50" CIRCUMFERENCE TREE
  - 3) 51.4' WEST TO THE TOP CENTER OF A 4" STEEL PIPE WATER LINE MARKER
  - 4) 2' EAST TO THE CENTERLINE TRAVELED WAY OF ROAD NORTH-SOUTH
  - 5) 12' NORTH TO THE CENTERLINE TRAVELED WAY OF A FIELD ENTRANCE TO THE EAST
  - 6) 18' SOUTH TO A CROP LINE TO THE EAST

WEST QUARTER CORNER SECTION 27-19-11