

NORTHWEST CORNER SECTION 28, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 371 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 24" X 12" X 5"** FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-19-11 ON MARCH 26, 1857.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH TO THE 19" X 13" X 5" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 29-19-11
 - 2) 80.00 CHAINS SOUTH TO THE 24" X 10" X 5" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-19-11
 - 3) 39.89 CHAINS EAST TO THE 19" X 10" X 5" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 21 & 28-19-11
 - 4) 79.78 CHAINS EAST TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 21, 22, 27 & 28-19-11
- 2) JAMES MEANS. COUNTY SURVEYOR FROM 1865 TO 1867, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 77 & 78 [PACKET 150 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY JOHN R. GRIFFITH AND OTHERS FOR A ROAD IN EMPORIA TOWNSHIP THAT WAS SURVEYED JULY 20, 1867 AND ACCEPTED AND ESTABLISHED IN THE COMMISSIONERS JOURNAL ON PAGE 184 ON SEPTEMBER 2, 1867 FOR A 40 FOOT WIDE ROAD, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 21-19-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR ONE MILE TO THE SOUTHWEST CORNER OF SECTION 22-19-11 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 120 RODS TO THE BANK OF THE COTTONWOOD RIVER; THENCE SW 44 CHAINS 64 LINKS ALONG SAID RIVER BANK SW 33° [FOR] 32 RODS 63 LINKS; THENCE ALONG SAID RIVER BANK SW 58° [FOR] 24 RODS 10 LINKS; THENCE SW 81°30' [FOR] 64 RODS 7 LINKS; THENCE WEST PAST JONATHAN WHEELER'S HOUSE 53 RODS; THENCE SW ALONG THE NORTH LINE OF A RAVINE 40 RODS 12 LINKS TO THE NE1/4 OF SECTION 30-19-11; THENCE WEST ALONG THE CENTER LINE OF SECTION 30 [FOR] 250 RODS; THENCE NORTH 60 LINKS; THENCE WEST 70 RODS INTERSECTING A ROAD GOING ALONG PIKE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY.
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 6 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 61 DATED FEBRUARY 26, 1874 TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 20-19-11 INTO NORTH AND SOUTH HALVES, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 20-19-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,322' NORTH TO THE 20" X 16" X 3" LIMESTONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 20-19-11
 - 2) 2,644' NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 20-19-11
- 4) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 159 DATED JUNE 8, 1883 AT THE REQUEST OF TOM PRICE TO SURVEY TO ESTABLISH THE 1/8TH CORNERS ON THE NORTH AND SOUTH LINES OF THE NORTHWEST 1/4 OF SECTION 28-19-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 28-19-11 ON THIS **INFORMAL SURVEY**.

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 19.98-1/2 CHAINS EAST TO THE STONE HE SET FOR THE NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 28-19-11
 - 2) 39.97 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 28-19-11
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 41, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 222 DATED APRIL 25, 1902 AT THE ORDER OF J. M. STEEL TO SURVEY A 5 ACRE TRACT IN THE SOUTHWEST 1/4 OF SECTION 21-19-11, SAID THAT **HE FOUND THE STONE AT 20 FEET SOUTH AND 25 FEET WEST OF A CORNER OF A HEDGE** AT THE SOUTHWEST CORNER OF SECTION 21-19-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 52.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.10 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 21-19-11
 - 2) 40.18 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 21-19-11
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 60, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 140 DATED APRIL 25, 1902 FOR A ROAD IN TOWNSHIP 19, RANGE 11 FOR E. M. HEIDT THAT WAS ACQUIRED BY PURCHASE, SAID THAT **HE FOUND THE STONE AT 20 FEET SOUTH AND 25 FEET WEST OF THE CORNER OF A HEDGE** AT THE SOUTHWEST CORNER OF SECTION 21-19-11 TO BEGIN THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 153 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.

HIS NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 20.10 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/2/4 CORNER OF THE SW1/4 OF SECTION 21-19-11, IN THE MIDDLE OF THE ROAD AND ON LINE WITH A HEDGE TO THE WEST
 - 2) 31.75 CHAINS NORTH TO THE STAKE MARKED "A" HE SET AT AN ANGLE TO THE NORTHEASTERLY ON THIS ROAD SURVEY
 - 3) 40.18 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 21-19-11, AT 52 LINKS EAST AND 7 LINKS SOUTH OF AN 18" ELM TREE
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 576 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 169 THROUGH 172 PETITION BY E. M. HEIDT AND OTHERS FOR A ROAD IN TOWNSHIP 19-11 [PACKET 622 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 8, 1902, SAID THAT **HE FOUND THE STONE AT 20 FEET SOUTH AND 25 FEET WEST OF THE CORNER OF A HEDGE** AT THE SOUTHEAST CORNER OF SECTION 20-19-11 ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD, 25 FEET ON EACH SIDE OF THE LINE AS SURVEYED. HE NOTED THAT THIS ROAD WAS ACQUIRED BY PURCHASE BY THE DEEDS RECORDED IN BOOK 73 ON PAGE 578, BOOK 73 ON PAGE 442, AND BOOK 73 ON PGE 443 IN THE REGISTER OF DEEDS OFFICE. SEE THE SURVEY REPORT ON PAGE 172 FOR THE LOCATION OF THE CENTERLINE OF THIS ROAD SURVEY.

- 8) ANSON B. HARVEY, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 87, A **PRIVATE AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 167 DATED FEBRUARY 1, 1904 BY THE ORDER OF EVEN R. GRIFFITH TO SURVEY THE NORTHEAST 1/4 OF SECTION 29-19-11, SAID THAT **HE FOUND THE STONE AT THE NORTHEAST CORNER OF SECTION 29-19-11 ON THIS PRIVATE AGREEMENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 20 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.97 CHAINS SOUTH TO THE STAKE HE SET FOR THE EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 29-19-11
 - 2) 39.94 CHAINS SOUTH TO THE STAKE HE SET FOR THE EAST 1/4 CORNER OF SECTION 29-19-11
 - 3) 79.89 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-19-11
 - 4) 39.86 CHAINS WEST TO THE 1' X 8" X 2" STONE HE SET FOR THE NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 29-19-11. [**NOTE:** HIS SURVEY DRAWING SHOWS THAT HE SET THE STONE AT THE 1/2/4 CORNER AND HE DOES NOT SHOW A MONUMENT AT THE NORTH 1/4 CORNER SO THIS NUMBER COULD BE 19.86 CHAINS. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 9) O. D. HENRY, COUNTY ENGINEER FROM 1929 TO 1944, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 102 FOR A SURVEY MADE APRIL 3, 1931 AT THE REQUEST OF THE EMPORIA TOWNSHIP BOARD TO WIDEN THE TOWNSHIP ROAD ALONG THE COTTONWOOD RIVER WHERE IN PLACES THE RIVER WAS ENCROACHING ON THE ROAD BY HE BANK CAVING IN IN THE NORTHEAST 1/4 OF SECTION 29-19-11, SAID THAT **HE FOUND THE GOVERNMENT STONE IN GOOD CONDITION** AT THE NORTHEAST CORNER OF SECTION 29-19-11 ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THE SURVEY. THERE IS ALSO AN INSERT DATED NOVEMBER 1965 THAT ADDED ADDITIONAL WIDTH TO THIS ROAD. THE ORIGINAL SURVEY AND INSERT GIVE THE FOLLOWING INFORMATION:
- 1) 1,309.85' WEST TO THE 1/8TH STONE HE FOUND IN PLACE THAT WAS SET ON A PREVIOUS SURVEY
 - 2) 1,921.75' WEST TO THE IRON PIN HE SET FOR THE 1965 ROAD WIDENING SURVEY
 - 3) 1,961.75' WEST TO THE 9" X 5" X 20" ROAD STONE HE SET ON THE 1931 ROAD WIDENING SURVEY
- 10) ON PAGE 130 IN BOOK "D" IN THE KRETSINGER COLLECTION DATED MARCH 29, 1934, IT STATES THAT THEY "UNCOVERED THE STONE AT THE SOUTHWEST CORNER OF SECTION 21-19-11". ON PAGE 133 THEY GIVE THE FOLLOWING TIES TO THE **SANDSTONE AND IRON PIN** AT THE SOUTHWEST CORNER OF SECTION 21-19-11 DATED SEPTEMBER 14, 1945:
- 1) 43.5' SE TO A GUY POLE
 - 2) 43.2' SW TO A TRANSMISSION POLE
- 11) ON PAGE 135 IN BOOK "D" IN THE KRETSINGER COLLECTION DATED JULY 9-14, 1945, IT STATES THAT **THEY FOUND THE SANDSTONE WITH 4 MARKS ON THE EAST SIDE** AT THE SOUTHWEST CORNER OF SECTION 21-19-11.
- 1) 57.5' NW TO A NAIL IN AN ELM TREE ABOUT 1 FOOT ABOVE GROUND
 - 2) 42.7' SE TO AN OSAGE TELEPHONE POLE
 - 3) 27.33' NW TO A KEP TRANSMISSION POLE
- 12) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY L. M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 102 AND DATED NOVEMBER 1946, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 29-19-11 ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THE SURVEY. HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,921.75' WEST TO THE IRON PIN HE SET ON THIS SURVEY
 - 2) 1,961.75' WEST TO THE ROAD STONE HE FOUND ON THIS SURVEY

CONTINUED ON PAGE 4

- 13) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS A **PIN OVER STONE** AT THE "CORNER TO SECTIONS 20, 21, 28 & 29-19-11".
 - 1) 27.4' NW TO A LIGHT POLE
 - 2) 25' WEST AND 20' SOUTH OF A HEDGE

- 14) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS A **PIN OVER STONE** AT THE "NE CORNER SECTION 29-19-11".
 - 1) 46.00' GAS PIPE TO SE
 - 2) 44.50' GAS PIPE TO NE
 - 3) 28.15' POWER POLE TO NW

- 15) KRETSINGER REFERENCE TIE BOOK NUMBER 13 ON PAGE 53 SHOWS A **SANDSTONE** AT THE "SW CORNER SECTION 21-19-11".
 - 1) 29' NW TO THE NEAR FACE OF A POWER POLE
 - 2) 42' SW TO THE NEAR FACE OF A TELEPHONE POLE
 - 3) 52.7' NE TO A NAIL IN AN ELM TREE

- 16) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F29003 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE SURVEY OF A 1 ACRE TRACT OF GROUND LOCATED IN THE NORTHEAST 1/4 OF SECTION 19-18-11 DATED MARCH 9, 1972, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE NORTHEAST CORNER OF SECTION 29-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY. HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 936.5' SOUTH TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE 1 ACRE TRACT AS WITNESSED BY THE 1/2" IRON PIN HE SET AT 25' WEST
 - 2) 1,095' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE 1 ACRE TRACT AS WITNESSED BY THE IRON PIN HE SET AT 25' WEST LOCATED IN THE CENTER OF A 22' CULVERT PIPE

- 17) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 12, 1982, SAID THAT **HE FOUND THE GLO SANDSTONE** AT THE SOUTHWEST CORNER OF SECTION 21-19-11 FROM INFORMATION IN THE COUNTY ENGINEERS OFFICE. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP OVER THE TOP CENTER OF THE STONE.**
 - 1) 28.6' NW TO A SPIKE & WASHER IN A POWER POLE
 - 2) 44.5' NE TO THE NEAR FACE OF A GAS LINE MARKER POST
 - 3) 50.0' SOUTH TO A SQUARE 1/2" REBAR
 - 4) 50.0' WEST TO A 5/8" ROUND REBAR

- 18) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F21001 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE SUBDIVISION OF SECTION 21-19-11 AND AN EASEMENT FOR THE CITY OF EMPORIA LOCATED IN THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SAID SECTION 21 FOR PROJECT NUMBER 90387 DATED JANUARY 5, 1991 AND RECORDED IN VOLUME 459 ON PAGE 353 IN THE REGISTER OF DEEDS OFFICE ON MAY 10, 1991 STATES IN HIS *REPORT OF SURVEY* THAT **HE FOUND THE GLO STONE WITH REBAR** AT THE SOUTHWEST CORNER OF SECTION 21-19-11. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES. HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,649.23' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 21-19-11
 - 2) 5,298.46' NORTH TO THE STONE & REBARS HE FOUND AT THE NORTHWEST CORNER OF SECTION 21-19-11

HIS INFORMATION IS CONTINUED ON PAGE 5

- 3) 2,645.38' EAST TO THE STONE & REBARS HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 21-19-11
 - 4) 3,970.04' EAST TO THE STONE & REBARS HE FOUND AT THE SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 21-19-11
 - 5) 5,291.12' EAST TO THE REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 21-19-11
- 19) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 1997, FOR JOB NUMBER 95024-02, THE GPS SURVEY OF EMPORIA AND LOCAL AREA, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE GLO SANDSTONE** AT THE SOUTHWEST CORNER OF SECTION 21-19-11 FROM HIS TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED OCTOBER 1982.
- 1) STATE PLANE COORDINATES IN U.S. FEET – GROUND LEVEL
NORTH = 1942813.693 EAST = 1969346.940
 - 4) 59.4' NW TO A SPIKE & WASHER IN A POWER POLE
 - 3) 53.7' NE TO A GAS LINE MARKER POST
 - 4) 63.2' SE TO A GAS LINE MARKER POST
 - 5) 3.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF ROAD 150 EAST-WEST
- 20) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F29005 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A SURVEY FOR A ROAD CHANGE IN THE NORTHWEST QUARTER OF SECTION 29-19-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 5/8" REBAR OVER THE GLO SANDSTONE** AT THE NORTHEAST CORNER OF SECTION 29-19-11. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,961.66' WEST TO THE ROAD STONE HE FOUND
 - 2) 2,634.19' WEST TO THE THEORETICAL POSITION FOR THE NORTH 1/4 CORNER OF SECTION 29-19-11 – FALLS IN THE RIVER
 - 3) 5,268.38' WEST TO THE **TRUE POSITION** FOR THE NORTHWEST CORNER OF SECTION 29-19-11, AS WITNESSED BY THE 5/8" REBAR **HE SET 100.00' SOUTH OF THE TRUE POSITION**
 - 4) 5,282.31' SOUTH TO THE 5/8" REBAR OVER THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-19-11
- 21) RAYMOND L. CORBETT, L.S. 1965, OF KAW VALLEY ENGINEERING, INC., IN A LAND SURVEY REFERENCE REPORT DATED JUNE 11, 2001, FOR JOB NUMBER A01S0243, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE GLO STONE** AT THE SOUTHWEST CORNER OF SECTION 21-19-11 RECOVERED FROM COUNTY SURVEYORS RECORDS.
- 1) 59.4' NW TO A SPIKE & WASHER IN A POWER POLE
 - 2) 53.7' NE TO A GAS LINE MARKER POST
 - 3) 63.2' SE TO A GAS LINE MARKER POST
 - 4) IN THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD INTERSECTION
- 22) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 8, 2011 FOR PROJECT NUMBER 11071-02, A SURVEY OF PART OF TRACT 2 AND ALL OF TRACT 3 IN SECTION 20-19-11 FOR JOHN & BROCK KRETSINGER, SURVEY F20003 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE GLO SANDSTONE** AT THE SOUTHEAST CORNER OF SECTION 20-19-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE. HE NOTED THAT HE HAD FOUND THIS GLO STONE IN 1982.

- 1) 2.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 150 TO THE WEST
- 2) 8' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 150 TO THE EAST
- 3) 59.4' NW TO A SPIKE & WASHER IN A POWER POLE
- 4) 53.7' NE TO A GAS LINE MARKER POST
- 5) 63.2' SE TO A GAS LINE MARKER POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,634.34' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 20-19-11 – FALLS IN CULTIVATION
 - 2) 5,268.68' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 20-19-11, AS **WITNESSED BY A 5/8" REBAR HE SET 100.00 FEET SOUTH**
- 23) RONALD J. SHANKS, P.S. 1255 OF BARTLETT & WEST IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 14, 2015 FOR PROJECT NUMBER 16521-2252, SAID THAT **HE FOUND THE EXISTING 5/8" REBAR WITH A PARTIAL ORANGE PLASTIC CAP (NOT IDENTIFIABLE)** AT THE NORTHEAST CORNER OF SECTION 29-19-11 FROM A LAND SURVEY REFERENCE REPORT BY PS #752 DATED 4-1-2004. HE SENT THE FOLLOWING **HORIZONTAL TIES**. [**NOTE:** TIES BY STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR DATED APRIL 8, 2001 INDICATE THAT THIS 5/8" REBAR IS OVER THE GLO SANDSTONE! WARREN CHIP WOODS, P. S. 603, COUNTY SURVEYOR]
- 1) NAD 83 COORDINATES: NORTH: 1942813.300000 EAST: 1969347.030000
 - 2) 59.43' NW TO A NAIL & WASHER IN THE EAST FACE OF A POWER POLE
 - 3) 59.52' SSW TO A NAIL & BOTTLECAP IN THE EAST FACE OF A POWER POLE
 - 4) 78.10' ESE TO A MAG NAIL IN THE NORTHEAST FACE OF A GUY POLE
 - 5) 8' SOUTH TO THE TRAVELED WAY OF COUNTY ROAD 150 TO THE EAST
 - 6) 2' EAST TO THE TRAVELED WAY OF COUNTY ROAD J
 - 7) 0.3' BELOW THE ROAD SURFACE

NORTHWEST CORNER SECTION 28-19-11