

**CENTER CORNER SECTION 29, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 7, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 7 DATED JANUARY 28, 1870 TO PERMANENTLY ESTABLISH THE CENTER CORNER AND TO DIVIDE THE NORTHWEST 1/4 EQUALLY BY A LINE RUNNING NORTH & SOUTH AND THE SOUTHWEST 1/4 BY A LINE RUNNING EAST & WEST, ALL IN SECTION 29-19-11, SAID THAT **HE SET A STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 29-19-11 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 1,316-1/4' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SW1/4 OF SECTION 29-19-11
  - 2) 2,632-1/2' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 29-19-11
  
- 2) ANSON B. HARVEY, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 87, A **PRIVATE AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 167 DATED FEBRUARY 1, 1904 BY THE ORDER OF EVEN R. GRIFFITH, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 29 ON THIS **PRIVATE AGREEMENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 20 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 19.97-1/2 CHAINS EAST TO A STAKE HE SET FOR THE 1/2/4 CORNER ON THE SOUTH SIDE OF THE NE1/4 OF SECTION 29
  - 2) 39.95 CHAINS EAST TO A STAKE HE SET FOR THE EAST 1/4 CORNER OF SEC. 29
  
- 3) W. S. RUGGLES, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 82 DATED JANUARY 15, 1920 FOR THE L. REES ESTATE FOR A TRACT IN THE NORTHWEST 1/4 OF SECTION 29-19-11 BY THE **MUTUAL CONSENT** OF THE INTERESTED PARTIES, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE CENTER OF SECTION 29** ON THIS **MUTUAL CONSENT** SURVEY. HE DOES NOT DESCRIBE THE MONUMENT AT THIS CORNER.
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED FEBRUARY 22, 1999, FOR JOB NUMBER 96308, SURVEY F29005 IN THE SURVEY FILE FOR SECTION 17-36 IN TOWNSHIP 19-11 FOR A ROAD CHANGE IN THE NORTHWEST QUARTER OF SECTION 29-19-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT, SAID THAT **HE FOUND A 4" X 10" LIMESTONE WITH "CC" ON THE EAST FACE THAT WAS FOUND BY ALVA J. SMITH IN 1904 IN SURVEY BOOK "F" ON PAGE 167** AT THE CENTER CORNER OF SECTION 29. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP ON THE EAST SIDE OF THE STONE.**
  - 1) 8.5' SE TO A 40 D SPIKE & SHINER IN A TWIN 24" COTTONWOOD TREE
  - 2) 3.7' SSW TO A 40 D SPIKE & SHINER IN A TWIN 10" HEDGE TREE
  - 3) 4.3' SOUTH TO A LONE HEDGE POST
  - 4) IN LINE WITH OLD FENCE POSTS TO THE EASTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,634.13' WEST TO A 5/8" REBAR WITH LYON COUNTY CAP HE FOUND AT THE WEST 1/4 CORNER OF SECTION 29
  - 2) 1,120.00' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE ANGLE POINT FROM THE 1946 ROAD CHANGES
  - 3) 1,172.34' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH CORNER OF THE 1946 ROAD CHANGES

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 2,644.21' NORTH TO THE THEORETICAL POSITION FOR THE NORTH 1/4 CORNER OF SECTION 29 – FALLS IN THE RIVER
  - 5) 2,627.44' SOUTH TO A 5/8" REBAR OVER THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 29
- 5) RONALD J. SHANKS, P.S. 1255 OF BARTLETT & WEST IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 14, 2015 FOR PROJECT NUMBER 16521-2252, SAID THAT **HE FOUND THE EXISTING 10" X 4" LIMESTONE** AT THE CENTER CORNER OF SECTION 29-19-11 FROM A LAND SURVEY REFERENCE REPORT BY PS #752 DATED 2-22-1999. HE SENT THE FOLLOWING **HORIZONTAL TIES:**
- 1) NAD 83 COORDINATES: NORTH: 1940112.320000 EAST: 1966784.460000
  - 2) **STONE PROJECTS 0.5' ABOVE THE GROUND SURFACE**
  - 3) **0.20' EAST TO A 5/8" REBAR WITH A LYON COUNTY PLASTIC CAP**
  - 4) 8.18' SE TO A 60 D NAIL IN THE WEST FACE OF A 40" COTTONWOOD TREE
  - 5) 3.60' SSW TO A NAIL & SHINER IN THE NORTH FACE OF A 15" OSAGE ORANGE TREE
  - 6) 4.30' SOUTH TO A MAG NAIL IN THE EAST FACE OF A HEDGE FENCE POST

CENTER QUARTER CORNER SECTION 29-19-11