

**NORTH 1/16<sup>TH</sup> CORNER NORTHWEST QUARTER OF SECTION 29, TOWNSHIP 19 SOUTH,  
RANGE 11 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 7, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 7 DATED JANUARY 28, 1870 TO ESTABLISH THE CENTER CORNER AND TO DIVIDE THE NORTHWEST 1/4 EQUALLY BY A LINE RUNNING NORTH & SOUTH AND THE SOUTHWEST 1/4 BY A LINE RUNNING EAST & WEST, ALL IN SECTION 29-19-11, SAID THAT **HE SET A STONE** FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 29 ON LINE AND HALFWAY BETWEEN THE STONES HE FOUND AT THE NORTHWEST AND NORTH 1/4 CORNERS OF SECTION 29 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 1,322' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SEC. 29
  - 2) 1,322' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SEC. 29
  
- 2) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 94, FOR THE SURVEY OF A 55.64 ACRE TRACT IN THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 20-19-11, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 20 ON THIS **PERMANENT SURVEY**. THE FIELD SURVEY WAS COMPLETED JUNE 3, 1920 AND THE SURVEY WAS RECORDED JUNE 11, 1920.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 1,320.5' WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 20

NORTH SIXTEENTH CORNER NORTHWEST QUARTER SECTION 29-19-11