

**NORTH 1/16<sup>TH</sup> CORNER SOUTHWEST QUARTER OF SECTION 29, TOWNSHIP 19 SOUTH,  
RANGE 11 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 7, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 7 DATED JANUARY 28, 1870 TO ESTABLISH THE CENTER CORNER AND TO DIVIDE THE NORTHWEST 1/4 EQUALLY BY A LINE RUNNING NORTH & SOUTH AND THE SOUTHWEST 1/4 BY A LINE RUNNING EAST & WEST, ALL IN SECTION 29-19-11, SAID THAT **HE SET A STONE** FOR THE PERMANENT 1/2/4 CORNER ON THE SOUTH SIDE OF THE NORTHWEST 1/4 OF SECTION 29 ON LINE AND HALFWAY BETWEEN THE STONE HE FOUND AT THE WEST 1/4 CORNER AND THE STONE HE SET FOR THE PERMANENT CENTER OF SECTION 29 ON THIS **PERMANENT SURVEY**.
  
- 2) W. S. RUGGLES, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 82 DATED JANUARY 15, 1920 FOR THE L. REES ESTATE FOR A TRACT IN THE NORTHWEST 1/4 OF SECTION 29-19-11 BY THE MUTUAL CONSENT OF THE INTERESTED PARTIES, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 29 ON THIS MUTUAL CONSENT SURVEY.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:
  - 1) 1,320' WEST TO A GAS PIPE HE SET FOR THE SOUTHWEST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 29
  - 2) 750' NORTH TO A GAS PIPE HE SET FOR THE NORTHEAST PARCEL CORNER
  - 3) 993' NORTH TO THE CENTER OF THE PUBLIC ROAD

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER SECTION 29-19-11