

NORTHWEST CORNER SECTION 30, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 43 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A POST** FOR THE CORNER OF SECTIONS 19 & 30-19-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 27, 1856, FROM WHICH:
 - 1) AN ASH TREE 12" IN DIAMETER BEARS N. 71° E. AT 4 LINKS DISTANCE
 - 2) A SYCAMORE TREE 18" IN DIAMETER BEARS S. 29° E. AT 20 LINKS DISTANCE
 - 3) A BOX ELDER TREE 13" IN DIAMETER BEARS N. 50° W. AT 31 LINKS DISTANCE
 - 4) AN ELM TREE 13" IN DIAMETER BEARS S. 46-1/2° W. AT 43 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) 38.05 CHAINS EAST TO THE LOCATION FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-19-11, AS WITNESSED BY THE POST OF MULBERRY THEY SET ON TRUE LINE BETWEEN SECTIONS 19 & 30-19-111 AT 150 LINKS WEST OF THE 1/4 SECTION POINT THAT FALLS IN THE CREEK
 - 2) 78.05 CHAINS EAST TO THE 24" X 9" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-19-11
 - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 27" X 15" X 2" SANDSTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 30-19-11
 - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 26" X 17" X 2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-19-11

- 2) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1865, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGE 43 AND DATED JANUARY 1864, SAID THAT **HE FOUND** THE NORTHWEST CORNER OF SECTION 30-19-11 ON THE RANGE LINE ON THIS ROAD SURVEY.

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 47 AND DATED DECEMBER 1873, SAID THAT **HE FOUND** THE NORTHWEST CORNER OF SECTION 30-19-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,654' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 30-19-11

- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY C. P. COWEN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 116, A **PERMANENT SURVEY** AT THE REQUEST OF GEORGE CRICKLAND TO ESTABLISH THE LINES AND CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 6-20-11 RECORDED IN SURVEY BOOK "F" ON PAGE 132 DATED MAY 1-9, 1888, SAID THAT **HE FOUND THE POINT** FOR THE NORTHWEST CORNER OF SECTION 30-19-11 ON THE RANGE LINE FROM WITNESS TREES ON THIS **PERMANENT SURVEY**. HE DID NOT SAY IF HE SET A MONUMENT FOR THIS CORNER ON THIS SURVEY.
 - 1) A SYCAMORE TREE BEARS S. 29° E. AT 13.2'
 - 2) THE ELM TREE, BOX ELDER TREE AND ASH WITNESS TREES FROM PREVIOUS TIES COULD NOT BE FOUND

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 56, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 237 DATED MAY 13, 1902 ORDERED BY W. S. WILLIAMSON TO SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER OF SECTION 25-19-10 AND THE CORNERS AND BOUNDARIES OF A TRACT OF LAND IN THE NORTHEAST CORNER OF SECTION 25-19-10, SAID THAT **HE SET AN 18" X 10" X 4" STONE** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 25-19-10 ON THE RANGE LINE AT HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 24-19-10 AND THE STONE THAT HE FOUND

AT THE EAST 1/4 CORNER OF SECTION 25-19-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 66, AND ADDITIONAL INFORMATION IS IN PACKET "M 47" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE. HE MARKED THE FOLLOWING WITNESS TREES:

- 1) A 12" MULBERRY TREE IS N. 68° W. AT 21.5 FEET DISTANCE
- 2) A 36" SYCAMORE TREE IS S. 57°30' W. AT 15.5 FEET DISTANCE
- 3) A 6" BOX ELDER TREE IS N. 60° E. AT 10 FEET 10" DISTANCE

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.06 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 24-19-10
- 2) 40.06 CHAINS SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 25-19-10

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F30001 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE SURVEY OF A TRACT OF LAND IN THE SOUTHWEST QUARTER OF SECTION 31-19-11 FOR PROJECT 960307 DATED JANUARY 24, 1999, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 30-19-11, BUT HIS TIES ARE MISSING FROM THE SURVEY TIE FILES. HE DEVELOPED STATE PLANE COORDINATES FOR THE RANGE LINE FROM THE WEST 1/4 CORNER OF SECTION 19-19-11 TO THE SOUTHWEST CORNER OF SECTION 30-19-11 AS A STRAIGHT LINE WITH A BEARING OF S. 01°09'36" E. AND HE GAVE THE FOLLOWING STATE PLANE COORDINATES TO ME ON JULY 20, 2004:

WEST 1/4 CORNER SECTION 19-19-11:

NORTH	1945194.080
EAST	1958833.193

NORTHWEST CORNER SECTION 30-19-11:

NORTH	1942553.557
EAST	1950006.654

WEST 1/4 CORNER SECTION 30-19-11

NORTH	1939913.034
EAST	1958940.115

SOUTHWEST CORNER SECTION 30-19-11

NORTH	1937272.511
EAST	1958993.577

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,641.06' SOUTH ON THE RANGE LINE TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 30-19-11 – FALLS IN THE RIVER
- 2) 2,741.06' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE TRACT SURVEYED
- 3) 5,282.12' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-19-11

NORTHWEST CORNER SECTION 30-19-11