

WEST 1/4 CORNER SECTION 30, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 43 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 27" X 15" X 2"** FOR THE WEST 1/4 CORNER OF SECTION 30-19-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 27, 1856.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE POST THEY SET FOR THE CORNER TO SECTIONS 19 & 30-19-11
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 26" X 17" X 2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-19-11
- 2) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN SURVEY NUMBER 6 RECORDED IN SURVEY BOOK "A" ON PAGE 50 FOR THE DESCRIPTION OF A SECTION OF ROAD SURVEYED MARCH 16, 1860, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 30-19-11 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY.
- 3) JAMES MEANS, COUNTY SURVEYOR FROM 1865 TO 1867, IN SURVEY NUMBER 7 IN THE 4TH TERM RECORDED ON PAGE 93 IN SURVEY BOOK "A" DATED JULY 20, 1867, FOR A ROAD SURVEY IN TOWNSHIP 19-11, SAID THAT HE ENDED THIS ROAD SURVEY AT 72 LINKS NORTH OF THE **GOVERNMENT 1/4 POST** AT THE WEST 1/4 CORNER OF SECTION 30-19-11 ON THE RANGE LINE. HE NOTED THAT THIS ROAD WAS TO BE "40 FEET WIDE THE WHOLE WAY".
- 4) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 46, SURVEY 129 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 45 DATED MAY 13, 1870 TO DIVIDE THE SOUTHEAST 1/4 OF SECTION 25-19-10 INTO 2 EQUAL PARTS BY A LINE PASSING NORTH & SOUTH THROUGH IT, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 25-19-10 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,323-1/4' WEST TO THE POST HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 25-19-10
 - 2) 2,646-1/2' WEST TO THE POST HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 25-19-10
 - 3) 5,293' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 25-19-10
 - 4) 2,637' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-19-11
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY D. T. McAULEY, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 205 [PACKET 56 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY H. C. THOMPSON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-11 THAT HE SURVEYED OCTOBER 18, 1872, AND WAS ORDERED ESTABLISHED AS A 60 FOOT WIDE ROAD BY THE BOARD OF COUNTY COMMISSIONERS ON JANUARY 6, 1873 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT HE ENDED THIS ROAD SURVEY AT A POINT 80 RODS EAST OF THE WEST 1/4 CORNER OF SECTION 30-19-11 ON THE RANGE LINE.
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 47 AND DATED DECEMBER 1873, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER BETWEEN SECTIONS 25-19-10 & 30-19-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 2,654' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE CORNER TO SECTIONS 24, 25, 19 & 30
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 129 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 51 DATED JANUARY 6, 1874 TO ESTABLISH THE CENTER CORNER AND THE 1/2/4 CORNERS ON THE EAST AND WEST CENTER LINE OF SECTION 25-19-10, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 25-19-10 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HE SAID TO REFER TO SURVEYS 48 AND 127 OF THE 6TH TERM.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320-3/4' WEST TO THE 14" X 10" X 2" LIMESTONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 25-19-10
- 2) 2,641-1/2' WEST TO THE POST HE FOUND AT THE CENTER CORNER OF SECTION 25-19-10 THAT **HE REPLACED** WITH A 15" X 8" X 6" LIMESTONE FOR THE PERMANENT CENTER CORNER OF SECTION 25-19-10
- 3) 3,965-3/4' WEST TO THE 20" X 10" X 2-1/2" LIMESTONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NW1/4 OF SEC. 25-19-10
- 4) 5,290' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 25-19-10
- 8) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 42, A ROAD SURVEY IN TOWNSHIP 19, RANGES 10 & 11 RECORDED IN SURVEY BOOK "E" ON PAGE 42 DATED JUNE 17, 1884 FOR T. H. WILLIAMS, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 25-19-10 ON THE RANGE LINE TO BEGIN THIS ROAD SURVEY.
- 9) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 275 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 50 TO 52 PETITIONED BY T. H. WILLIAMS AND OTHERS FOR THE VACATION AND RELOCATION OF COUNTY ROADS IN TOWNSHIPS 19-10, 19-11, 20-10 AND 20-11 [PACKET 522 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 17, 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 10, 1884, AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON DECEMBER 9, 1884 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 25-19-10 ON THE RANGE LINE TO BEGIN THIS ROAD SURVEY. [NOTE: THE ROAD EXTENDING SOUTH ON THE RANGE LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-19-10 WAS **NOT ALLOWED** BY THE VIEWERS - WARREN CHIP WOODS, L.S. 603 - COUNTY SURVEYOR]
- 10) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 56, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 237 DATED MAY 13, 1902 ORDERED BY W. S. WILLIAMSON TO SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER OF SECTION 25-19-10 AND THE CORNERS AND BOUNDARIES OF A TRACT OF LAND IN THE NORTHEAST CORNER OF SECTION 25-19-10, SAID THAT AFTER MEASURING EAST FROM THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 25-19-10 AND THE 1/8TH STONE HE FOUND ON THE SOUTH SIDE OF THE NORTHEAST 1/4 OF SECTION 25-19-10, HE DUG AND **HE FOUND THE STONE AT 3' EAST OF THE MIDDLE OF THE ROAD AND 1' SOUTH OF A FENCE RUNNING EAST** AT THE EAST 1/4 CORNER OF SECTION 25-19-10 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE

66, AND ADDITIONAL INFORMATION IS IN PACKET "M 47" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.06 CHAINS NORTH ON THE RANGE LINE TO THE 18" X 10" X 4" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 25-19-10
 - 2) 80.12 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 24-19-10
 - 3) 20.05 CHAINS WEST TO THE STONE HE FOUND ON THE NORTH 1/8TH CORNER OF THE SE1/4 OF SECTION 25-19-10
 - 4) 80.20 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 25-19-10
- 11) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 141 AND DATED NOVEMBER 1902, SAID THAT **HE FOUND THE STONE AT 3' EAST OF THE MIDDLE OF THE ROAD AND 1' SOUTH OF A FENCE RUNNING EAST** AT THE WEST 1/4 CORNER OF SECTION 30-19-11 ON THE RANGE LINE ON THIS ROAD SURVEY.
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F30001 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE SURVEY OF A TRACT OF LAND IN THE SOUTHWEST QUARTER OF SECTION 31-19-11 FOR PROJECT 960307 DATED JANUARY 24, 1999, SHOWS ON HIS SURVEY DRAWING THAT THE LOCATION FOR THE WEST 1/4 CORNER OF SECTION 30-19-11 FALLS IN THE RIVER. HE DEVELOPED STATE PLANE COORDINATES FOR THE RANGE LINE FROM THE WEST 1/4 CORNER OF SECTION 19-19-11 TO THE SOUTHWEST CORNER OF SECTION 30-19-11 AS A STRAIGHT LINE WITH A BEARING OF S. 01°09'36" E. AND HE DETERMINED A **THEORETICAL POSITION** FOR THE WEST 1/4 CORNER OF SECTION 30-19-11 TO BE ON THAT LINE. HE GAVE THE FOLLOWING STATE PLANE COORDINATES TO ME ON JULY 20, 2004:

WEST 1/4 CORNER SECTION 19-19-11:

NORTH	1945194.080
EAST	1958833.193

NORTHWEST CORNER SECTION 30-19-11:

NORTH	1942553.557
EAST	1950006.654

WEST 1/4 CORNER SECTION 30-19-11:

NORTH	1939913.034
EAST	1958940.115

SOUTHWEST CORNER SECTION 30-19-11:

NORTH	1937272.511
EAST	1958993.577

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,641.06' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-19-11
- 2) 100.00' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE TRACT SURVEYED
- 3) 2,641.06' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-19-11
- 4) 500.00' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE TRACT SURVEYED, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 20.00' SOUTH

HIS INFORMATION IS CONTINUED ON PAGE 4

- 5) 2,555.13' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 30-19-11

WEST QUARTER CORNER SECTION 30-19-11