

WEST 1/4 CORNER SECTION 31, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 43 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 25" X 12" X 2"** FOR THE WEST 1/4 CORNER OF SECTION 31-19-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 27, 1856.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 26" X 17" X 2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-19-11
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 14" X 2-1/2" SANDSTONE WITH A MOUND OF ROCKS THEY SET FOR THE CORNER TO TOWNSHIPS 19 & 20 SOUTH, RANGES 10 & 11 EAST AT THE SOUTHWEST CORNER OF SECTION 31-19-11
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 22, 2007 FOR PROJECT NUMBER 07230-02, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF TWO TRACTS IN THE WEST HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-10 FOR NELLIE OWENS, SAID THAT HE DETERMINED THAT THE EAST 1/4 CORNER OF SECTION 36-19-10 ON THE RANGE LINE WAS **LOST. HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 36-19-10 ON THE RANGE LINE.
- 1) 67.25' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 2) 26.6' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 3) 18.35' WEST TO A 40 D NAIL & WASHER IN A 4" DIAMETER HEDGE TREE
 - 4) 41.85' SW TO A CONCRETE NAIL & WASHER IN THE SOUTH GATE POST
 - 5) IN LINE WITH A FENCE AND HEDGE TO THE WEST – EXTENDED
 - 6) 1.0' SOUTH TO A LINE OF FENCE TO THE EAST – EXTENDED
 - 7) 1.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "G" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,617.46' NORTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-19-10
 - 2) 2,650.50' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 36-19-10 AT THE TOWNSHIP CORNER
 - 3) 1,321.58' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 36-19-10
 - 4) 2,643.16' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF SECTION 36-19-10
 - 5) 5,281.88' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE WEST 1/4 CORNER OF SECTION 36-19-10
- 3) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN SURVEY F36004 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE NORTH HALF OF THE NORTHWEST QUARTER OF THE NORTHEAST QUARTER OF SECTION 36-19-10 FOR RICHARD MILLER FOR PROJECT NUMBER 07372-02 DATED NOVEMBER 2, 2007, HE SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE EAST 1/4 CORNER OF SECTION 36-19-10 ON THE RANGE LINE. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,308.73' NORTH ON THE RANGE LINE TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 36-19-10

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 1,965.16' NORTH ON THE RANG LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE S1/2 OF THE NE1/4 OF THE NE1/4 OF SECTION 36-19-10
- 3) 2,617.46' NORTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-19-10
- 4) 1,321.58' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 36-19-10
- 5) 2,643.16' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE CENTER CORNER OF SECTION 36-19-10

WEST QUARTER CORNER SECTION 31-19-11