

NORTH 1/4 CORNER SECTION 33, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 371 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 17" X 12" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 33-19-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.80-1/2 CHAINS WEST TO THE 24" X 10" X 5" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-19-11
 - 2) 39.80-1/2 CHAINS EAST TO THE 27" X 7" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-19-11

- 2) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN SURVEY NUMBER 26 RECORDED IN SURVEY BOOK "A" ON PAGE 61 DATED DECEMBER 7, 1860 TO ESTABLISH THE CENTER OF SECTION 33-19-11, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND** THE NORTH 1/4 CORNER OF SECTION 33-19-11 ON THIS SURVEY. HE DOES NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 161 RODS, 6 LINKS SOUTH TO THE STAKE HE SET FOR THE CENTER CORNER OF SECTION 33-19-11
 - 2) 321 RODS, 11 LINKS SOUTH TO THE SOUTH 1/4 CORNER OF SECTION 33-19-11

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 13, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 13 DATED FEBRUARY 24, 1870 TO ESTABLISH THE CENTER OF SECTION 28-19-11 AND TO SUBDIVIDE THE NORTHEAST 1/4 INTO 1/4/4 LOTS, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 28-19-11 ON THIS **PERMANENT SURVEY**.

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 98, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 98 DATED MAY 11, 1885 ORDERED BY MILTON CHAMNESS TO LOCATE THE CENTER OF SECTION 33-19-11, SAID THAT **HE FOUND THE ORIGINAL CORNER** AT THE NORTH 1/4 CORNER OF SECTION 33-19-11 FROM THE AFFIDAVIT OF GEORGE SUDDOCK, DAVID LLOYD, DAVID WILLIAMS, AND G. H SUDDOCK, AND CONFIRMED BY MILTON CHAMNESS, ON THIS **PERMANENT SURVEY**. THIS SURVEY IS ALSO RECORDED IN BOOK 41 ON PAGE 33 IN THE REGISTER OF DEEDS OFFICE.

- 5) AI CHAMNESS, DEPUTY COUNTY SURVEYOR FROM 1906 TO 1946, IN A BOOK LABELED "CHAMNESS BOOK Y" IN THE KRETSINGER COLLECTION, ON PAGES 46 TO 47 FOR A SURVEY OF THE NORTH LINE OF SECTION 33-19-11 AND DATED APRIL 23, 1942, SAID THAT **HE DROVE A SQUARE REINFORCING ROD, 1/2" IN DIAMETER, FOR THE NORTH 1/4 CORNER OF SECTION 33-19-11**, AT 23.85' NORTH OF [VERY LITTLE EAST] A TRANSMISSION POLE OF K. E. P. HE SAID THAT 8' WEST OF SAID K. E. P. POLE HE DROVE ANOTHER SQUARE ROD 27.33' SOUTHWEST OF SAID 1/4 CORNER. AT 8' EAST OF SAID TRANSMISSION POLE HE DROVE ANOTHER IRON PIN AS A WITNESS 27.25' SOUTHEAST OF SAID 1/4 CORNER.

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 1990, FOR JOB NUMBER 90028, SAID THAT **HE FOUND A 1/2" X 24" REBAR OVER THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 28-19-11.
 - 1) 44.15' NNW TO A NAIL & WASHER IN A 40" OAK TREE
 - 2) 28.8' NORTH TO A NAIL & WASHER IN AN 8" ASH TREE
 - 3) 35.9' NNE TO A NAIL & WASHER IN A 6" ASH TREE

HIS TIES ARE CONTINUED ON PAGE 2

- 4) 25.85' SOUTH TO A NAIL & SHINER IN A POWER POLE
 - 5) 2.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD
- 7) WARREN CHIP WOODS. L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 31, 1996, **FOUND THE 1/2" REBAR WITH "BROSEMER LS 752" CAP AT 6" BELOW SURFACE OF THE GRAVEL ROAD THAT IS REPORTED TO BE OVER THE STONE OF RECORD** AT THE NORTH 1/4 CORNER OF SECTION 33-19-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED MARCH 10, 1990.
- 1) 43.1' NNW TO A PK NAIL & WASHER IN A 120" CIRCUMFERENCE OAK TREE
 - 2) 24.7' NORTH TO A PK NAIL & WASHER IN A 30" CIRCUMFERENCE ASH TREE
 - 3) 25.5' SOUTH TO A NAIL & SHINER IN A POWER POLE
 - 4) 123.4' WEST TO THE EAST EDGE OF WEARING SURFACE OF BRIDGE 941.3-526.0
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 7, 2004, FOR PROJECT NUMBER 04110-02, SAID THAT **HE FOUND THE SANDSTONE WITH THE 1/2" REBAR WITH HIS "LS 752" CAP OVER THE TOP OF THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 33-19-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.
- 1) 42.55' NNW TO A NAIL & WASHER IN A 42" ELM TREE
 - 2) 24.30' SOUTH TO A 40 D NAIL & WASHER IN A POWER POLE
 - 3) 35.7' NNE TO A 40 D NAIL & WASHER IN A 14" ASH TREE
 - 4) 2.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 140 EAST-WEST
- HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
- 1) 2,638.12' WEST TO THE NORTHWEST CORNER OF THE NW1/4 OF SEC. 33-19-11
 - 2) 2,636.73' EAST TO THE NORTHEAST CORNER OF THE NE1/4 OF SEC. 33-19-11

NORTH QUARTER CORNER SECTION 33-19-11