

**WEST 1/4 CORNER SECTION 33, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 370 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 24" X 14" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 32 & 33-19-11.
  
- 2) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN SURVEY NUMBER 26 RECORDED IN SURVEY BOOK "A" ON PAGE 61 DATED DECEMBER 7, 1860 TO ESTABLISH THE CENTER OF SECTION 33-19-11, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND** THE WEST 1/4 CORNER OF SECTION 33-19-11 ON THIS SURVEY. HE DOES NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 159 RODS, 16 INKS EAST TO THE STAKE HE SET FOR THE CENTER CORNER OF SECTION 33-19-11
  - 2) 318 RODS, 25 LINKS EAST TO THE EAST 1/4 CORNER OF SECTION 33-19-11
  
- 3) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN SURVEY NUMBER 27 RECORDED IN SURVEY BOOK "A" ON PAGE 61 DATED DECEMBER 8, 1860 TO SURVEY 10 ACRES FROM THE SOUTH SIDE OF THE NORTHEAST 1/4 OF SECTION 33-19-11, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND** THE WEST 1/4 CORNER OF SECTION 33-19-11 ON THIS SURVEY. HE DOES NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER.
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 27, 2003, FOR PROJECT NUMBER 03102-02, SURVEY F33001 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE SURVEY OF A 10.27 ACRE TRACT IN THE WEST HALF OF SECTION 33-19-11, SAID THAT HE DEEMED THAT THE WEST 1/4 CORNER OF SECTION 33-19-11 WAS **LOST** IN EAST-WEST POSITION AND **OBLITERATED** IN NORTH-SOUTH POSITION. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 33-19-11 BY THE BEST EVIDENCE OF THE ORIGINAL POSITION. HE DEEMED THIS TO BE THE LINE OF HEDGE AND FENCE TO THE EAST. THIS CORNER IS ALSO THE SOUTHWEST CORNER OF THE 10.27 ACRE TRACT.
  - 1) 23.65' EAST TO A 40 D NAIL & WASHER IN A CORNER FENCE POST
  - 2) 56.15' NW TO THE NORTHEAST CORNER OF A RETAINING WALL AT THE GROUND
  - 3) 39.0' WNW TO THE SOUTHEAST CORNER OF A RETAINING WALL AT THE GROUND
  - 4) 38.0' SW TO THE TOP CENTER OF THE WEST END OF A C.M.P. UNDER COUNTY ROAD "J"
  - 5) 1.5' EAST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "J" NORTH-SOUTH
  - 6) IN LINE WITH A FENCE AND A HEDGE TO THE EASTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 662.00' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTHWEST CORNER OF THE 10.27 ACRE TRACT, AS WITNESSED BY THE 1/2" X 24" REBAR WITH HIS "LS 752" CAP HE SET AT 25' EAST ON THE EAST RIGHT-OF-WAY LINE OF COUNTY ROAD "J"
  - 2) 2,647.42' NORTH TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 33-19-11
  - 3) 2,652.00' SOUTH TO THE SQUARE #4 REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 33-19-11 ON THE TOWNSHIP LINE
  - 4) 669.50' EAST TO THE COTTON GIN SPINDLE HE SET IN A TREE STUMP FOR THE SOUTHEAST CORNER OF THE 10.27 ACRE TRACT

WEST QUARTER CORNER SECTION 33-19-11