

**CENTER CORNER NORTHWEST QUARTER OF SECTION 34, TOWNSHIP 19 SOUTH,  
RANGE 11 EAST**

- 1) AI CHAMNESS, DEPUTY COUNTY SURVEYOR FROM 1906 TO 1946, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 128 DATED NOVEMBER 15, 1945 ORDERED BY WILLIAM EDWARDS TO LOCATE AND PERMANENTLY ESTABLISH THE EAST LINE OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 34, SAID THAT **HE SET A 1/2" REINFORCING ROD OF STEEL** ON LINE AND HALFWAY BETWEEN THE 1/2" REINFORCING ROD OF STEEL HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 34 AND THE STONE THAT HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF THE EAST 1/2 OF THE NORTHWEST CORNER OF SECTION 34.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,340' NORTH TO THE 1/2" REINFORCING ROD OF STEEL HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 34 AT 34 FEET SOUTH OF THE HEDGE ON THE NORTH SIDE OF THE ROAD
- 2) 1,340' SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 34 AND HE SET A 1/2" REINFORCING ROD OF STEEL ON THE SOUTH SIDE OF THE STONE AS IT SEEMED RATHER LOOSE IN THE GROUND

CENTER CORNER NORTHWEST QUARTER SECTION 34-19-11