

NORTH 1/16TH CORNER NORTHWEST QUARTER OF SECTION 34, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY #79 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 1 DATED JANUARY 3, 1873 TO SUBDIVIDE THE NORTHWEST 1/4 OF SECTION 34 EQUALLY BY A LINE RUNNING NORTH & SOUTH, SAID THAT **HE DROVE A STAKE** FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 34 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE CORNER TO SECTIONS 27, 28,33 & 34 34 AND A POINT 8-1/2 FEET SOUTH TO THE 1/4 CORNER BETWEEN SECTIONS 27 & 34 AS "SAID CORNER NOT BEING IN ITS ORIGINAL POSITION" ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,332' WEST TO THE STONE HE FOUND AT THE CORNER TO SEC. 27, 28, 33 & 34
 - 2) 1,332' EAST TO A POINT 8-1/2' SOUTH OF THE 1/4 CORNER BETWEEN SECTIONS 27 & 34 "SAID CORNER NOT BEING IN ITS ORIGINAL POSITION"
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 69, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 148 DATED MARCH 17 & 18, 1903 AT THE REQUEST OF ROBERT H. EVANS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 34-19-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET AN 18" X 12" X 3" STONE IN THE DITCH ON THE SOUTH SIDE OF THE ROAD, 12 FEET WEST AND 4-1/2 FEET NORTH OF AN ELM TREE, AND 34 FEET SOUTH OF A HEDGE ON THE NORTH SIDE OF THE ROAD** FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH LINE OF THE NORTHWEST 1/4 OF SECTION 34 ON LINE AND HALFWAY BETWEEN THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 34 AND THE STONE THAT FOUND AT THE NORTHWEST CORNER OF SECTION 34 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 122 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 71" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.15 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34
 - 2) 20.15 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 34 BY THE AFFIDAVIT OF CHARLES EVANS
- 3) AI CHAMNESS, DEPUTY COUNTY SURVEYOR FROM 1906 TO 1946, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 128 DATED NOVEMBER 15, 1945 ORDERED BY WILLIAM EDWARDS TO LOCATE AND PERMANENTLY ESTABLISH THE EAST LINE OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 34, SAID THAT **HE SET A 1/2" REINFORCING ROD OF STEEL** FOR THE PERMANENT NORTHEAST CORNER THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 34 ON LINE AND HALFWAY BETWEEN THE IRON PIN THAT HE FOUND NORTHWEST CORNER AND THE NORTH 1/4 CORNER OF SECTION 34 ON THIS **PERMANENT SURVEY**.

- 1) 34' SOUTH OF A HEDGE ON THE NORTH SIDE OF THE ROAD

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,326.4' WEST TO THE IRON PIN HE FOUND MARKING THE NORTHWEST CORNER OF SECTION 34 "THE ORIGINAL STONE BEING GONE"
- 2) 1,326.4' EAST TO THE NORTH 1/4 CORNER OF SECTION 34 LOCATED 2 FEET WEST OF THE SOUTH SIDE OF THE NORTH ABUTMENT OF THE BRIDGE ACROSS

DRY CREEK ON STATE HIGHWAY 99 AND ABOUT 9 FEET EAST OF THE WEST RAILING OF SAID BRIDGE

- 3) 1,340' SOUTH TO A 1/2" REINFORCING ROD OF STEEL HE SET ON THE PERMANENT MID POINT ON EAST LINE OF THE WEST 1/2 OF THE SW1/4 OF SECTION 34
 - 4) 2,680' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 34 AND HE DROVE A 1/2" REINFORCING ROD OF STEEL ON THE SOUTH SIDE OF THE STONE AS IT SEEMED RATHER LOOSE IN THE GROUND
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MARCH 15, 2007, FOR PROJECT NUMBER 07051-02, SURVEY F34005 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A 10.00 ACRE TRACT IN THE EAST HALF OF THE NORTHWEST QUARTER OF SECTION 34-19-11 FOR CLINT MILLER/ANDERSON, SAID THAT **HE FOUND A 5/8" REBAR WITH 1" RIBS** AT THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 34 ATTRIBUTABLE TO E. C. GOLDSMITH BY AI CHAMNESS IN A PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 128 DATED 1945.
- 1) 89.25' WSW TO THE NORTHEAST CORNER OF A CONCRETE TELEPHONE PAD
 - 2) 57.3' NW TO A SPIKE & WASHER IN A 10" HACKBERRY TREE
 - 3) 105.40' ESE TO A 40 D NAIL & WASHER IN A POWER POLE
 - 4) 43.0' EAST TO THE CENTER OF A FIELD ENTRANCE
 - 5) 12.0' NORTH TO THE TRAVELED WAY OF GRAVEL ROAD 140 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,327.12' WEST TO THE STONE & REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 34
 - 2) 1,326.64' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 34
 - 3) 2,309.65' SOUTH TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 10.00 ACRE TRACT
 - 4) 2,676.34' SOUTH TO THE STONE & REBAR [ALVA J. SMITH & AI CHAMNESS] HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 34, BEING THE SOUTHWEST CORNER OF THE 10.00 ACRE TRACT

NORTH SIXTEENTH CORNER NORTHWEST QUARTER SECTION 34-19-11