

**WEST 1/16TH CORNER SOUTHEAST QUARTER OF SECTION 34, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 69, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 148 DATED MARCH 17 & 18, 1903 AT THE REQUEST OF ROBERT H. EVANS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 34-19-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET AN 18" X 8" X 3" STONE AT 18-1/2 FEET WEST OF A HEDGE** FOR THE PERMANENT 1/2/4 CORNER ON THE WEST SIDE OF THE SOUTHEAST 1/4 OF SECTION 34 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 34 AND A STAKE THAT SET FOR THE SOUTH 1/4 CORNER OF SECTION 34 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 122 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 71" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 19.99 CHAINS NORTH TO THE 16" X 15" X 4" STONE MARKED "X" ON THE WEST SIDE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 34 AT 20 FEET SOUTH AND 24 FEET WEST OF A HEDGE CORNER
- 2) 19.99 CHAINS SOUTH TO A STAKE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 34 ON THE TOWNSHIP LINE

WEST SIXTEENTH CORNER SOUTHEAST QUARTER SECTION 34-19-11