

**WEST 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST QUARTER OF SECTION 34, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 69, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 148 DATED MARCH 17 & 18, 1903 AT THE REQUEST OF ROBERT H. EVANS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 34-19-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A SANDSTONE ON LINE WITH A FENCE AND 30 FEET EAST OF A HEDGE ON THE WEST SIDE OF THE ROAD** FOR THE PERMANENT 1/2/4 CORNER ON THE WEST SIDE OF THE SOUTHWEST 1/4 OF SECTION 34-19-11 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34 ON THE TOWNSHIP LINE AND THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 34 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 3 ON PGE 122 IN THE "KRETSINGER COLLECTION" AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 71" IN MISCELLANEOUS SURVEY DRAWER 3 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE.

**HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:**

- 1) 20.09 CHAINS SOUTH TO THE STAKE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-19-11 ON THE TOWNSHIP LINE
  - 2) 39.79 CHAINS SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-20-11
  - 3) 20.09 CHAINS NORTH TO THE 20" X 8" X 7" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 34 AT **3 FEET WEST OF A TRUE LINE BETWEEN THE SECTION CORNERS** AT 30 FEET EAST OF A HEDGE ON THE WEST SIDE OF THE ROAD
  - 4) 60.73 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 20, 2013 FOR PROJECT NUMBER 13191, SURVEY F33002 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 TO SURVEY THE NORTH LINE OF THE SOUTHEAST 1/4 OF SECTION 33-19-11 FOR DOUDICAN, SAID THAT **HE SET A 1/2" IRON PIN WITH HIS "L.S. 752" CAP** FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 33 ON TRUE LINE AND HALFWAY BETWEEN THE EAST 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 33.
- 1) IN THE TRAVELED WAY OF THE GRAVEL ROAD NORTH-SOUTH [COUNTY ROAD "K"]
  - 2) 33.2' SE TO A 40 D NAIL & WASHER SET IN THE TOP OF FENCE BRACE POST
  - 3) 19.3' ESE TO A 40 D NAIL & WASHER SET IN THE SOUTH SIDE OF AN 18" LOCUST TREE
  - 4) 10' NORTH TO THE CENTERLINE OF A METAL CULVERT
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,324.90' NORTH TO A KDOT ALUMINUM CAP HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 33
  - 2) 1,324.90' SOUTH TO A 5/8" IRON PIN OVER THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 33 ON THE TOWNSHIP LINE
  - 3) 1,316.05' WEST TO A 1/2" X 24" IRON PIN WITH HIS "L.S. 752" CAP HE SET FOR THE CENTER OF THE SE1/4 OF SECTION 33
  - 4) 2,632.10' WEST TO THE THEORETICAL POSITION FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 33

WEST SIXTEENTH CORNER SOUTHWEST QUARTER SECTION 34-19-11