

CENTER CORNER SECTION 35, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 213 [PACKET 79 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY JOHN H. WILLIAMS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-11 THAT HE SURVEYED ON JUNE 9, 1873, AND WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 7, 1873 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 35-19-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE 1/2 SECTION LINE FOR 158 RODS TO THE STONE HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 35 & 36-19-11 AT A TURN TO THE NORTH TO THE CORNER TO SECTIONS 25, 26, 35 & 26 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS WEST ON THE 1/2 SECTION LINE FOR 2 RODS TO THE FIRST MILE STONE MARKED "1/M" HE SET; THEN CONTINUES WEST ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 34-19-11 TO END THIS ROAD SURVEY
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 107 OF THE 7TH TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 29 DATED JUNE 9, FOR A COUNTY ROAD IN TOWNSHIP 19-11, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 35-19-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 158 RODS EAST TO THE 1/4 CORNER BETWEEN SECTIONS 35 & 36-19-11
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F35002 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A SUBDIVISION OF TH NORTH HALF OF THE SOUTHWEST QUARTER OF SECTION 35-19-11 FOR PROJECT NUMBER 96309-02 DATED FEBRUARY 4, 1997 SAID IN HIS *REPORT OF SURVEY* THAT HE EXCAVATED FOR THE STONE THAT WAS SET BY MILLIKEN AT THE CENTER CORNER OF SECTION 35-19-11, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE CENTER CORNER OF SECTION 35-19-11 AT THE PRORATED DISTANCE BETWEEN THE EAST 1/4 CORNER AND THE WEST 1/4 CORNER OF SECTION 35-19-11 AND ON LINE BETWEEN THEM.

- 1) 48.20' SOUTH TO A RAILROAD SPIKE IN A ROCK
- 2) 132.30' NORTH TO A NAIL & SHINER IN A 6" HEDGE TREE
- 3) 76.90' WSW TO A NAIL & SHINER IN A WOOD SIGN POST
- 4) 67.0' ESE TO THE WEST END OF AN 18" PIPE IN A FIELD ENTRANCE
- 5) 10.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,620.21' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF A 48.66 ACRE TRACT
- 2) 1,980.26' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF A 20.00 ACRE TRACT
- 3) 2,461.21' WEST TO THE 9/16" IRON PIN HE FOUND AT THE WEST 1/4 CORNER OF SECTION 35-19-11
- 4) 2,608.19' EAST TO THE 1/2" REBAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 35-19-11
- 5) 1,314.77' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/16TH CORNER OF THE SW1/4 OF SECTION 35-19-11
- 6) 2,629.53' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 35-19-11 ON THE TOWNSHIP LINE

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED NOVEMBER 19, 2004 FOR PROJECT NUMBER 04416-02, SURVEY F35004 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A 32.9 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 35-19-11 FOR W. C. BURDEN, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE CENTER CORNER OF SECTION 35-19-11 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED FEBRUARY 1997.
- 1) 9.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
 - 2) 22.4' NW TO A 40 D NAIL & WASHER IN A POST
 - 3) 40.9' WEST TO THE CENTERLINE OF A FIELD ENTRANCE TO THE NORTH
 - 4) 62.7' WNW TO A 40 D NAIL & WASHER IN A POST
 - 5) 67.0' ESE TO THE WEST END OF AN 18" CMP AT A FIELD ENTRANCE
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,298.01' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT THE SOUTHEAST CORNER OF A PREVIOUSLY CONVEYED TRACT AND WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25' NORTH
 - 2) 2,608.24' EAST TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 35-19-11
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2013 FOR PROJECT NUMBER 13034-02, SURVEY F35005 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11, THE SURVEY OF A 12.00 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 35-19-11 FOR F. SCHEVE, SAID THAT **HE FOUND THE 5/8" IRON PIN WITH A LYON COUNTY CAP** AT THE CENTER CORNER OF SECTION 35-19-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE LYON COUNTY ENGINEERS OFFICE DATED NOVEMBER 2004.
- 1) 9.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 135 EAST-WEST
 - 2) 22.4' NORTHWEST TO A 40 D NAIL & WASHER IN A FENCE POST
 - 3) 62.7' WEST-NORTHWEST TO A 40 D NAIL & WASHER IN A FENCE POST
 - 4) 41.00' WEST TO THE CENTER OF A FIELD ENTRANCE TO THE NORTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,629.59' SOUTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 35-19-11

CENTER QUARTER CORNER SECTION 35-19-11