

NORTHWEST CORNER SECTION 35, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 359 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 33" X 8" X 3"** ON THE LEFT BANK OF A CREEK FOR THE CORNER TO SECTIONS 34, 35, 26 & 27-19-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.801-1/2 CHAINS EAST TO THE 16" X 13" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-19-11
 - 2) 79.61 CHAINS EAST TO THE 20" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-19-11
- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 21 DATED AUGUST 10, 1882, FOR A ROAD SURVEY IN TOWNSHIP 19, RANGE 11 FOR A. W. ALLEN, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 35-19-11 ON THIS ROAD SURVEY. NO WIDTH WAS RECORDED FOR THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 80 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-19-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 80 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-19-11 ON THE TOWNSHIP LINE TO COMMENCE THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, A ROAD SURVEY FOR ROAD 193 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 358 TO 360 PETITIONED BY A. W. ALLEN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-11 [PACKET 408 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 10, 1882, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 11, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 25, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 35-19-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 3) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 80 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-19-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 4) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 80 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-19-11 ON THE TOWNSHIP LINE TO COMMENCE THIS ROAD SURVEY

- 4) JAMES H. BROSEMER, L.S. 82, CHIEF OF SURVEYS, FOR KDOT PROJECT 57-56-K0548-01, IN 1981, SAID THAT HE EXCAVATED WITH A COUNTY MOTOR GRADER FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 34, BUT HE DID **NOT** FIND THE STONE. HE SAID THAT THE EAST-WEST POSITION WAS DETERMINED BY THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER; I.E., 20' EAST OF THE REMAINS OF A NORTH-SOUTH HEDGE. THE NORTH-SOUTH POSITION WAS DETERMINED FROM 1/2 THE DISTANCE BETWEEN THE SOUTHEAST CORNER OF SECTION 34-19-11 ON THE TOWNSHIP LINE AND THE NORTHEAST CORNER OF SECTION 27-19-11, AND THE CALL OF THE GLO NOTES, AS THERE IS NO PHYSICAL EVIDENCE FOR THE NORTH-SOUTH POSITION NEAR THIS CORNER. **HE SET A 1/2" REBAR WITH AN ALUMINUM KDOT CAP STAMPED "NE 34-19-11"** FOR THE NORTHEAST CORNER OF SECTION 34-19-11.

HIS TIES ARE ON PAGE 2

- 1) 22.0' WSW TO A SPIKE & KDOT WASHER IN A 50" HEDGE TREE
- 2) 32.1' WNW TO A SPIKE & KDOT WASHER IN A 70" HEDGE TREE
- 3) 26.5' NW TO A SPIKE & KDOT WASHER IN A 20" HEDGE TREE
- 4) 20.0' WEST TO THE REMAINS OF A NORTH-SOUTH HEDGE [TREES & STUMPS]
- 5) 6.5' EAST TO THE TRAVELED WAY OF A TRAIL ROAD NORTH-SOUTH

NORTHWEST CORNER SECTION 35-19-11