

**WEST 1/16<sup>TH</sup> CORNER NORTHEAST QUARTER OF SECTION 35, TOWNSHIP 19 SOUTH,  
RANGE 11 EAST**

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 30, 2005, FOR PROJECT NUMBER 05313-02, SURVEY F36009 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS CAP** FOR THIS CORNER ON TRUE LINE AND HALFWAY BETWEEN THE NORTH QUARTER CORNER AND THE CENTER OF SECTION 36.

- 1) 25.40' SSE TO A CONCRETE NAIL & WASHER IN A CORNER POST
- 2) 30.85' NE TO A CONCRETE NAIL & WASHER IN A CORNER POST
- 3) 30.30' NW TO THE WEST END AT THE OF TOP CENTER OF A STEEL CASING FOR A DRIVE ENTRANCE
- 4) 16.5' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- 5) 17.0' WEST TO THE EAST LINE OF A HOUSE EXTENDED
- 6) 3.3' NORTH TO THE CENTERLINE OF TRAVELED-WAY EAST-WEST [COUNTY ROAD 137]

**HIS DRAWING SHOWS THE FOLLOWING DISTANCES:**

- 1) 1,327.20' NORTH TO THE STONE FOUND AT THE NORTH 1/4 CORNER OF SEC. 36
- 2) 1,327.20' SOUTH TO THE THEORETICAL LOCATION FOR THE CENTER OF SEC. 36
- 3) 1,323.54' EAST TO A 1/2" CAPPED REBAR SET FOR THE CENTER OF THE NORTHEAST 1/4 OF SECTION 36
- 4) 2,647.08' EAST TO A 1/2" CAPPED REBAR SET FOR THE 1/16TH CORNER

2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 2, 2008 FOR PROJECT NUMBER 08253-02, SURVEY F36010 IN THE SURVEY FILE FOR TOWNSHIP 19-11, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS CAP** AT THIS CORNER FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.

- 1) 25.40' SSE TO A CONCRETE NAIL & WASHER IN A CORNER POST
- 2) 30.85' NE TO A CONCRETE NAIL & WASHER IN A CORNER POST
- 3) 30.30' NW TO THE WEST END AT THE TOP CENTER OF A STEEL CASING FOR A DRIVE ENTRANCE
- 4) 16.5' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- 5) 3.3' NORTH TO THE CENTERLINE TRAVELED-WAY OF ROAD 137 EAST-WEST
- 6) 17.0' WEST TO THE EAST LINE OF A HOUSE EXTENDED

**HIS DRAWING SHOWS THE FOLLOWING DISTANCES:**

- 1) 1,316.06' WEST TO A 5/8" CAPPED REBAR SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 36
- 2) 2,634.45' WEST TO A 5/8" CAPPED REBAR SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 36
- 3) 1,327.09' SOUTH TO THE THEORETICAL LOCATION FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 36
- 4) 3,957.27' SOUTH TO A 1/2" REBAR FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 36

WEST SIXTEENTH CORNER NORTHEAST QUARTER SECTION 35-19-11