

CENTER CORNER SECTION 36, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F36004 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE SURVEY OF A 29.75 ACRE TRACT OF LAND IN THE SOUTHWEST 1/4 OF SECTION 36-19-11 DATED NOVEMBER 21& 22, 1974, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 36-19-11, BUT THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCE:

- 1) 2,630± SOUTH TO THE MONUMENT AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 36
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 30, 2005, FOR PROJECT NUMBER 05313-02, SURVEY F36009 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A SURVEY OF THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-11 FOR JAYLENE ARNETT, SAID THAT HE DETERMINED THE **THEORETICAL POSITION** OF THE CENTER CORNER OF SECTION 36 AT THE INTERSECTION OF LINES FROM OPPOSITE QUARTER CORNERS, BUT HE DID **NOT** MONUMENT IT.
- 1) 2,642.75' EAST TO A 5/8" X 24" REBAR WITH A LYON COUNTY CAP AT THE EAST 1/4 CORNER
- 2) 2,635.52' WEST TO A 1/2" REBAR AT THE WEST 1/4 CORNER
- 3) 2,629.94' SOUTH TO A 1/2" X 24" REBAR AT THE SOUTH 1/4 CORNER
- 4) 2,654.40' NORTH TO A STONE AT THE NORTH 1/4 CORNER

- 3) STEVEN S. BROSEMER, L.S. 752, IN SURVEY F36010 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHWEST QUARTER OF SECTION 36-19-11 FOR JOHN & NORMA WIEDMER FOR PROJECT NUMBER 08253-02 DATED SEPTEMBER 2, 2008 SAID THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE CENTER OF SECTION 36 BUT IT WAS **NOT** MONUMENTED ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,317.69' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 36
- 2) 1,976.53' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF THE NW1/4 OF SECTION 36
- 3) 2,635.37' WEST TO A 1/2" REBAR FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 36
- 4) 1,327.09' NORTH TO A 1/2" REBAR FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 36
- 5) 2,630.18' SOUTH TO A 1/2" REBAR FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 36
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 22, 2009 FOR PROJECT NUMBER 09140-02, THE PLAT FOR MARY'S PLACE SUBDIVISION, SAID THAT **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE CENTER OF SECTION 36 AT THE INTERSECTION OF THE LINES FROM OPPOSITE SECTION CORNERS.
- 1) 8.5' NORTH TO A LINE OF FENCE TO THE EAST AND WEST
- 2) 12.0' EAST TO A LINE OF FENCE TO THE NORTH AND SOUTH
- 3) 14.08' NW TO A SPIKE & BOTTLE CAP IN THE SW FACE OF A BRACE POST
- 4) 9.05' NNW TO A SPIKE & BOTTLE CAP IN THE SW FACE OF A GATE POST

HIS PLAT DRAWING SHOWS THE FOLLOWING DISTANCES:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 2,635.40' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 36
- 2) 2,629.99' SOUTH TO A 5/8" REBAR FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 36

CENTER QUARTER CORNER SECTION 36-19-11