

**CENTER CORNER NORTHEAST QUARTER OF SECTION 36, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 30, 2005, FOR PROJECT NUMBER 05313-02, SURVEY F36009 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A SURVEY OF THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-11 FOR JAYLENE ARNETT, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE CENTER CORNER OF THE NORTHEAST 1/4 OF SECTION 36 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/16TH CORNERS.

- 1) 78.45' NE TO A 40 D NAIL IN A POWER POLE
- 2) 39.15' NW TO A CONCRETE NAIL & WASHER IN A HEDGE POST
- 3) 69.0' WEST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- 4) 20.0' SOUTH TO A 1/2" REBAR WITH HIS CAP [**HORIZONTAL TIE**]
- 5) 3.5' NORTH TO THE CENTERLINE OF TRAVELED-WAY OF ROAD 137 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,323.54' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE 1/16TH CORNER ON THE WEST SIDE OF THE NE1/4 OF SECTION 36
- 2) 1,323.11' NORTH TO THE THEORETICAL POSITION FOR THE 1/16TH CORNER ON THE NORTH SIDE OF THE NE1/4 OF SECTION 36
- 3) 1,323.54' EAST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE 1/16TH CORNER ON THE EAST SIDE OF THE NE1/4 OF SECTION 36
- 4) 661.56' SOUTH TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTH-WEST CORNER OF THE S1/2 OF THE SE1/4 OF THE NE1/4 OF SECTION 36
- 5) 1,323.11' SOUTH TO THE THEORETICAL POSITION FOR THE 1/16TH CORNER ON THE SOUTH SIDE OF THE NE1/4 OF SECTION 36

CENTER CORNER NORTHEAST QUARTER SECTION 36-19-11