

**CENTER CORNER NORTHWEST QUARTER OF SECTION 36, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 62 OF THE 7TH TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 210 DATED JULY 15, 1872 FOR A ROAD IN TOWNSHIP 19, RANGES 11 & 12, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER IN THE CENTER OF THE NORTHWEST 1/4 OF SECTION 36 ON THIS ROAD SURVEY.

2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 204 [PACKET 39 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY B. F. PARKER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 19-11 & 19-12 THAT HE SURVEYED ON JULY 15, 1872, AND WAS ORDERED ESTABLISHED AS A 40 FOOT WIDE ROAD AT A MEETING HELD BY THE COUNTY BOARD ON OCTOBER 7, 1872 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE CENTER CORNER OF THE NORTHWEST 1/4 OF SECTION 36-19-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE 1/2/4 LINE FOR 52-6/10 RODS TO A TURN TO THE SOUTHEASTERLY
- 2) THIS ROAD EXTENDS NORTH ON THE 1/2/4 LINE FOR 80 RODS TO THE NORTH 1/16TH CORNER OF THE NW1/4 OF SECTION 36-19-11 AT A TURN TO THE WEST

3) DAN J. MELANDER, L.S. 504 AND RICHARD L. THOMPSON, L.S. 505, IN SURVEY SR #36001 IN THE LARGE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 DATED AUGUST 7, 1971, SHOWS ON THEIR SURVEY DRAWING A **STEEL PIN** AT THE CENTER OF THE NORTHWEST 1/4 OF SECTION 36-19-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

THEIR DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320.0' WEST TO THE STEEL PIN THEY SET FOR THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 36-19-11
- 2) 1,319.0' NORTH TO THE STEEL PIN THEY SET FOR THE NORTH 1/16TH CORNER OF THE NW1/4 OF SECTION 36-19-11

4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 2, 2008 FOR PROJECT NUMBER 08253-02, SURVEY F36010 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHWEST QUARTER OF SECTION 36-19-11 FOR JOHN & NORMA WIEDMER, SAID THAT **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE CENTER CORNER OF THE NORTHWEST 1/4 OF SECTION 36-19-11 AT THE INTERSECTION OF THE LINES BETWEEN THE OPPOSITE 1/16TH CORNERS.

- 1) IN LINE WITH A FENCE TO THE NORTH
- 2) 5.8' EAST TO A LINE OF FENCE TO THE SOUTH
- 3) 16' NORTH TO THE CENTERLINE TRAVELED WY OF COUNTY ROAD 137 EAST-WEST
- 4) 11.5' SE TO THE TOP CENTER OF A 3" PIPE CORNER FENCE POST
- 5) 58.1' EAST TO THE TOP CENTER OF A TELEPHONE PEDESTAL

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 265.00' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE "EXCEPTED TRACT"
- 2) 659.19' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF THE SW1/4 OF THE NW1/4 OF SECTION 36-19-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 1,318.39' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 36-19-11
- 4) 1,331.05' NORTH TO THE 1/2" REBAR FROM A PRIOR SURVEY IN 2007 HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 36-19-11
- 5) 1,316.06' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 36-19-11
- 6) 493.00' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE "EXCEPTED TRACT"
- 7) 664.55' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE SW1/4 OF THE NW1/4 OF SECTION 36-19-11
- 8) 1,329.10' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 36-19-11

CENTER CORNER NORTHWEST QUARTER SECTION 36-19-11