

**NORTH 1/16<sup>TH</sup> CORNER SOUTHWEST QUARTER OF SECTION 36, TOWNSHIP 19 SOUTH,  
RANGE 11 EAST**

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 2, 2008 FOR PROJECT NUMBER 08253-02, SURVEY F36010 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHWEST QUARTER OF SECTION 36-19-11 FOR JOHN & NORMA WIEDMER, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 36 ON LINE AND HALFWAY BETWEEN THE WEST 1/4 CORNER AND THE THEORETICAL CENTER OF SECTION 36.
  - 1) 25.8' ENE TO A CONCRETE NAIL & BOTTLECAP IN A CORNER FENCE POST
  - 2) 21.8' ENE TO A CONCRETE NAIL & BOTTLE CAP IN A BRACE POST
  - 3) 20.0' NORTH TO A LINE OF FENCE EAST-WEST
  - 4) 6.0' EAST TO A LINE OF FENCE RUNNING NORTH

**HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:**

  - 1) 668.54' WEST TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE SE1/4 FO THE SW1/4 OF THE NW1/4 OF SECTION 36
  - 2) 1,317.68' WEST TO A 1/2" REBAR FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 36
  - 3) 664.55' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTH-EAST CORNER OF THE SE1/4 OF THE SW1/4 OF THE NW1/4 OF SECTION 36
  - 4) 836.10' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE SOUTH-EAST CORNER OF THE "EXCEPTED TRACT"
  - 5) 1,329.10' NORTH TO A 5/8" REBAR WITH LYON COUNTY CAP SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 36
  - 6) 2,660.15' NORTH TO A 1/2" REBAR FORM A PRIOR SURVEY IN 2007 FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 36
  - 7) 1,317.69' EAST TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 36

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER SECTION 36-19-11