

NORTHWEST CORNER SECTION 36, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 352 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 3"** FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-19-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.95 CHAINS EAST TO THE 20" X 14" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 36-19-11
 - 2) 79.90 CHAINS EAST TO THE POST THEY SET FOR THE CORNER TO SECTIONS 25 & 36-19-11 ON THE EAST TOWNSHIP LINE

- 2) IN ROAD RECORD BOOK "A" ON PAGE 127 [PACKET 241 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] FOR THE SECOND ROAD ON A PETITION BY DAVID J. LEWIS AND OTHERS FOR SECTION LINE ROADS IN TOWNSHIPS 19-11 & 20-11 WITHOUT A SURVEY, THE BOARD OF COUNTY COMMISSIONERS ORDERED THE SECTION LINES FOR THE SECOND ROAD DECLARED PUBLIC HIGHWAYS ESTABLISHED ON JUNE 22, 1869 IN THE COMMISSIONERS JOURNAL ON PAGE 269. THE LAW OF 1869 PROVIDES FORTY FEET WIDTH ON SECTION LINE ROADS.
 - 1) THIS SECOND ROAD EXTENDS NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 14-19-11 AT THE TERMINUS OF THE SECOND ROAD
 - 2) THIS SECOND ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 14-20-11 TO COMMENCE THIS SECOND ROAD

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 30, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 30 DATED APRIL 27, 1870 TO ESTABLISH THE CENTER [TEMPORARY] AND DIVIDE THE SOUTHWEST 1/4 OF SECTION 25-19-11 BY A LINE RUNNING NORTH & SOUTH, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 25-19-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,319-1/2' EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 25-19-11
 - 2) 2,639' EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 25-19-11

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 62 OF THE 7TH TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 210 DATED JULY 15, 1872 FOR A ROAD IN TOWNSHIP 19, RANGES 11 & 12, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 36-19-11 ON THIS ROAD SURVEY.

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 204 [PACKET 39 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY B. F. PARKER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 19-11 & 19-12 THAT HE SURVEYED ON JULY 15, 1872, AND WAS ORDERED ESTABLISHED AS A 40 FOOT WIDE ROAD AT A MEETING HELD BY THE COUNTY BOARD ON OCTOBER 7, 1872 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 36-19-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 80 RODS TO THE NORTH 1/16TH CORNER OF THE NW1/4 OF SECTION 36-19-11 AT A TURN TO THE SOUTH
 - 2) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 294-2/3 RODS TO A TURN TO THE NORTHEASTERLY DUE TO THE COTTONWOOD RIVER

- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 213 [PACKET 79 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY JOHN H. WILLIAMS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-11 THAT HE SURVEYED ON JUNE 9, 1873, AND WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 7, 1873 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTIONS 36-19-11 TO BEGIN THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 36-19-11 AT A TURN TO THE WEST; AND CONTINUES WEST ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 34-19-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 107 OF THE 7TH TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 29 DATED JUNE 9, FOR A COUNTY ROAD IN TOWNSHIP 19-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 36-19-11 TO BEGIN THIS ROAD SURVEY.
- 8) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN INFORMAL SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 148 DATED MARCH 12, 1883 AT THE REQUEST OF HUGHES TO ESTABLISH THE 1/8TH CORNERS AND THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 25-19-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 25-19-11 ON THIS INFORMAL SURVEY.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
- 1) 19.95 CHAINS EAST TO THE STONE HE SET FOR THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 25-19-11
 - 2) 39.90 CHAINS EAST TO THE STONE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 25-19-11
 - 3) 59.85 CHAINS EAST TO THE STONE HE SET FOR THE SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 25-19-11
 - 4) 79.80 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-19-11 ON THE RANGE LINE
- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS AN **IRON PIN** AT THE "NW CORNER SECTION 36-19-11".
- 1) 25' SOUTH OF A FENCE LINE TO THE EAST
 - 2) 31.6' NE TO A SPIKE IN A POLE
 - 3) 34.2' SE TO THE BASE OF AN ELM SAPLING
- 10) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F25003 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 SHOWING THE LINES OF A SURVEY OF A TRACT OF LAND CONSISTING OF A PART THE EAST 1/2 OF THE SOUTHWEST 1/4 AND ALL OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 25-19-11, BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHWEST CORNER OF SECTION 25-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,657' NORTH TO THE "MONUMENT" AT THE WEST 1/4 CORNER OF SEC. 25-19-11
 - 2) 5,314' NORTH TO THE "MONUMENT" AT THE NORTHWEST CORNER OF SECTION 25-19-11
 - 3) 1,320' EAST TO THE "MONUMENT" HE SET FOR THE SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 25-19-11

HIS INFORMATION IS CONTINUED ON PAGE 3

- 4) 2,640' EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 25-19-11
 - 5) 3,960' EAST TO THE "MONUMENT" HE SET FOR THE SOUTHEAST TRACT CORNER, BEING THE SOUTHEAST CORNER OF THE WEST HALF OF THE SOUTHEAST QUARTER OF SECTION 25-19-11
- 11) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F35001 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHEAST 1/4 OF SECTION 35-19-11 BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE NORTHEAST CORNER OF SECTION 35-19-11. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 660' WEST TO THE NORTHWEST TRACT CORNER – NO PIN SET
 - 2) 417.43' SOUTH TO THE IRON PIN HE SET ON THE SECTION LINE AT THE SOUTHEAST CORNER OF A 4 ACRE TRACT
 - 3) 1,077.43' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHEAST TRACT CORNER
- 12) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #25001 IN THE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 DATED OCTOBER 28, 1965, SHOWS ON HIS SURVEY DRAWING A **5/8" DIAMETER IRON PIN** AT THE SOUTHWEST CORNER OF SECTION 25-19-11. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,639' EAST TO THE "MONUMENT" AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 25-19-11 – NOT DESCRIBED
- 13) DAN J. MELANDER, L.S. 504 AND RICHARD L. THOMPSON, L.S. 505, IN LARGER SURVEY SR #36001 IN THE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 DATED AUGUST 7, 1971, SHOWS ON HIS SURVEY DRAWING A **STEEL PIN** AT THE NORTHWEST CORNER OF SECTION 36-19-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
THEIR SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,319.70' EAST TO THE STEEL PIN AT THE NORTH 1/16TH CORNER OF THE NW1/4 OF SECTION 36-19-11
 - 2) 1,319.27' SOUTH TO THE STEEL PIN AT THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 36-19-11
- 14) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 5, 1983, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTHWEST CORNER OF SECTION 36-19-11, BUT HE DID **NOT** FIND THE STONE. **HE FOUND AND ACCEPTED A 5/8" REBAR** FOR THE NORTHWEST CORNER OF SECTION 36-19-11 THAT WAS SET BY LESLIE M. GOULD. **HE PLACED A LYON COUNTY CAP ON THE REBAR.**
- 1) 38.5' NW TO THE NEAR FACE OF A 6" DIAMETER OAK
 - 2) 35.5' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 3) 4.0' WEST TO THE TRAVELED WAY OF THE ROAD TO THE SOUTH
 - 4) 7.0' NORTH OF THE TRAVELED WAY OF THE ROAD TO THE EAST
- 15) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 31, 1996, **FOUND THE 5/8" REBAR WITHOUT A CAP AT 3" BELOW THE GRAVEL ROAD SURFACE** AT THE NORTHWEST CORNER OF SECTION 36-19-11 FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED APRIL 5, 1983. **I PLACED A NEW LYON COUNTY CAP ON THE TOP OF THE REBAR.**

MY TIES ARE ON PAGE 4

- 1) 38.5' SW TO THE NEAR FACE OF A 40" CIRCUMFERENCE OAK
 - 2) 58.2' NE TO THE TOP OF A CORNER FENCE POST
 - 3) 4' WEST TO THE TRAVELED WAY OF COUNTY ROAD "M" TO THE SOUTH
 - 4) 6' NORTH TO THE TRAVELED WAY OF COUNTY ROAD 140 TO THE EAST
- 16) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 24, 1999, **FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP AT 3" BELOW THE SURFACE OF GRAVEL ROAD "M"** AT THE NORTHWEST CORNER OF SECTION 36-19-11 FROM MY TIES DATED MAY 31, 1996 ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 38.5' SW TO THE NEAR FACE OF A 40" CIRCUMFERENCE OAK TREE
 - 2) 58.2' NE TO THE TOP CENTER OF A CORNER FENCE POST
 - 3) 35.5' ENE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) 4' WEST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "M" TO THE SOUTH
 - 5) 6' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 140 TO THE EAST
- 17) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 28, 2003, FOR PROJECT NUMBER 01570-02, SURVEY F35003 IN THE SURVEY FILE FOR SECTION 17-36 IN TOWNSHIP 19-11 FOR A 17.38 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 35-19-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTHEAST CORNER OF SECTION 35-19-11 FROM HIS EXISTING REFERENCE TIES DATED APRIL 1983.
- 1) 39.35' SW TO A CONCRETE NAIL & WASHER IN THE ROOT OF A 14" DIAMETER OAK TREE
 - 2) 32.55' WEST TO A CONCRETE NAIL & WASHER IN THE TOP OF A POST FOR A SPLIT-RAIL FENCE
 - 3) 47.10' NW TO A CONCRETE NAIL & WASHER IN THE TOP OF A POST FOR A SPLIT-RAIL FENCE
 - 4) 42.00' NORTH TO THE SOUTH LINE OF HOUSE TO THE NORTH AND EAST – EXTENDED
 - 5) 5.0' NORTH TO THE CENTERLINE TRAVELED WY OF COUNTY ROAD 140 EXTENDED TO THE WEST
 - 6) 3.0' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "M"
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 417.42' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 4 ACRE SQUARE TRACT
 - 2) 864.3' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 17.38 ACRE TRACT
 - 3) 417.71' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE 4 ACRE SQUARE TRACT, ATTRIBUTABLE TO GOULD
 - 4) 1,077.60' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE 17.38 ACRE TRACT, ATTRIBUTABLE TO GOULD [GOULD DISTANCE = 1,077.43']
- 18) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 19, 2004 FOR PROJECT NUMBER 04416-02, SURVEY F35004 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A 32.9 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 35-19-11 FOR W. C. BURDEN, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTHEAST CORNER OF SECTION 35-19-11 FROM HIS EXISTING REFERENCE TIES ON FILE IN THE COUNTY ENGINEERS OFFICE DATED JANUARY 2003.

HIS TIES ARE ON PAGE 5

- 1) 42.00' NORTH TO THE SOUTH LINE OF THE HOUSE TO THE NORTH AND EAST EXTENDED WEST
- 2) 32.55' WEST TO A CONCRETE NAIL & WASHER IN THE TOP OF A POST FOR A SPLIT RAIL FENCE
- 3) 47.10' NW TO A CONCRETE NAIL & WASHER IN THE TOP OF A POST FOR A SPLIT RAIL FENCE
- 4) 3.0' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "M" NORTH-SOUTH
- 5) 5.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 140 TO THE EAST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.56' SOUTH TO THE P.O.B. OF THE 32.9 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT 20.00' WEST
- 2) 2,662.36' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 35-19-11

- 19) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 30, 2005, FOR PROJECT NUMBER 05313-02, SURVEY F36009 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A SURVEY OF THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-11 FOR JAYLENE ARNETT, SAID THAT **HE FOUND THE 5/8" REBAR** AT THE NORTHWEST CORNER OF SECTION 36-19-11 FROM HIS EXISTING TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE DATED NOVEMBER 2004.

- 1) 38.20' SW TO A 40 D AND WASHER IN A 16" OAK TREE
- 2) 81.85' NW TO A 40 D AND WASHER IN A 20" HACKBERRY TREE
- 3) 42.0' NORTH TO THE SOUTH LINE OF A HOUSE EXTENDED
- 4) 27.10' NE TO THE TOP CENTER OF THE NORTH END OF A CORRUGATED METAL PIPE CULVERT
- 5) 2.5' NORTH TO THE CENTERLINE TRAVELED WAY OF ROAD 140 TO THE EAST
- 6) 6.5' WEST TO THE CENTERLINE TRAVELED WAY OF ROAD "M" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,633.84' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 36-19-11 FROM RICE IN 1883
- 2) 3,959.55' EAST TO THE THEORETICAL POSITION FOR THE NORTH 1/16TH CORNER OF THE NE1/4 OF SECTION 36-19-11
- 3) 5,286.26 EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 36-19-11 ON THE RANGE LINE
- 4) 2,662.43' SOUTH TO THE 1/2" REBAR HE FOUND AT THE WEST 1/4 CORNER OF SECTION 36-19-11
- 5) 5,284.29' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 36-19-11 ON THE TOWNSHIP LINE

- 20) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 10, 2007 FOR PROJECT NUMBER 07333-02, SURVEY F25004 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE SURVEY OF AN 8.15 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 25-19-11 FOR BRYAN WHITMORE, SAID THAT **HE FOUND THE 5/8" REBAR** AT THE SOUTHWEST CORNER OF SECTION 25-19-11 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED SEPTEMBER 2005.

- 1) 38.20' SW TO A 40 D AND WASHER IN A 16" OAK TREE
- 2) 81.85' NW TO A 40 D AND WASHER IN A 20" HACKBERRY TREE
- 3) 42.0' NORTH TO THE SOUTH LINE OF A HOUSE EXTENDED
- 4) 27.10' NE TO THE TOP CENTER OF THE NORTH END OF A CORRUGATED METAL PIPE CULVERT

HIS TIES ARE CONTINUED ON PAGE 6

- 5) 2.5' NORTH TO THE CENTERLINE TRAVELED WAY OF ROAD 140 TO THE EAST
 - 6) 6.5' WEST TO THE CENTERLINE TRAVELED WAY OF ROAD "M" NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.30' EAST TO THE 1/2" REBAR HE FOUND [GOULD] AT THE SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 25-19-11, BEING THE SOUTHWEST CORNER OF THE 8.15 ACRE TRACT
- 2) 1,779.30' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTH-EAST CORNER OF THE 8.15 ACRE TRACT
- 3) 2,633.84' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 25-19-11, BEING THE SOUTHEAST CORNER OF THE REMAINDER OF THE GOULD TRACT

- 21) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 2, 2008 FOR PROJECT NUMBER 08253-02, SURVEY F36010 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHWEST QUARTER OF SECTION 36-19-11 FOR JOHN & NORMA WIEDMER, SAID THAT **HE FOUND THE 5/8" REBAR** AT THE NORTHWEST CORNER OF SECTION 36-19-11 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED DECEMBER 2007.

- 1) 38.20' SW TO A 40 D NAIL & WASHER IN A 16" OAK TREE
- 2) 81.85' NW TO A 40 D NAIL & WASHER IN A 20" HACKBERRY TREE
- 3) 42.0' NORTH TO THE SOUTH LINE OF A HOUSE EXTENDED
- 4) 27.10' NE TO THE TOP CENTER OF THE NORTH END OF A CORRUGATED METAL PIPE CULVERT
- 5) 4' NORTH TO THE CENTERLINE TRAVELED-WAY OF COUNTY ROAD 140 TO THE EAST
- 6) 3' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "M" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.11' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SEC. 36-19-11, FROM A PRIOR SURVEY IN 2007
- 2) 1,331.08' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 36-19-11
- 3) 1,996.62' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF THE SW1/4 OF SECTION 36-19-11
- 4) 2,662.16' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 36-19-11

- 22) JOSHUA L. JUNGHANS, L.S. 1488, OF KAW VALLEY ENGINEERING, INC. IN A LAND SURVEY REFERENCE REPORT DATED JUNE 25, 2014 FOR PROJECT NUMBER F14S0049, THE SURVEY OF TWO TRACTS IN THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 25-19-11 FOR LORETTA McFARLAND, SURVEY F25005 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11, SAID THAT **HE FOUND THE 5/8" IRON BAR WITH ILLEGIBLE CAP** AT 0.1 FOOT BELOW THE SURFACE AT THE SOUTHWEST CORNER OF SECTION 25-19-11 USING A MAGNETIC LOCATOR AND MAPS. HE SENT THE FOLLOWING HORIZONTAL TIES:

- 1) 25.2' SE TO THE SOUTH END TOP OF A 12" CMP
- 2) 27.1' NE TO THE NORTH END TOP OF A 12" CMP
- 3) 38.6' SW TO A MAG NAIL SET IN THE EAST FACE OF AN 18" TREE
- 4) 3' WEST TO THE CENTERLINE OF COUNTY ROAD "M" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,657.32' NORTH TO THE 5/8" BAR WITH ILLEGIBLE CAP HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 25-19-11
- 2) 515.00' EAST TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE SOUTHWEST CORNER OF TRACT "A", AS WITNESSED BY THE 1/2" X 24" REBAR

WITH "KVE CLS 20" CAP HE SET AT 25 FEET NORTH ON THE NORTH RIGHT-OF-WAY LINE OF COUNTY ROAD 140

- 3) 917.20' EAST TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET AT THE SOUTHWEST CORNER OF TRACT "B", AS WITNESSED BY THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET AT 25 FEET NORTH ON THE NORTH RIGHT-OF-WAY LINE OF COUNTY ROAD 140
- 4) 1,319.40' EAST TO THE 1/2" BAR HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 25-19-11, AS WITNESSED BY THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET AT 25 FEET NORTH ON THE NORTH RIGHT-OF-WAY LINE OF COUNTY ROAD 140. THIS 1/16TH CORNER IS ALSO THE SOUTHEAST CORNER OF TRACT "B".

NORTHWEST CORNER SECTION 36-19-11