

**WEST 1/16TH CORNER NORTHEAST QUARTER OF SECTION 36, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 30, 2005, FOR PROJECT NUMBER 05313-02, SURVEY F36009 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A SURVEY OF THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-11 FOR JAYLENE ARNETT, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE WEST 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 36 ON TRUE LINE AND HALFWAY BETWEEN THE NORTH QUARTER CORNER AND THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 36.

- 1) 25.40' SSE TO A CONCRETE NAIL & WASHER IN A CORNER POST
- 2) 30.85' NE TO A CONCRETE NAIL & WASHER IN A CORNER POST
- 3) 30.30' NW TO THE WEST END AT THE OF TOP CENTER OF A STEEL CASING FOR A DRIVE ENTRANCE
- 4) 16.5' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- 5) 17.0' WEST TO THE EAST LINE OF A HOUSE EXTENDED
- 6) 3.3' NORTH TO THE CENTERLINE OF TRAVELED-WAY EAST-WEST [COUNTY ROAD 137]

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,327.20' NORTH TO THE STONE SET BY RICE IN 1883 FOUND AT THE NORTH 1/4 CORNER OF SECTION 36
- 2) 1,317.20' SOUTH TO THE THEORETICAL POSITION FOR THE CENTER OF SEC. 36
- 3) 3,957.14' SOUTH TO A 5/8" REBAR WITH A LYON COUNTY CAP SET FOR THE SOUTH 1/4 CORNER OF SECTION 36
- 4) 1,323.54' EAST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE CENTER OF THE NE1/4 OF SECTION 36
- 5) 2,647.08' EAST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE 1/16TH CORNER ON THE EAST SIDE OF THE NE1/4 OF SECTION 36

2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 2, 2008 FOR PROJECT NUMBER 08253-02, SURVEY F36010 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHWEST QUARTER OF SECTION 36-19-11 FOR JOHN & NORMA WIEDMER, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE EAST 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 36 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.

- 1) 25.40' SSE TO A CONCRETE NAIL & WASHER IN A CORNER POST
- 2) 30.85' NE TO A CONCRETE NAIL & WASHER IN A CORNER POST
- 3) 30.30' NW TO THE WEST END AT THE TOP CENTER OF A STEEL CASING FOR A DRIVE ENTRANCE
- 4) 16.5' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- 5) 3.3' NORTH TO THE CENTERLINE TRAVELED-WAY OF ROAD 137 EAST-WEST
- 6) 17.0' WEST TO THE EAST LINE OF A HOUSE EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,316.06' WEST TO A 5/8" REBAR WITH LYON COUNTY CAP SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 36
- 2) 1,581.06' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTHWEST CORNER OF THE "EXCEPTED TRACT"
- 3) 1,975.25' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF THE SW1/4 OF THE NW1/4 OF SECTION 36
- 4) 2,634.45' WEST TO A 5/8" REBAR WITH LYON COUNTY CAP SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 36
- 5) 1,327.09' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 36

HIS INFORMATION IS CONTINUED ON PAGE 2

- 6) 3,957.27' SOUTH TO A 1/2" REBAR FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 36

WEST SIXTEENTH CORNER NORTHEAST QUARTER SECTION 36-19-11