

**WEST 1/16TH CORNER NORTHWEST QUARTER OF SECTION 36, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

- 1) DAN J. MELANDER, L.S. 504 AND RICHARD L. THOMPSON, L.S. 505, IN SURVEY SR #36001 IN THE LARGE SURVEY DRAWER FOR SECTIONS 17-36 IN TOWNSHIP 19-11 DATED AUGUST 7, 1971, SHOWS ON THEIR SURVEY DRAWING A **STEEL PIN** AT THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 36, BUT THERE ARE NO TIES ON THE SURVEY.

THEIR DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,319.27' NORTH TO A STEEL PIN AT THE NORTHWEST CORNER OF SECTION 36
 - 2) 1,320.0' EAST TO A STEEL PIN AT THE CENTER OF THE NORTHWEST 1/4 OF SECTION 36
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 2, 2008 FOR PROJECT NUMBER 08253-02, SURVEY F36010 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHWEST QUARTER OF SECTION 36-19-11 FOR JOHN & NORMA WIEDMER, SAID THAT **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 36 ON TRUE LINE AND HALFWAY BETWEEN THE NORTHWEST CORNER AND THE WEST QUARTER CORNER OF SECTION 36.
- 1) 30.0' ESE TO A CONCRETE NAIL & BOTTLE CAP IN A CORNER FENCE POST
 - 2) 83.7' NNE TO A CONCRETE NAIL & BOTTLE CAP IN A BRACE POST
 - 3) 26.6' ESE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) 33.0' NORTH TO THE CENTERLINE TRAVELED-WAY OF ROAD 137 TO THE EAST
 - 5) 3.7' WEST TO THE CENTERLINE TRAVELED-WAY OF ROAD "M" NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:**
- 1) 1,331.08' NORTH TO A 5/8" REBAR FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 36
 - 2) 665.54' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF THE NW1/4 OF SECTION 36
 - 3) 1,331.08' SOUTH TO A 1/2" REBAR FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 36
 - 4) 659.20' EAST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTHEAST CORNER OF EH NW1/4 OF THE SW1/4 OF THE NW1/4 OF SECTION 26
 - 5) 1,053.39' EAST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTHWEST CORNER OF THE "EXCEPTED TRACT"
 - 6) 1,318.39' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 36
 - 7) 2,634.45' EAST TO A 1/2" REBAR WITH HIS "LS 752" CAP FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 36

WEST SIXTEENTH CORNER NORTHWEST QUARTER SECTION 36-19-11