

**NORTHWEST CORNER SECTION 02, TOWNSHIP 19 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 69 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 12" X 3"** FOR THE CORNER TO SECTIONS 2 & 3-19-12 ON THE TOWNSHIP LINE ON DECEMBER 11, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 17" X 12" X 3" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 2-19-12
- 2) 80.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 21" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-19-12
- 3) 37.70 CHAINS SOUTH TO THE 20" X 18" X 1-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 3-19-12
- 4) 77.70 CHAINS SOUTH TO THE 20" X 16" X 1-3/4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-19-12

- 2) JAMES MEANS, COUNTY SURVEYOR FROM 1865 TO 1867, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 57 [PACKET 394 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY P. B. PLUMB AND OTHERS FOR A ROAD FROM THE LAWRENCE AND EMPORIA ROAD EAST ON THE TOWNSHIP LINE TO INTERSECT THE ROAD FROM FOREST HILL TO WATERLOO THAT WAS SURVEYED ON JANUARY 25, 1866, AND ESTABLISHED IN THE COMMISSIONERS JOURNAL ON PAGE 122 ON FEBRUARY 12, 1866, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 2-19-12 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY. **[NOTE:** HE HAD MISLABELED THE SECTION CORNERS ON HIS DRAWING – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE TOWNSHIP LINE TO THE STONE WHERE THE LAWRENCE AND EMPORIA ROAD CROSSES THE NORTH LINE OF TOWNSHIP 19 [RANGE 11] TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE TOWNSHIP LINE WITH AN ANGLE TO THE SOUTHERLY AROUND BADGER CREEK IN THE NORTHEAST 1/4 OF SECTION 2-19-12 AND THE NORTHWEST 1/4 OF SECTION 1-19-12 AND RETURNS TO THE TOWNSHIP LINE AND CONTINUES EAST ON THE TOWNSHIP LINE TO THE ROAD FROM FOREST HILL TO WATERLOO AT THE TERMINUS OF THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 41 DATED DECEMBER 12, 1882 FOR A ROAD BETWEEN SECTIONS 2 AND 3 IN TOWNSHIP 19, RANGE 12 FOR THOMAS I. JONES, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 2-19-12 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY. THERE IS NO WIDTH RECORDED ON THIS ROAD SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 160 RODS TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 2-19-12; THEN CONTINUES SOUTH ON THE SECTION LINES FOR 160 RODS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 2-19-12 TO COMMENCE THIS ROAD SURVEY
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD 197 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 374 TO 376 PETITION BY THOMAS I. JONES AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-13 THAT HE SURVEYED ON DECEMBER 12, 1882, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON JANUARY 4, 1883 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOAR OF COUNTY COMMISSIONERS, AND

RECORDED ON JANUARY 22, 1883 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST OF SECTION 2-19-12 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY.

HIS NOTES SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 160 RODS TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 2-19-12; THEN CONTINUES SOUTH ON THE SECTION LINES FOR 160 RODS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 2-19-12 TO COMMENCE THIS ROAD SURVEY
  
- 5) MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, FOR R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 71, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 71 DATED OCTOBER 9 THROUGH NOVEMBER 1, 1884 ORDERED BY N. J. WIRT TO SURVEY THE NORTHEAST 1/4 OF SECTION 4-19-12, SAID THAT **HE FOUND THE GOVERNMENT STONE** AT THE NORTHEAST CORNER OF SECTION 3-19-12 ON THE TOWNSHIP LINE. HE RAN THE TOWNSHIP LINE FROM THIS GOVERNMENT STONE WEST TO THE GOVERNMENT STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-19-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 5,278' WEST ON THE TOWNSHIP LINE TO THE 3" X 5" X 18" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 4-19-21
  - 2) 7,917' WEST ON THE TOWNSHIP LINE TO THE 3" X 6" X 16" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 4-19-12
  - 3) 10,556' WEST ON THE TOWNSHIP LINE TO THE TEMPORARY STAKE HE SET FOR THE NORTHWEST CORNER OF SECTION 4-19-12
  - 4) 13,195' WEST ON THE TOWNSHIP LINE TO THE GOVERNMENT STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-19-12
  
- 6) REA BOOK 31 ON PAGE 20 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE SOUTH EAST CORNER OF SECTION 34-18-12 ON THE TOWNSHIP LINE AT 5,280 FEET EAST OF THE SOUTHWEST CORNER OF SECTION 34-18-12 ON JUNE 19, 1939. THEY SAID THAT THIS CORNER IS A LITTLE EAST OF A WIRE FENCE TO THE NORTH AND A LITTLE WEST OF THE CENTER OF THE ROAD TO THE SOUTH.
  - 1) 32' NE TO A WITNESS PIN
  - 2) 34' NW TO A WITNESS PIN
  
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-12 SHOWS A **REA PIN** AT THE "SW CORNER SECTION 35-18-12" ON THE TOWNSHIP LINE.
  - 1) 32' NE TO A WITNESS [REA]
  - 2) 34' NW TO A WITNESS [REA]
  
- 8) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F35006 IN THE SURVEY FILE FOR TOWNSHIP 18-12 DATED MAY 12, 1970 FOR A SURVEY TO LOCATE THE CORNERS AND LINES OF THE SOUTHWEST QUARTER AND THE WEST HALF OF THE SOUTHEAST QUARTER OF SECTION 35-18-12, SHOWS ON HIS DRAWING AN **IRON PIN** AT THE SOUTHWEST CORNER OF SECTION 35-18-12 ON THE TOWNSHIP LINE. THERE ARE NO TIES ON THE SURVEY.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,656' NORTH TO THE CORNER POST HE SET IN CONCRETE AT THE WEST 1/4 CORNER OF SECTION 35-18-12
  - 2) 2,641' EAST ON THE TOWNSHIP LINE TO THE 1/2" ROUND IRON PIN AT THE SOUTH 1/4 CORNER OF SECTION 35-18-12
  - 3) 3,961.5' EAST ON THE TOWNSHIP LINE TO THE 1/2" ROUND IRON PIN AT THE SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 35-18-12

- 4) 5,282' EAST ON THE TOWNSHIP LINE TO THE STONE IN PLACE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-18-12
  
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 5, 1989, FOR JOB NUMBER 89044, SAID THAT **HE FOUND A 1/2" REBAR** AT THE NORTHEAST CORNER OF SECTION 3-19-12 ON THE TOWNSHIP LINE FROM INFORMATION IN THE COUNTY ENGINEERS OFFICE.
  - 1) IN LINE WITH A FENCE TO THE NORTH
  - 2) IN THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
  - 3) 25.3' NORTH TO A LINE OF FENCE TO THE EAST
  - 4) 32.6' SOUTH TO A LINE OF FENCE TO THE EAST
  - 5) 35.4' EAST TO A LINE OF FENCE TO THE SOUTH
  
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 22, 1992, FOR JOB NUMBER 92277-02, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE SOUTHEAST CORNER OF SECTION 34-18-12 ON THE TOWNSHIP LINE FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED MAY 1989.
  - 1) 66.6' SSE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 2) 35.5' NW TO A PK NAIL & SHINER IN A POWER POLE
  - 3) 49.1' SW TO A PK NAIL & WASHER IN A POWER POLE
  - 4) 8.8' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE SOUTH
  - 5) IN LINE WITH A FENCE TO THE NORTH
  
- 11) ROBERT J. BORSICK. L.S. 1180, OF BARTLETT & WEST ENGINEERS, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 12, 2006 FOR PROJECT NUMBER 15340-001, A BOUNDARY SURVEY FOR WESTAR IN THE NORTHEAST 1/4 OF SECTION 34-18-12, LARGE SURVEY SR#34001 IN THE SURVEY DRAWER FOR TOWNSHIP 18-12 *FOR INFORMATIONAL PURPOSES ONLY*, SAID THAT **HE FOUND THE 1/2" REBAR AT 0.3 FEET DEEP** AT THE SOUTHEAST CORNER OF SECTION 34-18-12 ON THE TOWNSHIP LINE FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE. THE FOLLOWING TIES ARE **HORIZONTAL TIES:**
  - 1) 33.83' NW TO A PK NAIL & WASHER IN A GUY POLE
  - 2) 25.5' NORTH TO A MAG NAIL & WASHER IN A CORNER FENCE POST
  - 3) 50.74' WSW TO A MAG NAIL & WASHER IN A GATE POST
  - 4) 47.28' SE TO A MAG NAIL & WASHER IN A CORNER FENCE POST
  - 5) 9' EAST TO THE CENTERLINE OF COUNTY ROAD "T"
  - 6) IN THE CENTERLINE OF COUNTY ROAD 190**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
  - 1) 2,639.88' WEST ON THE TOWNSHIP LINE TO THE FOUND DRILL HOLE IN A BRIDGE DECK AT THE SOUTH 1/4 CORNER OF SECTION 34-18-12
  - 2) 2,652.79' NORTH TO THE 1/2" REBAR WITH "L.S. 667" CAP HE FOUND AT THE EAST 1/4 CORNER OF SECTION 34-18-12
  - 3) 5,306.34' NORTH TO THE 1/2" REBAR WITH "L.S. 752" CAP HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-18-12

NORTHWEST CORNER SECTION 02-19-12