

CENTER OF SECTION 05, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) LLOYD J. DOBLER, L.S. 541, IN SURVEY F05003 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR THE SURVEY OF A 3.689 ACRE TRACT IN THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 5-19-12 DATED FEBRUARY 1, 1978, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE NORTHWEST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 5, BUT THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILE.
 - 1) 1,382.90' SOUTH TO A 1/2" IRON PIN SET FOR THE NORTHWEST CORNER OF THE 3.689 ACRE TRACT
 - 2) 1,885.50' SOUTH TO A 1/2" IRON PIN SET FOR THE SOUTHWEST CORNER OF THE 3.689 ACRE TRACT
 - 3) 2,648.90' SOUTH TO THE SOUTHWEST CORNER OF THE W1/4 OF THE SE1/4 OF SECTION 5
 - 4) 2,617.14' EAST TO AN IRON PIN SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 5 [**NOTE: THIS DISTANCE IS NOT CORRECT FOR THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SE1/4 AS IT IS ALMOST A HALF MILE!**]

- 2) STEVEN S. BROSEMER, L.S. 752, IN A SECTION CORNER REPORT DATED JUNE 22, 1982, SAID THAT **HE FOUND A 5/8" REBAR** OF UNCERTAIN ORIGIN AT THE CENTER OF SECTION 5, AND HE ACCEPTED IT AS THE CORNER.
 - 1) 35.2' NE TO A SPIKE IN THE SIDE OF A GATE POST
 - 2) IN LINE WITH A WIRE FENCE TO THE EAST
 - 3) 30.5' WEST TO A LINE OF POWER POLES TO THE SOUTH
 - 4) 99.4' SSW TO A SPIKE IN A POWER POLE
 - 5) 2,648.1' SOUTH TO THE SOUTH 1/4 CORNER OF SECTION 05
 - 6) 2,541.9' NORTH TO THE NORTH 1/4 CORNER OF SECTION 05

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING DISTANCES:

 - 1) 2,541.9' NORTH TO THE NORTH 1/4 CORNER OF SECTION 5
 - 2) 2,648.1' SOUTH TO THE SOUTH 1/4 CORNER OF SECTION 5

- 3) AARON C. DAVIS, L.S. 1368, IN A SECTION CORNER REPORT DATED FEBRUARY 05, 2004, FOR PROJECT 03515-02, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE CENTER OF SECTION 5 FROM EXISTING TIES IN THE COUNTY ENGINEER'S OFFICE.
 - 1) 30.00' EAST TO A 1/2" REBAR WITH A "LS 752" CAP [HORIZONTAL TIE]
 - 2) IN LINE WITH A FENCE TO THE EAST EXTENDED
 - 3) 99.40' SW TO A 60 D SPIKE IN A POWER POLE
 - 4) 39.90' NE TO A 60 D SPIKE IN THE TOP CENTER OF A BRACE POST
 - 5) 33.95' EAST TO A 60 D SPIKE IN THE TOP OF A CORNER FENCE POST
 - 6) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "P5"

CENTER OF SECTION 05-19-12