

**NORTH 1/16<sup>TH</sup> CORNER SOUTHEAST QUARTER SECTION 08, TOWNSHIP 19 SOUTH, RANGE 12 EAST**

- 1) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 48, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 47 DATED MAY 28, 1870 TO DIVIDE THE SOUTHEAST 1/4 OF SECTION 8-19-12 INTO EQUAL PARTS BY A LINE RUNNING NORTH & SOUTH, SAID THAT **HE SET A LIMESTONE** FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH SIDE OF THE SOUTHEAST 1/4 OF SECTION 8 ON LINE AND HALFWAY BETWEEN THE STONES THAT HE FOUND AT THE CENTER CORNER AND AT THE 1/4 CORNER ON THE EAST SIDE OF SECTION 8 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:

- 1) 1,318' WEST TO THE STONE FOUND AT THE CENTER OF SECTION 8
  - 2) 1,318' EAST TO THE STONE FOUND AT THE 1/4 CORNER ON THE EAST SIDE OF SECTION 8
  - 3) 2,652-1/2' SOUTH TO THE STONE ALREADY ESTABLISHED AT THE 1/2/4/ CORNER ON THE SOUTH LINE OF THE SE1/4 OF SECTION 8
- 2) STEVEN S. BROSEMER, L.S. 752, IN FOR SURVEY F08010 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR TWO TRACTS IN THE EAST HALF OF THE SOUTHEAST QUARTER OF SECTION 8-19-12, BEING NORTH OF OLD HIGHWAY 50, EAST OF THE CENTER OF THE NEOSHO RIVER, AND SOUTH OF I-35 HIGHWAY DATED APRIL 27, 1984 AND RECORDED IN VOLUME 409 ON PAGE 112 IN THE REGISTER OF DEEDS OFFICE ON JUNE 6, 1984 SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE NORTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 8 TO BE ON LINE AND HALFWAY BETWEEN THE CENTER CORNER AND THE EAST 1/4 CORNER OF SECTION 8, BUT HE DID **NOT** MONUMENT THE POSITION ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,315.22' WEST TO A #4 SQUARE REBAR FOUND AT THE CENTER OF SECTION 8
- 2) 1,315.22' EAST TO A #4 SQUARE REBAR FOUND AT THE EAST 1/4 CORNER OF SECTION 8
- 3) 2,658.17' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 8

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 08-19-12