

NORTHWEST CORNER SECTION 08, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 542 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A POST** FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-19-12, FROM WHICH:
 - 1) A WALNUT TREE 9" IN DIAMETER BEARS N. 56°05' E. AT 39 LINKS DISTANCE
 - 2) A HACKBERRY TREE 18" IN DIA. BEARS N. 36°25' W. AT 22 LINKS DISTANCE
 - 3) A HACKBERRY TREE 24" IN DIAMETER BEARS S. 35° E. AT 23 LINKS DISTANCE
 - 4) AN ELM TREE 30" IN DIAMETER BEARS S. 47°40' W. AT 55 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) 40.00 CHAINS NORTH TO THE 18" X 15" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 6-19-12
 - 2) 78.40 CHAINS NORTH TO THE 12" X 9" X 7" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-19-12 ON THE TOWNSHIP LINE
 - 3) 39.85-1/2 CHAINS EAST TO A 30" X 10" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-19-12
 - 4) 79.71 CHAINS EAST TO A 28" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-19-12

- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 21 RECORDED IN SURVEY BOOK "A" ON PAGES 19 & 20 DATED JANUARY 22, 1859, A **PERMANENT SURVEY** TO ESTABLISH THE BOUNDARIES OF A 10 ACRE LOT OF LAND SOLD BY C. V. ESKRIDGE TO JOHN DUNN IN SECTION 7-19-12 SAID THAT **HE FOUND THE STONE POST FROM THE GOVERNMENT SURVEY** AT THE NORTHEAST CORNER OF SECTION 7-19-12 ON THIS **PERMANENT SURVEY**. HE MARKED THE FOLLOWING WITNESS TREES:
 - 1) A 20" DIAMETER HACKBERRY TREE IS S. 45° E. AT 23 LINKS
 - 2) A 30" DIAMETER ELM TREE IS S. 36° W. AT 54 LINKS
 - 3) A 16" DIAMETER HACKBERRY TREE IS N. 50-3/4° W. AT 39 LINKS
 - 4) A 10" DIAMETER WALNUT TREE IS N. 46-1/4° E. AT 22 LINKS

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 47 RECORDED IN SURVEY BOOK "A" ON PAGE 143 AND MAY 4 & 5, 1868 FOR A SURVEY OF LAND OWNED BY HILLERMAN, SMITH, LOGAN AND OTHERS, BEING SECTION 7-19-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 7-19-12 ON THIS SURVEY.

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 37, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 37 DATED MAY 31, 1870 TO ESTABLISH THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-19-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 6-19-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,626' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 6-19-12
 - 2) 5,120' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-19-12 ON THE RANGE LINE

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 238 DATED JANUARY 26, 1880 TO PERMANENTLY ESTABLISH THE NORTH 1/4 CORNER OF SECTION 7-19-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 7-19-12, SET IN THE GROUND AND WITNESSED BY SEVERAL WITNESS TREES, ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 2,640' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 7-19-12
 - 2) 5,102' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-19-12 ON THE RANGE LINE
- 6) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 9 AT THE REQUEST OF JACK FOWLER TO LOCATE THE NORTHERN BOUNDARY OF A TRACT IN SECTION 8-19-12 FOR CAMP ALEXANDER, SAID THAT HE DUG FOR THE STONE AT THE NORTHWEST CORNER OF SECTION 8-19-12, BUT HE DID **NOT** FIND THE STONE. **HE SET A 1-1/2" PIPE** FOR THE NORTHWEST CORNER OF SECTION 8-18-12 ON A LINE FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-19-12 ON THE RANGE LINE OVER THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 7-19-12 AND AT A PRORATED DISTANCE FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-19-12 EAST TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 11-19-12 ON THIS **PERMANENT SURVEY**. THE SURVEY BEGAN APRIL 6, 1955 AND WAS DELAYED DUE TO HIGH WATER AND AT ONE TIME DUE TO LACK OF COMPETENT HELP AND WAS COMPLETED ON MAY 5, 1955. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE BOOKS.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,614.58' WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 7-19-12
 - 2) 5,108.83' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-19-12 ON THE RANGE LINE
 - 3) 700.26' EAST TO THE 1-1/2" PIPE HE DROVE FOR A TRACT CORNER
 - 4) 5,271.62' EAST TO THE LOCATION FOR THE CALCULATED LOCATION FOR THE NORTHEAST CORNER OF SECTION 8-19-12
 - 5) 21,021.92' BY HIS CHAINING NOTES TO THE STONE HE FOUND IN PLACE AT THE NORTHEAST CORNER OF SECTION 11-91-12

NORTHWEST CORNER 08-19-12