

**WEST 1/16TH CORNER NORTHEAST QUARTER SECTION 08, TOWNSHIP 19 SOUTH,
RANGE 12 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 17 RECORDED IN SURVEY BOOK "A" ON PAGE 114 DATED FEBRUARY 19, 1868 TO SURVEY RICHARD RICH'S LAND, BEING THE SOUTH 1/4 OF THE SOUTH 1/2 AND 30 ACRES OF THE NORTH 1/2 OF THE SOUTH 1/2 OF THE NORTHWEST 1/4 OF SECTION 8-19-12, SAID THAT **HE SET A STONE POST** FOR THE EAST 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 8-19-12 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS, 5 LINKS SOUTH TO THE CENTER CORNER OF SECTION 8-19-12
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 65 DATED AUGUST 39 1883 FOR A ROAD IN TOWNSHIP 19-12 FOR D. M. MAY, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/8TH CORNER OF THE NORTHEAST 1/4 OF SECTION 8-19-12. HE USED THIS STONE TO SET A STONE MARKED "R+" FOR THE **ASSUMED** SOUTH 1/4 OF SECTION 5-19-12 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 80 RODS NORTH TO THE STONE MARKED "R+" HE SET FOR THE **ASSUMED CORNER** FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 5-19-12 TO BEGIN THIS ROAD SURVEY
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 293 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 542 TO 546 PETITIONED BY D. M. MAY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-12 [PACKET 463 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 14, 1883, AND WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 4, 1883 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 13, 1883 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE 1/8TH CORNER ON THE WEST SIDE OF THE NORTHEAST 1/4 OF SECTION 8-19-12. HE USED THIS 1/8TH STONE TO SET A STONE MARKED "R+" FOR THE ASSUMED SOUTH 1/4 CORNER OF SECTION 5-19-12 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 2) 80 RODS NORTH TO THE STONE MARKED "R+" HE SET FOR THE **ASSUMED CORNER** FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 5-19-12 TO BEGIN THIS ROAD SURVEY
- 4) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 9 AT THE REQUEST OF JACK FOWLER TO LOCATE THE NORTHERN BOUNDARY OF A TRACT IN SECTION 8-19-12 FOR CAMP ALEXANDER, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND AN IRON PIN IN PLACE** AT 1,320' SOUTH OF HIS LOCATION FOR THE NORTH 1/4 CORNER OF SECTION 8-19-12 ON THIS **PERMANENT SURVEY**. HE NOTED THAT THIS IRON PIN WAS THE SOUTHEAST CORNER OF THE SURVEYED TRACT. THE SURVEY BEGAN APRIL 6, 1955 AND WAS DELAYED DUE TO HIGH WATER AND AT ONE TIME DUE TO LACK OF COMPETENT HELP AND WAS COMPLETED ON MAY 5, 1955. THERE ARE NO TIES ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 660' NORTH TO THE IRON PIN HE FOUND IN PLACE AT THE NORTHEAST TRACT CORNER
- 2) 1,320' NORTH TO THE LOCATION FOR THE NORTH 1/4 CORNER OF SEC. 8-19-12

- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-12 SHOWS A **“MONUMENT”** AT THE “SE CORNER NE1/4 NW1/4 SECTION 0-19-12”. THERE IS NO DESCRIPTION OF THE MONUMENT ON THIS PAGE.
- 1) 32' NE TO THE SOUTH END OF A FENCE FROM THE NORTH [OSAGE POST]
 - 2) 19.4' NE TO A CROOKED POST
 - 3) 14.5' SE TO AN OSAGE POST IN CONCRETE
 - 4) 19.6' NORTH OF AN OSAGE POST IN CONCRETE

WEST SIXTEENTH CORNER NORTHEAST QUARTER 08-19-12