

NORTHWEST CORNER SECTION 10, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 527 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 15" X 3"** FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-19-12.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 20" X 14" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-19-12
- 2) 77.85 CHAINS NORTH TO THE 28" X 10" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-19-12 ON THE TOWNSHIP LINE
- 3) 39.84 CHAINS EAST TO THE 19" X 16" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 10-19-12
- 4) 79.68 CHAINS EAST TO THE 20" X 16" X 1-3/4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-19-12

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 157 DATED MAY 23, 1878, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 3-19-12 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 1,300 FEET TO THE FOREST HILL AND AMERICUS ROAD AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-19-12 TO BEGIN THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882,, IN A ROAD SURVEY FOR ROAD NUMBER 30 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 17 THROUGH 20 PETITIONED BY D. A. HUNTER AND OTHERS FOR A ROAD IN TOWNSHIP 19-12 [PACKET 285 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 23, 1878, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, EXCEPTING THAT PORTION THE HEDGE FENCE ALONG THE NORTH LINE OF THE NORTHWEST 1/4 OF SECTION 11-19-12 SHALL BE THE NORTH AND SOUTH LINES OF SAID ROAD, ON JULY 3, 1878 AS NOTED BY D. S. GILMORE, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED TO BY WILLIAM F. EWING, COUNTY CLERK, AND RECORDED ON JANUARY 4, 1900 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 3-19-12 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 1,300 FEET TO THE FOREST HILL AND AMERICUS ROAD AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-19-12 TO BEGIN THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 110 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 26 TO 28 PETITIONED BY C. H. ELDRIDGE AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 18-12 & 19-12 [PACKET 356 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 26, 1881, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON APRIL 16, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 5, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 9-19-12 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-18-12 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 9-19-12 TO COMMENCE THIS ROAD SURVEY
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 216 DATED MARCH 26, 1881, FOR A ROAD SURVEY IN TOWNSHIPS 18-12 & 19-12 APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 9-19-12 ON THIS ROAD SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 9-19-12 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-18-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 6) MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, FOR R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 71, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 71 DATED OCTOBER 9 THROUGH NOVEMBER 1, 1884 ORDERED BY N. J. WIRT TO SURVEY THE NORTHEAST 1/4 OF SECTION 4-19-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 4-19-12 ON THIS **PERMANENT SURVEY**. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,619' WEST TO THE 2" X 8" X 11" STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 4-19-12 THAT "CORRESPONDS WITH FENCES"
 - 2) 5,238' WEST TO THE TEMPORARY STAKE HE SET FOR THE SOUTHWEST CORNER OF SECTION 4-19-12
 - 3) 2,640' NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 4-19-12
 - 4) 5,138' NORTH TO THE 3" X 5" X 18" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 4-19-12 ON THE TOWNSHIP LINE
- 7) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 9 AT THE REQUEST OF JACK FOWLER TO LOCATE THE NORTHERN BOUNDARY OF A TRACT IN SECTION 8-19-12 FOR CAMP ALEXANDER, DOES **NOT** MENTION THE NORTHWEST CORNER OF SECTION 10-19-12 ON THIS **PERMANENT SURVEY**. HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-19-12 ON THE RANGE LINE TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 11-19-12. HE MAY HAVE DETERMINED A **THEORETICAL LOCATION** FOR THE NORTHWEST CORNER OF SECTION 10-19-12 AS HE DOES GIVE A DISTANCE BETWEEN THE NORTHWEST AND NORTHEAST SECTION CORNERS. THE SURVEY BEGAN APRIL 6, 1955 AND WAS DELAYED DUE TO HIGH WATER AND AT ONE TIME DUE TO LACK OF COMPETENT HELP AND WAS COMPLETED ON MAY 5, 1955.
- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-12 SHOWS A **1/2" DIAMETER REBAR SET FOR THE REA** AT THE "SW CORNER SECTION 03-19-12".
- 1) 31.4' NW TO A CORNER FENCE POST
 - 2) 30.4' SW TO A CORNER FENCE POST
 - 3) 31.5' NE TO A CORNER FENCE POST
 - 4) 29.9' SW TO A CORNER FENCE POST

CONTINUED ON PAGE 3

- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-12 SHOWS AN **IRON PIN** AT THE "NE CORNER SECTION 09-19-12".
 - 1) 30.50' SE TO A SPIKE IN THE TOP OF A CORNER FENCE POST
 - 2) 33.10' NE TO A SPIKE IN THE TOP OF A CORNER FENCE POST

- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 5, 1989, FOR JOB NUMBER 89044, SAID THAT **HE FOUND A 1/2" REBAR** AT THE SOUTHWEST CORNER OF SECTION 3-19-12.
 - 1) 20.0' NORTH TO A LINE OF FENCE TO THE WEST
 - 2) 22.0' NORTH TO A LINE OF FENCE TO THE EAST
 - 3) 23.0' WEST TO A LINE OF FENCE NORTH-SOUTH
 - 4) 20.0' SOUTH TO A LINE OF FENCE EAST-WEST
 - 5) 23.0' EAST TO A LINE OF FENCE TO THE SOUTH
 - 6) IN THE CENTERLINE TRAVELED WAY OF THE ROADS NORTH-SOUTH-EAST-WEST

NORTHWEST CORNER 10-19-12