

**WEST 1/4 CORNER SECTION 14, TOWNSHIP 19 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 520 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 15-19-12.
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 4, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 4 DATED JANUARY 21, 1870 TO ESTABLISH THE CENTER CORNER OF SECTION 14-19-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 14-19-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 2,658' EAST TO THE OAK POST HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 14-19-12
  - 2) 5,278' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 14-19-12
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 240 DATED FEBRUARY 2, 1880, TO ESTABLISH THE SOUTH LINE OF THE NORTHWEST 1/4 OF SECTION 15-19-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 15-19-12 ON THIS **PERMANENT SURVEY**.
- 4) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 127 DATED MAY 5 & 6, 1882 TO SURVEY A 5 ACRE PIECE IN THE SOUTHEAST CORNER OF SECTION 15-19-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 15-19-12 ON THIS SURVEY.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 35.39 CHAINS SOUTH TO THE STONE HE SET FOR THE NORTHEAST CORNER OF THE 5 ACRE PIECE
  - 2) 40.39 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 15-19-12
- 5) GREGORY ALAN MILES, L.S 667, APPOINTED COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 59 AT THE ORDER OF CLARE PEARSON FOR A SURVEY TO LOCATE AND PERMANENTLY ESTABLISH THE LINES AND CORNERS NECESSARY TO LOCATE THE ROAD EASEMENT ALONG THE EAST LINE OF PEARLIE SMITHS PROPERTY LOCATED IN THE NORTHWEST 1/4 OF SECTION 15-19-12, SAID THAT CLARE PEARSON, PEARLIE SMITH, AND ROSS E. LUDY WERE ALL PRESENT AT THE VIEWING ON JANUARY 13, 1981. HE SAID THAT **HE SET A 1/2" REBAR** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 15-19-12 ON LINE AND HALFWAY BETWEEN THE 1/2" STEEL PIN HE FOUND AT THE SOUTHEAST CORNER OF SECTION 15-19-12 AND HIS CALCULATED POSITION FOR THE NORTHEAST CORNER OF SECTION 15-19-12. THE SURVEY BEGAN JANUARY 13 AND WAS SIGNED MARCH 6, 1981. A NOTE ON THE LEFT PAGE STATES: "ON APRIL 16, 1981, CLARE PEARSON AND HIS ATTORNEY, PEARLIE SMITH AND HIS ATTORNEY, AND GENE LUDY, MET WITH THE COUNTY COMMISSIONERS AT WHICH TIME IT WAS DECIDED TO AMEND THIS PERMANENT SURVEY BY MAKING ROAD EASEMENT A 50-FOOT-WIDE STRIP". AN AMENDED SHEET IS INSERTED IN PERMANENT SURVEY BOOK 2, BUT SHOWS THE ORIGINAL DATE OF MARCH 6, 1981. THERE ARE NO TIES TO THE EAST 1/4 CORNER OF SECTION 15-19-12 ON THE SURVEY OR IN THE SURVEY TIE FILES.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,664.08' NORTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF SECTION 15-19-12 – NOT IDENTIFIED

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,644.08' SOUTH TO THE 1/2" STEEL PIN HE FOUND AT THE SOUTHEAST CORNER OF SECTION 15-19-12
  - 3) 2,637.65' WEST TO THE 1/2" REBAR HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 15-19-12
  - 4) 3,691.90' WEST TO THE 1/2" REBAR HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE ROAD EASEMENT
  - 5) 3,741.90' WEST TO THE 1/2" REBAR HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE ROAD EASEMENT
  - 6) 5,274.07' WEST TO THE 1/2" REBAR HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 15019-12
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 9, 2010 FOR PROJECT NUMBER 10092-02, SURVEY F15002 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR A SURVEY OF THE SOUTH HALF OF THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER FOR DAN FRUIT, SAID THAT **HE FOUND AN AXLE** AT THE EAST 1/4 OF SECTION 15-19-12. HE SAID THAT THE REBAR ATTRIBUTABLE TO MILES WAS **NOT** FOUND, AND THAT THIS CORNER WAS NOT DIRECTLY A PART OF THIS SURVEY.
- 1) THE AXLE IS ON THE NORTH SIDE OF A CORNER FENCE POST
  - 2) IN LINE WITH AN OLD FENCE TO THE SOUTH
  - 3) IN LINE WITH A HEDGE TO THE EAST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,651.94' NORTH TO THE 1/2" REBAR HE FOUND IN A DRILL HOLE IN ASPHALT AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 15-19-12
  - 2) 1,338.05' SOUTH TO THE THEORETICAL POSITION FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 15-19-12
  - 3) 2,007.08' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE N1/2 OF THE SE1/4 OF THE SE1/4 OF THE SE1/4 OF SEC. 15-19-12
  - 4) 2,341.59' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE S1/2 OF THE SE1/4 OF THE SE1/4 OF THE SE1/4 OF SECTION 15-19-12
  - 5) 2,676.10' SOUTH TO THE 5/8" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 15-19-12
  - 6) 1,317.19' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 15-19-12
  - 7) 2,634.38' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 15-19-12
  - 8) 5,270.61' WEST TO THE 1/2" REBAR HE FOUND [MILES] AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 15-19-12

WEST QUARTER CORNER 14-19-12